NOTICE OF
CHANGE

DOD-STD-35-118(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

INSULATION, THERMAL AND ACOUSTIC

TO ALL HOLDERS OF DOD-STD-35-118(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-118(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	23 JUNE 1978
3	18 SEPTEMBER 1992	3	23 JUNE 1978
4	18 SEPTEMBER 1992	4	23 JUNE 1978
5	18 SEPTEMBER 1992	5	23 JUNE 1978
6	18 SEPTEMBER 1992	6	23 JUNE 1978
7	18 SEPTEMBER 1992	7	23 JUNE 1978
8	18 SEPTEMBER 1992	8	23 JUNE 1978
9	18 SEPTEMBER 1992	9	23 JUNE 1978
10	18 SEPTEMBER 1992	10	23 JUNE 1978
11	18 SEPTEMBER 1992	11	23 JUNE 1978
17	18 SEPTEMBER 1992	17	23 JUNE 1978
18	18 SEPTEMBER 1992	18	23 JUNE 1978
19	18 SEPTEMBER 1992	19	23 JUNE 1978
20	23 JUNE 1978 (Reprinted without change)		
75	18 SEPTEMBER 1992	75	23 JUNE 1978
76	18 SEPTEMBER 1992	76	23 JUNE 1978
77	18 SEPTEMBER 1992	77	23 JUNE 1978
78	18 SEPTEMBER 1992	78	23 JUNE 1978
87	23 JUNE 1978 (Reprinted without change)		
88	18 SEPTEMBER 1992	88	23 JUNE 1978
89	18 SEPTEMBER 1992	89	23 JUNE 1978
90	23 JUNE 1978 (Reprinted without change)		
145	18 SEPTEMBER 1992	145	23 JUNE 1978
146	18 SEPTEMBER 1992	146	23 JUNE 1978
147	18 SEPTEMBER 1992	147	23 JUNE 1978
148	18 SEPTEMBER 1992	148	23 JUNE 1978

AMSC N/A AREA EGDS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE	NEW PAGE	DATE
12	18 SEPTEMBER 1992		

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of DOD-STD-35-118(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A455)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	9
	2.1	Government documents	9
	2.2	Non-Government publications	10
	3.	DEFINITIONS	13
	4.	GENERAL REQUIREMENTS	15
	4.1	Introduction	15
	4.2	Specification Requirement Sheet (SRS)	15
	4.3	Configuration	15
	4.3.1	Dimensions	15
	4.3.2	Illustrations	15
	4.4	Units of measure	15
	5	DETAILED REQUIREMENTS	17
	5.1	Introduction	17
	5.2	MSE Formats	17
	5.3	Referenced documents	17
	5.4	Deleted	17
	5.5	Tabulation	20
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	21
	5.6.1	Interrelationship of Codes	21
	5.6.2	Automatic MSE Data	21
	5.6.3	DOD-STD-35 Tables	21

TABLES

Table	I.	Title Index	3
	II.	Deleted	18
	III.	Tabulation Candidates	20

APPENDICES

Appendix	A.	Illustrations	153
	B	Characteristic Code Index	157
		Index	165

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, ACOUSTICAL	815001	AMS3676	GLASS FIBER, RESIN
		AMS3720	HONEYCOMB PAPER 60 LB
		AMS3722	HONEYCOMB PAPER 125 LB
		ASTM E 1042	TROWEL OR SPRAY
INSULATION, BLANKET, SOUND CONTROLLING	815003	MIL-I-7171	AIRCRAFT
INSULATION, BLOCK, SOUND CONTROLLING	815004	ASTM E 1264	TILES AND PANELS, PREFABRICATED
INSULATION, BOARD, SOUND CONTROLLING	815005	ASTM E 1264	TILES AND PANELS PREFABRICATED
		MIL-A-23054	FIBROUS GLASS
INSULATION, FELT, SOUND CONTROLLING	815006	MIL-I-22023	FIBROUS GLASS, FLEXIBLE

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, BLANKET, THERMAL	815008	ASTM C 665	MINERAL FIBER
		MIL-I-2818	FIBROUS MINERAL
		MIL-I-7171	AIRCRAFT
INSULATION, BLOCK, THERMAL	815009	ASTM C 552	CELLULAR GLASS
		ASTM C 523	FIBERBOARD
		MIL-I-2819	MACHINERY AND EQUIPMENT
INSULATION, BOARD, THERMAL	815010	ASTM C 578	POLYSTYRENE
		ASTM C 640	CORK
		HH-I-526	MINERAL FIBER
		ASTM C 728	MINERAL AGGREGATE
		HH-I-530	URETHANE
		ASTM C 552	CELLULAR GLASS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, BOARD, THERMAL	815010 (CONT)	ASTM C 523	FIBERBOARD
		MIL-I-742	FIBROUS GLASS
INSULATION, CLOTH, THERMAL	815011	MIL-I-22344	FIBROUS GLASS
		ASTM D 571/D315	ASBESTOS
INSULATION, COMPOUND, THERMAL	815012	MIL-C-22608	HIGH TEMPERATURE
		ASTM C 195	CEMENT
INSULATION, FELT, THERMAL	815013	MIL-I-16411	GLASS FIBER
		MIL-I-22023	FIBROUS GLASS, FLEXIBLE
		MIL-A-47094	ASBESTOS, PHENOLIC

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z.
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, PAPER, THERMAL	815014	ASTM C 171	BUILDING, FIBER COMPOUND
INSULATION, SHEET AND STRIP, THERMAL	815015	ASTM C 534	FLEXIBLE UNICELLULAR
		MIL-I-14511	CELLULAR PLASTIC
		MIL-P-15280	UNICELLULAR PLASTIC
		MIL-P-16562	SYNTHETIC, RUBBER-LIKE CELLULAR
INSULATION, SLEEVING AND TUBING, THERMAL	815016	ASTM C 534	FLEXIBLE UNICELLULAR

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, SLEEVING AND TUBING, THERMAL	815016 (CONT)	A-A-52152	FLEXIBLE
		MIL-P-15280	UNICELLULAR PLASTIC
		MIL-T-47051	HEAT SHRINKABLE
		MIL-I-47100	FLEXIBLE POLYAMIDE
INSULATION, TAPE, THERMAL	815017	ASTM D 315	ASBESTOS
		MIL-STD-769	PIPE AND TUBE
		ASTM D 1571/D315	ASBESTOS
INSULATION, THERMAL AND ACOUSTICAL	815018	ASTM C 1071	MINERAL, DUCT LINING
		MIL-I-22023	FIBROUS GLASS, FLEXIBLE
		MIL-I-7171	AIRCRAFT
INSULATION, THERMAL	815019	AMS-3676	GLASS FIBER, RESIN
		AMS-3720	HONEYCOMB PAPER 60 LB
		AMS-3722	HONEYCOMB PAPER 125 LB
		ASTM C 1136	VAPOR BARRIER
		ASTM C 739	LOOSE FILL, CELLULOSE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INSULATION, THERMAL	815019 (CONT)	HH-I-558	MINERAL FIBER, PIPE AND TUBE
		ASTM C 549	PERLITE
		ASTM C 516	VERMICULITE
		HH-I-1030	MINERAL FIBER, PNEUMATIC OR POURED
		MIL-I-2781	PIPE
		MIL-C-2861	CEMENT
		MIL-I-22344	FIBROUS GLASS, PIPE
		MIL-I-24172	POLYURETHANE, PREFORMED OR FOAM IN PLACE
		MIL-P-21929	POLYURETHANE

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-52152	Insulation Sleeving, Thermal, Tubular

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer and Related Materials, Methods of Inspection, Sampling and Testing
FED-STD-191	Textile Test Methods
FED-STD-595	Colors
FED-STD-601	Rubber, Sampling and Testing

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
DOD-STD-130	Identification Marking of U.S. Military Property
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-1285	Marking of Electrical and Electronic Parts
MIL-STD-1623	Fire Performance Requirements and Approved Specifications for Interior Finish Materials and Furnishings

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM C 165 - Compressive Strength of Preformed Block-Type Thermal Insulation, Test For

ASTM C 167 - Thickness and Density of Blanket or Batt-Type Thermal Insulating Materials, Test For

ASTM C 171 - Standard Specification for Sheet Materials for Curing Concrete

ASTM C 177 - Thermal Conductivity of Materials by Means of the Guarded Hot Plate, Test For

ASTM C 209 - Insulating Board (Cellulose Fiber), Structural and Decorative

ASTM C 236 - Thermal Conductance and Transmittance of Built-Up Sections by Means of the Guarded Hot Box, Test For

ASTM C 272 - Water Absorption of Core Materials for Structural Sandwich Constructions, Test For

ASTM C 303 - Density of Preformed Block-Type Thermal Insulation Test For

ASTM C 423 - Sound Absorption of Acoustical Materials in Reverberation Rooms, Test For

ASTM C 464 - Standard Test Method for Corrosion Effect of Thermal Insulating Cements on Base Metal

ASTM C 520 - Density of Granular Loose Fill Insulations, Test For

ASTM C 534 - Standard Specification for Preformed Flexible Elastomeric Cellular Thermal Insulation in Sheet and Tubular Form

ASTM C 553 - Mineral Fiber Blanket and Felt Insulation, Industrial Type, Specification For

ASTM C 581 - Standard Practice for Determining Chemical Resistance of Thermosetting Resins Used in Glass-Fiber-Reinforced Structures Intended for Liquid Service

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the currentversion before use.

ASTM C 661 - Standard Test Method for Indentation Hardness of Elastomeric-Type Sealants By Means of a Durometer

ASTM C 1071 - Standard Specification for Thermal and Acoustical Insulation (mineral Fiber, Duct Lining Material)

ASTM D 146 - Standard Test Methods for Sampling and Testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing

ASTM D 315 - Standard Specification for Woven Asbestos (Tapes)

ASTM D 395 - Compression Set of Vulcanized Rubber, Tests for

ASTM D 412 - Tension Testing of Vulcanized Rubber

ASTM D 695 - Standard Test Method for Compressive Properties of Rigid Plastics

ASTM D 746 - Standard Test Method for Brittlemess Temperature of Plastics and Elastomers by Impact

ASTM D 785 - Standard Test Method for Rockwell Hardness of Plastics and Electrical Insulating Materials

ASTM D 792 - Standard Test Methods for Specific Gravity (Relative Density) and Density of Plastics by Displacement

ASTM D 902 - Standard Test Methods for Flexible Resin-Coated Glass Fabrics and Glass Fabric Tapes Used for Electrical Insulation

ASTM D 1056 - Sponge and Expanded Cellular Rubber Products, Specification for

ASTM D 1084 - Standard Test Methods for Viscosity of Adhesives

ASTM D 1149 - Accelerated Ozone Cracking of Vulcanized Rubber, Test for

ASTM D 1343 - Standard Test Method for Viscosity of Cellulose Derivatives by Ball-Drop Method

ASTM D 1474 - Standard Test Methods for Indentation Hardness of Organic Coatings

ASTM D 1571 - Standard Specification for Woven Asbestos (Cloth)

ASTM D 1621 - Compressive Strength of Rigid Cellular Plastics, Test for

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

ASTM D 1622 - Apparent Density of Rigid Cellular PLastics, Test for

ASTM D 1667 - Sponge Made From Closed Cell Polyvinyl Chloride or Copolymers Thereof, Specification and Test For

ASTM D 1918 - Asbestos Content of Asbestos Textile Materials, Test for

ASTM D 2137 - Low-Temperature Impact Test for Brittleness Determination of Flexible Polymeric Materials or Fabrics Coated Therewith, or Both

ASTM D 2240 - Standard Test Method for Rubber Property - Durometer Hardness

ASTM D 2393 - Standard Test Method for Viscosity of Epoxy Resins and Related Components

ASTM D 2556 - Apparent Viscosity of Adhesives Hear-Rate-Dependent Flow Properties, Test Method for

ASTM E 96 - Standard Test Method for Water Vapor Transmission of Materials

ASTM E 154 - Standard Test Methods for Water Vapor Retarders Used in Contact with Earth Under Concrete Slabs, on Walls, or as Ground Cover

ASTM E 171 - Standard Specification for Standard Atmospheres for Conditioning and Testing Materials

ASTM E 380 - Metric Practice Guide

ASTM F 36 - Compressibility and Recovery of Gasket Materials, Standard Test Method for

ASTM G 21 - Standard Practice for Determining Resistance of Plastics to Bacteria

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

New Page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

THIS PAGE DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for additional specific column headings which may be used for thermal and acoustic insulation characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either feet or yards.

TABLE III. TABULATION CANDIDATES

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1650	ROLL MIN LENGTH (FEET)	1652	ROLL MIN LENGTH (YARDS)	1654	ROLL MIN LENGTH (METERS)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2144	THE TEST SPECIMEN DIAMETER SHALL BE 2144 INCH(S).
2146	THE TEST SPECIMEN DIAMETER SHALL BE 2146 MILLIMETER(S).
2148	THE NUMBER OF TEST CYCLES SHALL BE 2148.
2150	COMPRESSION SET. TESTING SHALL BE IN ACCORDANCE WITH ASTM D 1667.
2152	THE NUMBER OF SPECIMENS TO BE TESTED SHALL BE 2152.
2154	THE TEST SPECIMEN SIZE SHALL BE 2154 SQUARE INCH(S).
2156	THE TEST SPECIMEN SIZE SHALL BE 2156 SQUARE MILLIMETER(S).
2160	COMPRESSION STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2160.
2161	COMPRESSION STRENGTH. THE COMPRESSION STRENGTH SHALL BE AS FOLLOWS:
2162	THE COMPRESSION STRENGTH SHALL BE 2162 POUND(S) PER SQUARE INCH.
2164	THE COMPRESSION STRENGTH TOLERANCE SHALL BE PLUS OR MINUS 2164 POUND(S) PER SQUARE INCH.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
COMPRESSION STRENGTH (CONT)	
COMPRESSION STRENGTH (CONT)	
(KILOPASCALS)	2166
TOLERANCE, PLUS OR MINUS (KILOPASCALS)	2168
MINIMUM COMPRESSION STRENGTH (SELECT ONE)	
(PSI)	2170
(KILOPASCALS)	2172
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2176
PER ASTM D 695.	2178
PER ASTM C 165.	2180
PER ASTM D 1056.	2182
TEST TEMPERATURE (DEGREES CELSIUS)	2184
MAXIMUM PERIOD TO DEFLECTION MEASUREMENT AFTER LOAD APPLICATION (SECONDS)	2186
COMPRESSED TO PERCENT OF ORIGINAL THICKNESS (PERCENT)	2188

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2166	THE COMPRESSION STRENGTH SHALL BE 2166 KILOPASCAL(S).
2168	THE COMPRESSION STRENGTH TOLERANCE SHALL BE PLUS OR MINUS 2168 KILOPASCAL(S).
2170	THE COMPRESSION STRENGTH SHALL BE NOT LESS THAN 2170 POUND(S) PER SQUARE INCH.
2172	THE COMPRESSION STRENGTH SHALL BE NOT LESS THAN 2172 KILOPASCAL(S).
2176	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2176
2178	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 695.
2180	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM C 165.
2182	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 1056.
2184	THE TEST TEMPERATURE SHALL BE 2184 DEGREES CELSIUS.
2186	THE PERIOD TO DEFLECTION MEASUREMENT AFTER LOAD APPLICATION SHALL BE NOT GREATER THAN 2186 SECOND(S).
2188	THE MATERIAL SHALL BE COMPRESSED TO 2188 PERCENT OF ORIGINAL THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
COMPRESSION STRENGTH (CONT)	
TEST METHODS (CONT)	
PER ASTM D 1621, PROCEDURE A	2190
NUMBER OF SPECIMENS (QUANTITY)	2192
SPECIMEN WIDTH (SELECT ONE)	
(INCHES)	2194
(MILLIMETERS)	2196
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	2198
(MILLIMETERS)	2200
SPECIMEN LENGTH (SELECT ONE)	
(INCHES)	2204
(MILLIMETERS)	2205
SPECIMEN DIAMETER (SELECT ONE)	
(INCHES)	2206
(MILLIMETERS)	2207
NUMBER OF CYCLES (QUANTITY)	2208
COMPRESSED TO PERCENT OF ORIGINAL THICKNESS (PERCENT)	2209

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3204	DENSITY/SPECIFIC GRAVITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
3206	THE DENSITY SHALL BE NOT LESS THAN 3206 GRAM(S) PER CUBIC MILLIMETER.
3208	THE DENSITY SHALL BE NOT LESS THAN 3208 POUND(S) PER CUBIC FOOT.
3210	THE DENSITY SHALL BE NOT LESS THAN 3210 OUNCE(S) PER CUBIC INCH.
3212	THE DENSITY SHALL BE NOT GREATER THAN 3212 GRAM(S) PER CUBIC MILLIMETER.
3214	THE DENSITY SHALL BE NOT GREATER THAN 3214 POUND(S) PER CUBIC FOOT.
3216	THE DENSITY SHALL BE NOT GREATER THAN 3216 OUNCE(S) PER CUBIC INCH.
3218	THE SPECIFIC GRAVITY SHALL BE NOT LESS THAN 3218.
3220	THE SPECIFIC GRAVITY SHALL BE NOT GREATER THAN 3220.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DENSITY/SPECIFIC GRAVITY (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3224
PER ASTM C 303.	3226
PER ASTM C 520.	3228
PER ASTM C 167.	3230
PER ASTM D 1622.	3232
PER ASTM D 792.	3234
TEST TEMPERATURE (DEGREES CELSIUS)	3236
TOLERANCE, PLUS OR MINUS (DEGREES CELSIUS)	3238
PER ASTM D 1667.	3240
BY ANY CONVENTIONAL METHOD.	3242

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3224	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3224.
3226	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM C 303.
3228	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM C 520.
3230	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM C 167.
3232	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 1622.
3234	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 792.
3236	THE TEST TEMPERATURE SHALL BE 3236 DEGREES CELSIUS.
3238	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3238 DEGREES CELSIUS.
3240	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 1667.
3242	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ANY CONVENTIONAL METHOD.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DRYING (CURE, GEL)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2246
AS FOLLOWS:	2248
PERIOD TO REACH STRINGY STATE (SELECT ONE)	
(HOURS)	2250
(MINUTES)	2252
PERIOD TO REACH TACK FREE STATE (SELECT ONE)	
(HOURS)	2254
(MINUTES)	2256
PERIOD TO REACH FULL CURE (SELECT ONE)	
(HOURS)	2258
(MINUTES)	2260
SPECIMEN CONFORMS TO COLOR REQUIREMENTS.	2262
SPECIMEN CONFORMS TO HARDNESS REQUIREMENTS.	2264

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3118	THE INGREDIENT EFFLUX PERIOD SHALL BE 3118 SECOND(S).
3120	THE INGREDIENT EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3120 SECOND(S).
3122	THE INGREDIENT FRICTION SHALL BE 3122 CENTIPOISE(S).
3124	THE INGREDIENT FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3124 CENTIPOISE(S).
3126	THE INGREDIENT FRICTION SHALL BE 3126 PASCAL(S) PER SECOND.
3128	THE INGREDIENT FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3128 PASCAL(S) PER SECOND.
3044	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3044.
3046	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3046.
3048	THE APPLICABLE TEST METHOD SHALL BE 3048.
3050	THE TEST TEMPERATURE SHALL BE 3050 DEGREE(S) CELSIUS.
3052	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3052 DEGREE(S) CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VISCOSITY (CONT)	
PER DOCUMENT (CONT)	
RELATIVE HUMIDITY (PERCENT)	3054
HUMIDITY TOLERANCE, PLUS OR MINUS (PERCENT)	3056
WATER VAPOR TRANSMISSION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2502
AS FOLLOWS: (SELECT ONE)	2503
MAXIMUM PERMEABILITY PER INCH (VALUE)	2504
MAXIMUM PERMEABILITY PER MILLIMETER (VALUE)	2506
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2510
PER ASTM E 96.	2512
TEST METHOD (SELECT ONE)	
DISICCANT METHOD.	2514
WATER METHOD.	2516

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3054	THE TEST RELATIVE HUMIDITY SHALL BE 3054 PERCENT.
3056	THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 3056 PERCENT.
2502	WATER VAPOR TRANSMISSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2502.
2503	WATER VAPOR TRANSMISSION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2504	THE MATERIAL PERMEABILITY SHALL BE NOT GREATER THAN 2504 PER INCH.
2506	THE MATERIAL PERMEABILITY SHALL BE NOT GREATER THAN 2506 PER MILLIMETER.
2510	WATER VAPOR TRANSMISSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2510.
2512	WATER VAPOR TRANSMISSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM E 96.
2514	THE DESICCANT TEST METHOD SHALL APPLY.
2516	THE WATER TEST METHOD SHALL APPLY.

Supersedes page 147 of 23 JUNE 1978

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WATER VAPOR TRANSMISSION (CONT)	
PER ASTME96 (CONT)	
MOUNTING METHOD (DES)	2518
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	2520
(MILLIMETERS)	2522
CONDITIONING TEMPERATURE (DEGREES CELSIUS)	2524
TOLERANCE, PLUS OR MINUS (DEGREES CELSIUS)	2526
CONDITIONING RELATIVE HUMIDITY (PERCENT)	2528
TOLERANCE, PLUS OR MINUS (PERCENT)	2530
WORKMANSHIP	
(DOC DES)	6870
ADDITIONAL REQUIREMENTS	
A ___	7001
B ___	7002
C ___	7003
D ___	7004
E ___	7005

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.