MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

CONNECTOR ACCESSORIES

TO ALL HOLDERS OF DOD-STD-35-91A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-91A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5	20 January 1979	(Reprinted without change)	20 January 1979
6	8 October 1979	6	20 January 1979
11	20 January 1979	(Reprinted without change)	20 January 1979
12	8 October 1979	12	20 January 1979
25	20 January 1979	(Reprinted without change)	20 January 1979
26	20 January 1979	(Reprinted without change)	20 January 1979
31	20 January 1979	(Reprinted without change)	20 January 1979
32	8 October 1979	32	20 January 1979
33	8 October 1979	33	20 January 1979
34	20 January 1979	(Reprinted without change)	20 January 1979
39	20 January 1979	(Reprinted without change)	20 January 1979
40	8 October 1979	40	20 January 1979
41	8 October 1979	41	20 January 1979
42	20 January 1979	(Reprinted without change)	20 January 1979

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE	NEW PAGE	DATE
25a	8 October 1979	32g	8 October 1979
25b	8 October 1979	32h	8 October 1979
32a	8 October 1979	32i	8 October 1979
32b	8 October 1979	32j	8 October 1979
32c	8 October 1979	32k	8 October 1979
32d	8 October 1979	32l	8 October 1979
32e	8 October 1979	40a	8 October 1979
32f	8 October 1979	40b	8 October 1979

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of DOD-STD-91A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - ER
Army - ME
Army - MR
Army - SG
Army - CR

User activity:
Army - AR

Preparing activity:
Army - MI

(Project EDS-300)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MST TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONNECTOR, DUMMY	078019 (CONT)	MS27567	MIL-C-38159 MALE
		MS27568	FEMALE
		MIL-C-83713	DETAIL SHEET 61
CONTACT	078024	MIL-C-39029	VARIOUS CONFIG
COVER	078015	MS3180	MIL-C-26482 PLUG, BAYONET
		MS3181	RECPT, BAYONET
		MS3182	MIL-C-81703 PLUG, PUSH-PULL
		MS3183	RECPT, BALL
		MS3505	MIL-C-81790 RECT COVER
		MS17349	MIL-C-22992 RECPT, THREADED
		MS17350	PLUG, THREADED
		MS25042	MIL-C-5015 PLUG, THREADED
		MS25043	RECPT, THREADED
		MS27193	PLUG, THREADED
		MS27501	MIL-C-38999 PLUG, BAYONET
		MS27502	RECPT, BAYONET
		MS27510	PLUG, BAYONET
		MS27511	RECPT, BAYONET
		MS90376	PLASTIC CAP
		MS90563	MIL-C-22992 RECPT, THREADED
		MS90564	PLUG, THREADED
		MIL-C-28840	THREADED
		MIL-C-39012	COAXIAL
		MIL-C-83723	VARIOUS CONFIG
GROMMET	078022	MS27271	MIL-C-38159 CABLE SEAL
MOLD, POTTING	078018	MS3185	ST AND RT ANGLE
		MS25183	POTTING FORM
		MS27332	MIL-C-27599 POTTING RING
		MS27333	POTTING BOOT

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
MOLD, POTTING	078017 (CONT)	MS27485	MIL-C-38999 POTTING RING
		MS27486	POTTING BOOT
		MIL-C-24308	POTTING SHELL
SHIELD	07802	MS24132	MIL-C-28748 TO 26 CONTACTS
		MS24133	TO 75 CONTACTS
		MIL-C-24308	CABLE CLAMP
		MIL-C-39012	COAXIAL
TRANSITION, CABLE ASSEMBLY	078023	MS3184	BREAKOUT
PLUG, SEALING	078025	MS25251	8,12,16,20 SIZE
		MS3187	0-20 SIZE
		MS27488	16-22 SIZE
FASTENER ASSEMBLY	078026	MIL-C-24308	CLIP ASSY
STUFFING TUBE	078027	MIL-S-24235	METAL
		MIL-S-19622	NYLON

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table II provides codes for column headings which may be used for Connector Accessories characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Reprinted without change
Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:01Z
Check this source to verify that this is the current version before use.

TABLE II. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1565	SHELL SIZE	1573	CONN PART NUMBER	1575	CONNECTOR SERIES
1602	CONTACT TYPE	1606	CONTACT SIZE	1608	CONTACT TERM.
1610	CONTACT WIRE SIZE	1612	CONTACT CABLE ACCOM	1614	CONTACT MATING END SIZE
1616	CONTACT BARREL END SIZE	1789	TUBE SIZE	1790	TUBE NOM ID (IN.)
1792	TUBE NOM ID (MM)	1794	ILL NO.	1810	CONVOLUTED TUBE TYPE
1814	SHRINK TUBE TYPE	2120	TYPE	2122	SERIES
2124	CLASS	2126	FINISH	2128	STYLE
2136	CURRENT RATING AMPERES	2138	VOLTAGE RATING VOLTS	7071	MAXIMUM WEIGHT GRAMS
7072	MAXIMUM WEIGHT OUNCES				

Source: https://assist.dla.mil -- Downloaded: 20261O-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	DESIGN AND CONSTRUCTION.
	CONNECTOR IDENTIFICATION.
1573	ACCESSORY SHALL BE FOR USE WITH A CONNECTOR PART NUMBER 1573.
1574	CONNECTOR SHALL BE IN ACCORDANCE WITH 1574.
1575	SERIES 1575 SHALL APPLY.
1582	CONNECTOR VENDOR FSCM SHALL BE 1582.
1808	ACCESSORY SHALL BE FOR ATTACHMENT OF 1808 TO THE CONNECTOR.
	TUBING ATTACHMENT.
1810	TUBING SHALL BE CONVOLUTED TUBING TYPE 1810.
1812	CONVOLUTED TUBING SHALL BE IN ACCORDANCE WITH 1812.
1814	TUBING SHALL BE HEAT SHRINKABLE TYPE 1814.
1816	HEAT SHRINKABLE TUBING SHALL BE IN ACCORDANCE WITH 1816.
1790	PART SHALL BE FOR ATTACHMENT OF TUBING SIZE 1790 INCH(S) NOMINAL ID.
1792	PART SHALL BE FOR ATTACHMENT OF TUBING SIZE 1792 MILLIMETER(S) NOMINAL ID.
1789	PART SHALL BE FOR ATTACHMENT OF TUBING SIZE 1789.

Source: https://assist.dla.mil/ Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.
Reprinted without change

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION	
CONTACT (TYPE)	1602
NOTE: PIN, SOCKET SHIELDED MALE, ETC.	
CENTER CONTACT (TYPE)	1604
NOTE: FOR SHIELDED CONTACTS, PIN OR SOCKET	
CONTACT (SIZE)	1606
TERMINATION (METHOD)	1608
NOTE: CRIMP, SOLDER, WIRE WRAP	
WIRE (SIZE)	1610
CABLE ACCOMMODATION (IDENTIFIER)	1612
MATING END (SIZE)	1614
WIRE BARREL (SIZE	1616

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1602	CONTACT. CONTACT TYPE SHALL BE 1602.
1604	CENTER CONTACT TYPE SHALL BE 1604.
1606	CONTACT SIZE SHALL BE SIZE 1606.
1608	CONTACT TERMINATION METHOD SHALL BE 1608.
1610	CONTACT SHALL ACCOMMODATE SIZE(S) 1610 WIRE.
1612	CONTACT SHALL ACCOMMODATE 1612 CABLE.
1614	CONTACT MATING END SHALL BE SIZE 1614.
1616	CONTACT WIRE BARREL SHALL BE SIZE 1616.

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
WEIGHT	
MAXIMUM WEIGHT PER UNIT (SELECT ONE)	
U.S. (SELECT ONE)	
(OUNCES)	7022
(POUNDS)	7023
SI (SELECT ONE)	
(GRAMS)	7021
(KILOGRAMS)	7024
CABLE PULL-OUT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1681
NO EVIDENCE OF PHYSICAL DAMAGE.	1782
NO DISCONTINUITY.	3136
MAXIMUM LINEAR MOTION (SELECT ONE)	
(INCHES)	1683
(MILLIMETERS)	1684

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2280	CABLE SEAL FLEXING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2280.
2282	CABLE SEAL FLEXING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2017 OF MIL-STD-1344.
2284	TEST PROCEDURE I SHALL APPLY.
2286	THE ROLLER DIAMETER SHALL BE NOT LESS THAN 2286 INCH(S).
2288	THE ROLLER DIAMETER SHALL BE NOT LESS THAN 2288 MILLIMETER(S).
2290	DIMENSION X BETWEEN THE NEAREST END OF INTERNAL CABLE CLAMP AND ROLLER CENTERLINE SHALL BE NOT LESS THAN 2290 INCH(S).
2292	DIMENSION X BETWEEN THE NEAREST END OF INTERNAL CABLE CLAMP AND ROLLER CENTERLINE SHALL BE NOT LESS THAN 2292 MILLIMETER(S).
2294	CYCLING RATE SHALL BE APPROXIMATELY 2294 CYCLES PER MINUTE.
2296	THERE SHALL BE 2296 CYCLES PERFORMED.
2298	THE CABLE TO BE USED SHALL BE 2298.
1721	CHAIN TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1721.
1722	CHAIN TENSILE STRENGTH. THE CHAIN SHALL WITHSTAND THE TENSILE PULL WITHOUT EVIDENCE OF DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

Reprinted without change

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CHAIN TENSILE STRENGTH (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1711
PER DOCUMENT (DOC DES)	2300
TENSILE PULL (SELECT ONE)	
(POUNDS)	1713
(NEWTONS)	1714
DIRECTION (SELECT ONE)	
IN AXIS OF FASTENER.	1716
RIGHT ANGLE TO AXIS OF FASTENER.	1717
DURATION (MINUTES)	1715
CONTACT ENGAGEMENT AND SEPARATION FORCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1824
AS FOLLOWS:	1826
MAXIMUM ENGAGEMENT FORCE (SELECT ONE)	
(POUNDS)	1828

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1711 CHAIN TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1711.

2300 CHAIN TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2300.

1713 A TENSILE PULL OF 1713 POUND(S) SHALL BE APPLIED TO THE END OF THE COVER CHAIN.

1714 A TENSILE PULL OF 1714 NEWTON(S) SHALL BE APPLIED TO THE END OF THE COVER CHAIN.

1716 THE DIRECTION OF PULL SHALL BE WITH THE AXIS OF THE CHAIN IN THE SAME AXIS AS THAT OF THE FASTENER.

1717 THE DIRECTION OF PULL SHALL BE WITH THE AXIS OF THE CHAIN AT RIGHT ANGLES TO THE AXIS OF THE FASTENER.

1715 THE DURATION OF PULL SHALL BE 1715 MINUTE(S).

1824 CONTACT ENGAGEMENT AND SEPARATION FORCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1824.

1826 CONTACT ENGAGEMENT AND SEPARATION FORCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

1828 THE ENGAGEMENT FORCE SHALL BE NOT GREATER THAN 1828 POUND(S).

New page

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTACT ENGAGEMENT AND SEPARATION FORCE (CONT)	
MAXIMUM ENGAGEMENT FORCE (CONT)	
(OUNCES)	1830
(NEWTONS)	1832
MAXIMUM SEPARATION FORCE (SELECT ONE)	
(POUNDS)	1834
(OUNCES)	1836
(NEWTONS)	1838
MINIMUM SEPARATION FORCE (SELECT ONE)	
(POUNDS)	1840
(OUNCES)	1842
(NEWTONS)	1844
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1846
PER MIL-STD-1344, METHOD 2014.	1848
PROCEDURE I.	1850

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1830	THE ENGAGEMENT FORCE SHALL BE NOT GREATER THAN 1830 OUNCE(S).
1832	THE ENGAGEMENT FORCE SHALL BE NOT GREATER THAN 1832 NEWTON(S).
1834	THE SEPARATION FORCE SHALL BE NOT GREATER THAN 1834 POUND(S).
1836	THE SEPARATION FORCE SHALL BE NOT GREATER THAN 1836 OUNCE(S).
1838	THE SEPARATION FORCE SHALL BE NOT GREATER THAN 1838 NEWTON(S).
1840	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1840 POUND(S).
1842	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1842 OUNCE(S).
1844	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1844 NEWTON(S).
1846	CONTACT ENGAGEMENT AND SEPARATION FORCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1846.
1848	CONTACT ENGAGEMENT AND SEPARATION FORCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2014 OF MIL-STD-1344.
1850	PROCEDURE I SHALL APPLY.

New page

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTACT ENGAGEMENT AND SEPARATION FORCE (CONT)	
PROCEDURE I. (CONT)	
MAXIMUM PIN DIAMETER (SELECT ONE)	
(INCH)	1852
(MILLIMETERS)	1854
MAXIMUM BLADE WIDTH (SELECT ONE)	
(INCH)	1856
(MILLIMETERS)	1858
MAXIMUM BLADE THICKNESS (SELECT ONE)	
(INCH)	1860
(MILLIMETERS)	1862
MINIMUM PIN DIAMETER (SELECT ONE)	
(INCH)	1864
(MILLIMETERS)	1866
MINIMUM BLADE WIDTH (SELECT ONE)	
(INCH)	1868
(MILLIMETERS)	1870
MINIMUM BLADE THICKNESS (SELECT ONE)	
(INCH)	1872
(MILLIMETERS)	1874

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

New page

CHAR CODE	STANDARD PARAGRAPH
1852	THE MAXIMUM SIZE PIN SHALL BE 1852 INCH DIAMETER.
1854	THE MAXIMUM SIZE PIN SHALL BE 1854 MILLIMETER(S) DIAMETER.
1856	THE MAXIMUM SIZE BLADE SHALL BE 1856 INCH IN WIDTH.
1858	THE MAXIMUM SIZE BLADE SHALL BE 1858 MILLIMETER(S) IN WIDTH.
1860	THE MAXIMUM SIZE BLADE SHALL BE 1860 INCH IN THICKNESS.
1862	THE MAXIMUM SIZE BLADE SHALL BE 1862 MILLIMETER(S) IN THICKNESS.
1864	THE MINIMUM SIZE PIN SHALL BE 1864 INCH DIAMETER.
1866	THE MINIMUM SIZE PIN SHALL BE 1866 MILLIMETER(S) IN DIAMETER.
1868	THE MINIMUM SIZE BLADE SHALL BE 1868 INCH IN WIDTH.
1870	THE MINIMUM SIZE BLADE SHALL BE 1870 MILLIMETER(S) IN WIDTH.
1872	THE MINIMUM SIZE BLADE SHALL BE 1872 INCH IN THICKNESS.
1874	THE MINIMUM SIZE BLADE SHALL BE 1874 MILLIMETER(S) IN THICKNESS.

New page

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTACT ENGAGEMENT AND SEPARATION FORCE (CONT)	
PER MIL-STD-1344, METHOD 2014. (CONT)	
PROCEDURE II.	1876
CONTACT (PART NUMBER)	1878
MAXIMUM SURFACE ROUGHNESS (SELECT ONE)	
(MICROINCHES RMS)	1880
(MICROMETERS RMS)	1882
MINIMUM DEPTH OF ENGAGEMENT (SELECT ONE)	
(INCH)	1884
(MILLIMETERS)	1886
CONTACT RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1877
AS FOLLOWS:	1879
MAXIMUM DROP AT 25 DEGREES CELSIUS (MILLIVOLTS)	1881
MAXIMUM AVERAGE DROP AT 25 DEGREES CELSIUS (MILLIVOLTS)	1883
MAXIMUM INITIAL RESISTANCE (OHMS)	1885

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1876 PROCEDURE II SHALL APPLY.

1878 THE PART NUMBER OF THE QUALIFIED CONTACT TO BE INSERTED SHALL BE 1878.

1880 TEST CONTACT SURFACE FINISH SHALL BE NOT GREATER THAN 1880 MICROINCHES RMS.

1882 TEST CONTACT SURFACE FINISH SHALL BE NOT GREATER THAN 1882 MICROMETERS RMS.

1884 DEPTH OF ENGAGEMENT SHALL BE NOT LESS THAN 1884 INCH.

1886 DEPTH OF ENGAGEMENT SHALL BE NOT LESS THAN 1886 MILLIMETER(S).

1877 CONTACT RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1877.

1879 CONTACT RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

1881 THE MILLIVOLT DROP SHALL BE NOT GREATER THAN 1881 MILLIVOLTS AT 25 DEGREES CELSIUS.

1883 THE AVERAGE MILLVOLT DROP SHALL BE NOT GREATER THAN 1883 MILLIVOLTS AT 25 DEGREES CELSIUS.

1885 THE INITIAL CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1885 OHM(S).

New page

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTACT RESISTANCE (CONT)	
AS FOLLOWS: (CONT)	
MAXIMUM AFTER TEST RESISTANCE (OHMS)	1887
MAXIMUM ELEVATED TEMPERATURE DROP (MILLIVOLTS)	1888
MAXIMUM AVERAGE ELEVATED TEMPERATURE DROP (MILLIVOLTS)	1890
MAXIMUM INITIAL CENTER CONTACT RESISTANCE (MILLIVOLTS)	1892
MAXIMUM OUTER CONTACT RESISTANCE (MILLIVOLTS)	1894
MAXIMUM BRAID TO BODY CONTACT RESISTANCE (MILLIVOLTS)	1896
MAXIMUM CENTER CONTACT RESISTANCE AT ELEVATED TEMPERATURE (MILLIVOLTS)	1898
MAXIMUM CENTER CONTACT RESISTANCE AFTER ENVIRONMENTAL TESTS (MILLIVOLTS)	1900
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1902
PER MIL-STD-1344, METHOD 3004.	1904

New page

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1887	THE CONTACT RESISTANCE AFTER ENVIRONMENTAL TESTS SHALL BE NOT GREATER THAN 1887 OHM(S).
1888	THE MILLIVOLT DROP AT ELEVATED TEMPERATURE SHALL BE NOT GREATER THAN 1888 MILLIVOLTS.
1890	THE AVERAGE MILLIVOLT DROP AT ELEVATED TEMPERATURE SHALL BE NOT GREATER THAN 1890 MILLIVOLTS.
1892	THE INITIAL CENTER CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1892 MILLIVOLT(S) DROP.
1894	THE OUTER CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1894 MILLIVOLT(S) DROP.
1896	THE BRAID TO BODY CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1896 MILLIVOLT(S) DROP.
1898	THE CENTER CONTACT RESISTANCE AT ELEVATED TEMPERATURE SHALL BE NOT GREATER THAN 1898 MILLIVOLT(S) DROP.
1900	THE CENTER CONTACT RESISTANCE AFTER ENVIRONMENTAL TEST(S) SHALL BE NOT GREATER THAN 1900 MILLIVOLT(S) DROP.
1902	CONTACT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1902.
1904	CONTACT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3004 OF MIL-STD-1344.

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTACT RESISTANCE (CONT)	
PER MIL-STD-1344, METHOD 3004. (CONT)	
TEST CURRENT (SELECT ONE)	
(AMPERES)	1906
(MILLIAMPERES)	1908
HIGH TEMPERATURE TEST (DEGREES CELSIUS)	1910
CRIMP TENSILE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1912
MINIMUM TENSILE STRENGTH (POUNDS)	1914
WIRE (SIZE)	1916
MINIMUM TENSILE STRENGTH (NEWTONS)	1918
WIRE (SIZE)	1920

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1906	THE TEST CURRENT SHALL BE 1906 AMPERE(S).
1908	THE TEST CURRENT SHALL BE 1908 MILLIAMPERE(S).
1910	IN ADDITION TO MEASUREMENT AT AMBIENT TEMPERATURE, PERFORM MEASUREMENT AT 1910 DEGREES CELSIUS.
1912	CRIMP TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1912.
1914	CRIMP TENSILE STRENGTH. THE TENSILE FORCE REQUIRED TO SEPARATE THE WIRE FROM THE CONTACT CRIMP BARREL SHALL BE NOT LESS THAN 1914 POUND(S). WIRE BREAKAGE NOT DUE TO CRIMPING, AT LESS THAN TENSILE FORCE, SHALL NOT CONSTITUTE A FAILURE.
1916	FORCE SPECIFIED IS FOR SIZE 1916 WIRE.
1918	CRIMP TENSILE STRENGTH. THE TENSILE FORCE REQUIRED TO SEPARATE THE WIRE FROM THE CONTACT CRIMP BARREL SHALL BE NOT LESS THAN 1918 NEWTON(S). WIRE BREAKAGE NOT DUE TO CRIMPING, AT LESS THAN THE TENSILE FORCE, SHALL NOT CONSTITUTE A FAILURE.
1920	FORCE SPECIFIED IS FOR SIZE 1920 WIRE.

New page Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CRIMP TENSILE STRENGTH (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1922
PER MIL-STD-1344, METHOD 2003.	1924
SAMPLE (QUANTITY)	1926
CRIMP TOOL (PART NUMBER)	1928
DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4908
NO EVIDENCE OF FLASHOVER, MECHANICAL DAMAGE, ARCING, OR INSULATION BREAKDOWN.	4906

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

New page

CHAR CODE | STANDARD PARAGRAPH

1922 CRIMP TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1922.

1924 CRIMP TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2003 OF MIL-STD-1344.

1926 THE NUMBER OF TEST SAMPLES SHALL BE 1926.

1928 THE CRIMP TOOL PART NUMBER SHALL BE 1928.

4908 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4908.

4906 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. THERE SHALL BE NO EVIDENCE OF FLASHOVER, MECHANICAL DAMAGE, ARCING, OR INSULATION BREAKDOWN.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE (CONT)	
NO EVIDENCE OF FLASHOVER, MECHANICAL DAMAGE, ARCING, OR INSUALTION BREAKDOWN. (CONT)	
MAXIMUM LEAKAGE (MILLIAMPERES)	4894
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4884
PER MIL-STD-1344, METHOD 3001.	2432
*TEST VOLTAGE (SELECT ONE)	
(VOLTS, DC)	4885
(VOLTS, AC)	4849
SPECIAL PREPARATION PER DOCUMENT (DOC DES)	4859
DURATION OF VOLTAGE APPLICATION (SECONDS)	4891
MOUNTING PER DOCUMENT (DOC DES)	6280
REGULATION OF TEST VOLTAGE (PERCENT)	6308
MINIMUM KILOVOLTAMPERE RATING OF VOLTAGE SOURCE (KILOVOLTAMPERES)	4900

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.
Reprinted without change

CHAR CODE	STANDARD PARAGRAPH
4875	THE LEAKAGE CURRENT SHALL BE NOT GREATER THAN 4875 MILLIAMPERE(S).
4861	DIELECTRIC WITHSTANDING VOLTAGE AT SEA LEVEL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4861.
2452	DIELECTRIC WITHSTANDING VOLTAGE AT SEA LEVEL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3001 OF MIL-STD-1344. TEST CONDITION I SHALL APPLY.
4854	TEST VOLTAGE SHALL BE 4854 VOLTS, DC.
4855	TEST VOLTAGE SHALL BE 4855 VOLTS, AC.
4850	SPECIAL PREPARATION OR CONDITIONS SHALL BE IN ACCORDANCE WITH 4850.
4867	DURATION OF APPLICATION OF TEST VOLTAGE SHALL BE 4867 SECOND(S).
5000	MOUNTING SHALL BE IN ACCORDANCE WITH 5000.
4869	REGULATION OF TEST VOLTAGE SHALL BE WITHIN 4869 PERCENT.
4870	THE KILOVOLTAMPERE RATING OF HIGH VOLTAGE SOURCE SHALL BE NOT LESS THAN 4870 KILOVOLTAMPERE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.
Reprinted without change

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIELECTRIC WITHSTANDING VOLTAGE AT SEA LEVEL (CONT)	
PER MIL-STD-1344, METHOD 3001, TEST CONDITION I. (CONT)	
MAXIMUM SURGE CURRENT (SELECT ONE)	
(AMPERES)	4717
(MILLIAMPERES)	4897
METHOD OF VOLTAGE CONNECTION PER DOCUMENT (DOC DES)	6267
DURABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1930
NO EVIDENCE OF CONTACT DAMAGE.	1932
MAXIMUM CONTACT RESISTANCE (MILLIVOLTS)	1934
MINIMUM CONTACT SEPARATION FORCE (SELECT ONE)	
(POUNDS)	1936
(NEWTONS)	1938
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1940
PER MIL-STD-1344, METHOD 2016.	1942

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4717	THE SURGE CURRENT SHALL BE NOT GREATER THAN 4717 AMPERE(S).
4897	THE SURGE CURRENT SHALL BE NOT GREATER THAN 4897 MILLIAMPERE(S).
6267	METHOD OF CONNECTION OF TEST VOLTAGE SHALL BE IN ACCORDANCE WITH 6267.
1930	DURABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1930.
1932	DURABILITY. THERE SHALL BE NO EVIDENCE OF DEFECTS DETRIMENTAL TO THE MECHANICAL OR ELECTRICAL PERFORMANCE.
1934	THE CONTACT RESISTANCE MILLIVOLT DROP SHALL BE NOT GREATER THAN 1934 MILLIVOLT(S).
1936	THE INDIVIDUAL CONTACT SEPARATION FORCE AFTER TEST SHALL BE NOT LESS THAN 1936 POUND(S).
1938	THE INDIVIDUAL CONTACT SEPARATION FORCE AFTER TEST SHALL BE NOT LESS THAN 1938 NEWTON(S).
1940	DURABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1940.
1942	DURABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2016 OF MIL-STD-1344.

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DURABILITY (CONT)	
PER MIL-STD-1344, METHOD 2016. (CONT)	
CYCLES (QUANTITY)	1944
CYCLING RATE (CYCLES PER HOUR)	1946
FUNGUS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4760
FUNGUS RESISTANT BE CERTIFICATION OR BY TEST.	4761
NO EVIDENCE OF FUNGUS GROWTH WHEN TESTED.	4762
REQUIREMENT 4 OF MIL-STD-454.	2536

New page

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1944	THERE SHALL BE 1944 MATING AND UNMATING CYCLES.
1946	THE CYCLING RATE SHALL BE 1946 CYCLES PER HOUR.
4760	FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.
4761	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERNAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED, THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4762	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
2536	FUNGUS. MATERIALS OF CONSTRUCTION FOR THE ACCESSORY SHALL BE NONNUTRIENT FOR FUNGUS AS SPECIFIED IN REQUIREMENT 4 OF MIL-STD-454. CERTIFICATION OF THIS REQUIREMENT SHALL BE PROVIDED BY THE MANUFACTURER.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR
FUNGUS (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4754
PER MIL-STD-810, METHOD 508.	4755
TEST PERIOD (DAYS)	4756
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4798
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	4799
NO DEGRADATION OF PERFORMANCE.	4815
NO EVIDENCE OF ARCING, FLASHOVER, OR INSULATION BREAKDOWN WHEN DWV APPLIED.	1477
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4788
PER MIL-STD-1344, METHOD 1002.	2550
PROCEDURE TYPE (SELECT ONE)	
TYPE I.	2552

Reprinted without change.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1979—603-022/4268