MIL-C-83893C
13 Aug 1974
SUPERCEDING
MIL-C-83893B(USAF)
14 Nov 1972

MILITARY SPECIFICATION

CAMERA, STILL PICTURE, GENERAL PURPOSE, MEDIUM FORMAT (2 1/4 inch x 2 3/4 inch), RANGEFINDER/VIEWFINDER, TYPE KE-58&( )

This specification is approved for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers the requirements for a general purpose, medium format camera using 120 and 220 size film, intended for use by DOD photojournalists (military and civilian) for combat documentation, base support photography and audio-visual documentation using various types of black and white and color film. Such features as light weight, ease of handling, versatility, rugged construction, and provisions for rapid sequence photography as produced by good human engineering practices are essential requirements for this type of camera.

2. APPLICABLE DOCUMENTS

2.1 Documents. The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATION

Federal

PPP-B-636	Box, Fiberboard

Military

MIL-P-116	Preservation, Methods of
MIL-C-675	Coating of Glass Optical Elements (Antireflection)
MIL-F-8261	Fungus Resistance Tests, Aeronautical and Associated Materials, General Specification For

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables For Inspection by Attributes

FSC 6720

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

Military Con't

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-150	Photographic Lenses
MIL-STD-155	Joint Photographic Type Designation System
MIL-STD-810	Environmental Test Methods
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE STANDARDS

ANSI PH1.21	Roll Film, Backing Paper, and Spools, Dimensions For
ANSI PH1.38	No 220 Roll Film with Paper Leader and Trailer, Dimensions for
ANSI PH3.4	Performance Characteristics of Front Shutters Used in Still Cameras, Method for Determining
ANSI PH3.6	Tripod Connections for American Cameras, $\frac{1}{4}$-inch -20 Thread
ANSI PH3.18	Internal Synchronization of Front Shutters Classifying and Testing the
ANSI PH3.20	Focusing Camera Lenses, Distant Scales for
ANSI PH3.23	Shutter Cable Release Tip and Socket with Taper (European) Thread
ANSI PH3.30	Camera Accessory Shoes, Dimensions for
ANSI PH3.32	Exposure-Time Markings for Shutters Used in Still Cameras
ANSI PH3.33	Relative Aperture Markings for Still Camera Lenses

(Application for copies should be addressed to the American National Standards Institute Inc, 1430 Broadway, New York, New York 10018).

3. REQUIREMENTS

3.1 Preproduction testing. This specification makes provisions for preproduction testing (see 4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

3.2 Major components. Unless specified in the contract or purchase order, the camera shall consist of the following major components:

Component Number	Component Name
1	Camera Body
2	*Normal Lens*
3	Film Back 120/220 (see 3.6.3)
4	Accessories
5	Case

3.3 Materials. Materials used in the construction of the camera and components must be as specified herein. Materials not definitely specified shall be of uniform quality and condition, and free of seams, cracks and other defects which may adversely affect the strength, endurance, dust resistance, light tight integrity, wear resistance or appearance of the finished product. Quality workmanship shall be practiced throughout all phases of the design and construction of the camera and components.

3.3.1 Metals. Metals shall be of the corrosion resistant type or treated to resist corrosion caused by atmospheric conditions likely to be encountered during normal life or storage.

3.3.2 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.3.3 Fungus-resistant materials. Materials which are not nutrients for fungi shall be used to the greatest extent practicable. In cases where materials that are nutrients for fungi must be used, such materials shall be treated with an appropriate fungisidal agent, providing such treatment does not impair the intended use of the material. Material treated with fungisidal agent shall meet the test requirements of MIL-F-8261.

3.4 Design and construction. The camera shall be designed and constructed as a compact, versatile, and dependable hand held or tripod mountable camera for 120 and 220 size film.

3.4.1 Interchangeability. The camera designed shall provide for interchangeability of the major components to assure maximum versatility by adapting to such accessories as interchangeable lenses, interchangeable film backs, etc, not covered by this specification.

3.4.2 Ease of maintenance. The design shall use modular construction, wherever practicable, to facilitate maintenance,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

repair and adjustment within a minimum amount of time.

3.4.3 Human engineering. Human engineering principles and practices shall be the major consideration in the design of the camera and its components. Ease of operation including exposing and transporting the film, rapid changing of all adjustments, interchanging lenses or film backs, and light weight shall be of prime importance.

3.4.3.1 Operation. The camera and its components shall be designed for conventional two hand operation. The two hand operation shall include the film transport, shutter cocking, and focusing with one hand, and shutter release with the other hand. There should be no need to change hands during normal camera operation. A camera designed in which all operations may be accomplished with one hand shall not be excluded from consideration.

*3.4.4 System resolution. The area weight average resolution (AWAR) of the lens-camera body-film back combinations shall be not less than specified herein.

Focal Length	AWAR (Lines/mm)	Aperature
100mm± 10mm	40	Maximum

3.4.5 Finish. The finish of the camera and all components shall be nonreflective black and brushed metal to minimize reflections and/or glare. Chrome finish shall not be used.

*3.4.6 Type designation. The camera shall be type designated camera, still picture, general purpose, medium format, (2¼ inch x 2 3/4 inch), rangefinder/viewfinder, type KE-58 & ( ), in accordance with MIL-STD-155.

3.5 Performance

3.5.1 Environmental conditions. There shall be no failure or impairment of function when the camera is operated under the following conditions:

a. Ambient temperatures from 25° to 120° Fahrenheit (F).

b. Relative humidity up to 90 percent.

c. Altitude from sea level up to 10,000 feet.

d. Subsequent to storage at temperatures of -25° to 160°F.

3.5.2 Image quality. The film exposed in the camera shall produce professional quality negatives/transparancies free from

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

scratches, abrasions, or other marks that affect the quality of the finished image.

3.6 Details of components

3.6.1 Camera body. The camera body shall be constructed of aluminum alloy or similar light weight metal and shall be so constructed that all seams are light-tight and dust resistant. Under normal usage conditions, subject to fair wear and tear, the body shall maintain all operating parts of the camera in a proper alignment during the life of the camera.

3.6.1.1 Tripod socket. A tripod socket in accordance with ANSI Standard PH3.6 shall be provided in the base of the camera body, firmly embedded and flush with the base.

3.6.1.2 Accessory shoe. An accessory shoe, conforming to ANSI Standard PH3.30 shall be provided on the camera. The shoe shall be permanently mounted on the top of the camera.

3.6.1.3 Viewing system. An eye level type viewing system of the optical/rangefinder type utilizing the superimposed image principle for determining the point of proper focus shall be provided. The superimposed images shall be of sufficient size and contrast to provide ease in focusing under dimly lighted conditions. The viewing system shall display not less than 85 percent of the actual image size and shall indicate 2 1/4 x 2 3/4 inch format boundaries for a 100mm lens by suitable markings. Automatic parallax correction shall be provided. The correction shall be to the nearest limit of focus. The eyepiece shall be designed so that an operator wearing glasses will be able to see the entire field of view. The removable film backs shall not in any way obstruct the viewfinder or cause inconvenience in the use of the viewfinder.

*3.6.1.4 Tolerances. The lens seating surface to film back surface shall be maintained to a tolerance of $\pm$ .003 inches or to maintain a system AWAR of 40, whichever shall provide the most accuracy when interchanging components.

3.6.1.5 Shutter release. Provisions shall be made to trip the shutter from a removable hand grip located on one side of the camera body. The shutter release pressure shall not exceed 900 grams. Double exposure prevention shall be included.

3.6.2 Lenses. The camera shall include the following removeable and interchangeable Type III lens(es) with shutter(s) in accordance with MIL-STD-150.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

Focal Length	Maximum Relative Aperture
100mm ± 10mm	f/3.5 or faster

(Additional lenses of different focal length and/or maximum relative aperture, if required shall be specified in the contract or purchase order, and shall meet all requirements of this specification.)

*3.6.2.1 Flange focal distance. The flange focal distance of the interchangeable lens(es) shall be maintained to a tolerance of ± .0015 inches or to maintain a system AWAR of 40, whichever shall provide the most accuracy when interchanging components.

3.6.2.2 Anti-reflection coating. All glass-to-air surfaces of the lens(es) shall be coated with an anti-reflection coating in accordance with MIL-C-675.

3.6.2.3 Iris diaphragm. An iris diaphragm shall be provided to control the size of the aperture in each of the lenses listed in 3.6.2. The iris diaphragm shall provide a continuously variable size opening and shall be provided with an easily operated aperture control. The aperture setting shall be marked in accordance with PH3.33. Click stops shall be provided for each full f stop.

3.6.2.4 Focusing adjustment. The lenses shall be mounted in focusing type lens barrels or rack and pinion type focus for non-rotating lens mounts with a minimum focusing distance of not more than 1 foot per 25mm of focal length. The camera-to-subject distance shall be marked in accordance with PH3.20.

3.6.2.5 Shutter. The lens shall be provided with a between-the-lens type shutter having a speed range of at least 1 second to 1/400 second and bulb(B). The exposure time markings shall be in accordance with PH3.32. The shutter speed tolerance shall be in accordance with PH3.32. The shutter shall be synchronized for electronic flash equipment and flash bulbs, and shall be preset by means of a lever for either M or X Synchronization. A cable release socket in accordance with PH3.23 shall be provided. Provisions shall be made to cock the shutter from the camera body.

3.6.2.6 Lens mount. The lens mount shall be of the bayonet type or equivalent in order to minimize the time and motions required when interchanging lenses. The lens mount shall include the necessary provisions to automatically couple to the rangefinder mechanism.

*3.6.3 Film backs. The film backs shall be the daylight loading removable type that will accomodate both 120 & 220 size film. However, individual 120 size and 220 size film backs shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

acceptable. Unless specified in the contract or purchase order, the following quantities shall be supplied.

Quantity	Film Size
2 each	120/220 combination
OR	
2 each	120 size
1 each	220 size

(Additional film backs (see 6.2) of different film size, type and/or number of exposures per roll up to $3\frac{1}{4}$ x $4\frac{1}{4}$ Polaroid film, if required, shall be specified in the contract or purchase order, and shall meet all requirements of this specification.) The film plane to film/camera body seating surface shall be maintained to a tolerance of $\pm$ .001 inches or to maintain a system AWAR of 40 whichever shall provide the most accuracy when interchanging components.

3.6.3.1 The 120/220 (or individual 120 and 220 size) film back shall accomodate the standard 120 and 220 roll films in accordance with PH1.21 and PH1.38. The format size shall be $2\frac{1}{4}$ x 2 3/4 inches $\pm$ 1/16 inch and shall provide 10 exposures per size 120 roll and 20 exposures per size 220 roll. The 120/220 film back shall be easily converted to accommodate either 120 or 220 film within a few seconds without removing and/or replacing parts or components. The size of film in use shall be indicated automatically by an appropriate method and shall be visible from the outside of the film back.

3.6.3.2 Film transport. The film backs shall be provided with a winding lever or suitable mechanism for simultaneous film advance, shutter cocking and exposure count. Advancing one frame shall be accomplished by a single rotary stroke of not more than 180° or a series of short strokes. If a linear motion is used, the stroke shall not be more than 3 inches. The exposure counter shall indicate the number of frames exposed.

3.6.3.3 Dark slide. The film backs shall be equipped with a dark slide to facilitate changing film backs under normally lighted conditions without exposing the film. Provisions shall be made on the film back to store the dark slide. The dark slides shall be fully interchangeable between all film backs.

3.6.3.4 Pressure plate. The film back shall be equipped with a pressure plate or other suitable means to assure flatness of film plane concurrent with film exposure and commensurate with the required system resolution and shall be appropriately finished to prevent scratching the film.

3.6.3.5 Film speed/type indicator. Provisions shall be made on each film back to indicate or display the speed and type (color

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

or black and white) of the film in used. The method/indicator used shall be permanently mounted on the outside surface of the film back and readily visible to the camera operator.

*3.6.3.6 Safety interlocks. A safety interlock shall be provided to prevent removal of the film back without previously inserting the dark slide. An additional safety interlock shall be provided to prevent shutter release with the dark slide in place.

3.6.4 Accessories. Unless specified in the contract or purchase order, the accessories listed below shall be supplied with the camera.

3.6.4.1 Handgrip. The handgrip provided shall be designed to mount on the side of the camera body and shall be capable of supporting the weight of the body-lens-film back combination and accessory flash equipment. Provisions shall be made to trip the shutter from the handgrip with the thumb or index finger.

3.6.4.2 Sportsfinder. An open frame type sportsfinder shall be provided. The sportsfinder shall be designed to mount in the camera body accessory shoe and shall fold flat when not in use. The sportsfinder shall include provisions for parallox correction.

3.6.4.3 Lens shade/filter holder. The lens shade/filter holder provided shall be of the screw-in type and shall accommodate the standard "series" type filters. The lens hood shall be appropriately constructed to reduce flare light without vignetting. The lens shade may be either circular or rectanglur, and if rectangular, be adjustable so that regardless of thread wear or interference, the shade may be adjusted so that the shades are parallel with the frame boundaries. A retaining ring shall also be provided.

3.6.4.4 Filters. Five (5) "series" type filters to fit the lens shade/filter holder shall be provided in the following colors: Skylight (Wratten 1A), Red (Wratten 25), Medium Yellow (Wratten 8 or 9), Wratten 85 and Wratten 80B.

*3.6.4.5 Flash bracket. A metal flash bracket shall be provided which will readily attach to the camera body and which is capable of supporting the full weight of camera and flash. The flash bracket shall readily accept, by means of detachable bracket(s), flash units with a nominal 1½ inch diameter battery case.

3.6.5 Case. A carrying case with a comfortable handle shall be provided to hold the camera body and all components plus 2 additional lenses. The case shall be made of impact resistant reinforced plastic, aluminum alloy or similar lightweight, high strength materials. The case shall contain shock absorbing material with openings therein, shaped to fit the camera and components. The case shall have positive means of closure.

3.7 Weight. The camera, with 100mm lens 120/220 (or individual 120 or 220) film back and handgrip shall not exceed 6 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

3.8 Breakdown voltage, insulation. The electrical insulation shall have a minimum breakdown voltage of 1000 volts DC for electronic flash and 500 volts DC for flash unit.

3.9 Marking. The camera body and the carrying case shall be marked in accordance with MIL-STD-130.

*3.10 Operator's manual. Unless otherwise specified in the contract or purchase order, each camera shall be supplied with an operator's manual describing proper use and operator maintenance of the camera and accessories.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. Preproduction inspection and testing (see 4.4).

b. Quality conformance inspection and testing (see 4.5).

4.3 Test conditions. The inspection and test conditions shall be as follows:

4.3.1 Temperature and humidity. Unless otherwise specified all inspections and tests shall be conducted under prevailing ambient temperature, relative humidity and barometric pressure.

4.3.2 Test materials. The photographic film used for tests shall be Eastman Kodak Panatomic-X or equivalent, Eastman Kodak Plus X Professional and GAF Versapan, and processed in D-76 Developer to a gamma of 0.8.

4.4 Preproduction inspection and testing. The preproduction inspection and tests shall consist of all inspections and tests specified in this specification.

4.4.1 Sampling instructions. The preproduction sample(s) shall consist of one complete camera per 100 or fraction thereof specified in the contract or order that is representative of the production camera. The preproduction inspections and test shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

be accomplished as designated by the procuring activity.

4.4.2 Preproduction test plan. Unless otherwise specified by the procuring activity, the contractor shall submit to the procuring activity, for their approval, his detailed test plan prior to preproduction testing (see 6.2).

4.4.3 Preproduction test report. Unless otherwise specified by the procuring activity, the contractor shall submit to the procuring activity, for their approval, a test report prepared in accordance with MIL-STD-831 (see 6.2).

4.4.4 Inspection of preparation for delivery. Preparation for delivery shall be inspected to insure compliance with the requirements of section 5. This inspection shall be conducted on a sampling basis utilizing general inspection Level III of MIL-STD-105. Any evidence of noncompliance with the specified requirements shall be cause for rejection.

4.4.5 Inspection and tests

4.4.5.1 Environmental tests. The camera and components shall be environmentally tested according to the following test schedules. Following each individual test, the camera and components shall be tested in accordance with 4.5.2.2 of this specification. Upon the completion of all environmental tests, the camera and components shall be tested in accordance with 4.5.2.1 and 4.5.2.2 of this specification.

4.4.5.1.1 Altitude. The camera, complete with all components and in its carrying case, shall be tested in accordance with Method 500, Procedure I of MIL-STD-810.

4.4.5.1.2 High temperature. The camera, complete with all components and in its carrying case, shall be tested in accordance with Method 501, Procedure I of MIL-STD-810. The maximum operating temperature shall be 120°F.

4.4.5.1.3 Low temperature. The camera, complete with all components and in its carrying case, shall be tested in accordance with Method 502, Procedure I of MIL-STD-810. The minimum storage temperature shall be minus 25°F and the minimum operating temperature shall be 25°F.

4.4.5.1.4 Dust. The camera, as prepared for normal use but with the lens and shutter protected shall be tested in accordance with Method 510, Procedure I of MIL-STD-810, except steps 2 and 3 shall be omitted.

4.4.5.1.5 Humidity. The camera, complete with all components and in its carrying case, shall be tested in accordance with Method 507, Procedure I of MIL-STD-810. At the end of 9 cycles the camera

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

shall be removed from the carrying case and subjected to the last cycle outside the carrying case.

4.4.5.1.6 Shock. The camera, complete with all components and in its carrying case, shall be tested in accordance with Method 516, Procedure II of MIL-STD-810, except that the height of drop shall be 24 inches.

4.4.5.1.7 Fungus. Any parts or components of the camera which are capable or considered capable of sustaining fungus growth shall be tested in accordance with the test specified in Table I MIL-F-8261 for the type of material being tested.

4.4.5.2 Performance tests

4.4.5.2.1 Shutter test. The shutter shall be tested in accordance with PH3.4. The flash snychronization shall be tested in accordance with PH3.18.

4.4.5.2.2 Rangefinder test. The camera and components shall be tested on a Zoomar Mark II Opticometer or equal, for accuracy of infinity setting and accuracy of distance scale markings. There shall be no discernable error in the infinity setting and not more than 20 percent error in the distance scale markings.

4.4.5.2.3 Viewfinder test. The angular coverage of the viewfinder shall be tested by photographing a suitable test target with a linear scale and comparing the image observed with that recorded on film. The recorded image shall not differ from the observed image by more than +15, -5 percent.

4.5 Quality conformance inspection and testing. The quality conformance inspections and tests shall consist of the following inspections and tests:

a. Individual inspections and tests.

b. Periodic sampling tests.

4.5.1 Individual inspections and tests

4.5.1.1 Physical examination. Each camera, complete with all components, shall be inspected to determine conformance to the requirements of this specification with respect to fit of components, design, general construction, finish, quality, and workmanship.

4.5.1.2 Individual inspection. Each camera and lens, complete with all components, shall be examined for proper operation of all adjustments and controls. Each camera shall be checked on a Zoomar Mark II Opticometer or equal, for accuracy of the infinity

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

setting.

4.5.2 Periodic sampling tests. One camera, complete with all components, randomly selected from each 25 or fraction thereof, produced on any one contract shall be submitted to the following tests:

*4.5.2.1 Resolution test. The camera with the normal (100±10mm focal length) lens and the 120/220 (or 120 and 220) film back shall be tested in accordance with Method II of MIL-STD-150 using panatomic -X film or equivalent. Test exposures shall be made at all aperture settings.

4.5.2.2 Operational test. The camera and the 120/220 (or 120 and 220) film back shall be subjected to an operational test using Plus X professional and Versapan Film, exposing all frames at various shutter speed and aperture combinations. The processed film shall be examined for physical damage, banding frame overlap, abnormal or any other evidence of malfunction of the optical system, shutter, or film transport.

4.5.2.3 Interchangeability. The camera and all components shall be gauged or measured to determine conformance to 3.6.1.4, 3.6.2.1, and 3.6.3 to assure that image degradation will not result when interchanging lenses, camera bodies or film backs.

4.5.3 Rejection criteria. Failure of the camera to pass the tests specified in 4.5.1 and 4.5.2 shall be cause for rejection of the lot (see 4.5.2).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each camera and all accessories shall be preserved and packaged in accordance with MIL-P-116 Method IIB.

5.1.2 Level C. Each camera and all accessories shall be preserved and packaged in a manner which will afford adequate protection against deterioration and physical damage during shipment from the supplier to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each camera, preserved and packaged as specified in 5.1.1 shall be packed in a PPP-B-636, Type CF, Class - Weather Resistant, Variety DW, Grade VIIC, Style RSC, fiberboard box. Closure of container shall be as defined in the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Same as 5.2.1, except "PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 200, Style RSC, fiberboard box. Closure of container shall be as defined in the specification."

5.2.3. Level C. Each camera preserved and packaged as specified in 5.1.2 shall be packed in a manner which will afford adequate protection against damage during direct shipment from the supplier to the first receiving activity for immediate use. Containers shall comply with consolidated freight classification rules or other common carrier regulations applicable to the mode of transportation.

*5.3 Marking. In addition to any special marking required by the contract or purchase order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be "Camera, Still Picture, General Purpose, Medium Format (2 1/4 inch x 2 3/4 inch), Rangefinder/Viewfinder, Type KE-58 & ( ).

6.1 Intended use. The camera covered by this specification is intended for general purpose, combat, and documentary by Air Force photographers.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Point of inspection and preproduction sample.

c. Whether special marking is required (see 5.3).

d. Selection of applicable levels of preservation and packaging, and packing required for shipment (see 5.1 and 5.2).

e. Whether additional lenses of different focal length and/or maximum relative aperture are required (see 3.6.2).

f. Whether additional film backs of different film size, type or number of exposures per roll are required (see 3.6.3).

g. That test reports in conjunction with first article tests shall be covered by current DD Forms 1423 and 1664 (see 4.4.3).

6.3 The left hand margin of this specification is marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Navy - AS
Air Force - 70

Preparing Activity
Air Force - 70

Project No. 6720-0264

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-603-110/1682

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:52Z
Check the source to verify that this is the current version before use.