MILITARY SPECIFICATION

PLUG, LOCK
ASSEMBLY, PARTS FOR, ASSEMBLY AND PACKING

This specification is approved for use by the US Army Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This Military Specification covers parts for assembling and packing of Plug, Lock Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation - Packaging, Methods of
MIL-P-117	- Bag, Sleeve and Tubing - Interior Packaging
MIL-I-6866	- Inspection, Penetrant Method of
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for

FEDERAL

PPP-F-320	- Fiberboard; Corrugated and Solid, Sheet Stock, (Container Grade), and Cut Shapes
PPP-B-636	- Box, Shipping, Fiberboard
PPP-T-76	- Tape, Pressure - Sensitive Adhesive Paper, Water Resistant, (For Carton Sealing)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection By Attributes
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

USARRADCOM

PRODUCT AND PACKAGE DRAWINGS

9327328 - Plug, Lock Assembly
9312815 - Projectile, 105MM, HEAT-T-MP, M456A1E2

3. REQUIREMENTS

3.1 General.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Plug, lock assembly.-Lock plug assemblies shall comply with all requirements specified on dwg. 9327328 and all the requirements specified in applicable specifications.

3.3 Workmanship.-All parts and assemblies shall be free of chips, dirt, grease, rust, burrs, cracks and other foreign material. The cleaning methods used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.4 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection.-The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of 30 each of every component and every assembly. (Where a multiple cavity mold is used in the manufacturing process, a minimum of 5 samples shall be submitted from each mold cavity. Each part shall be identified with its mold cavity).

4.3.2 Inspections to be performed.-The First Article parts submitted in accordance with paragraph 4.3.1 will be subjected by the Government to all examinations and tests specified in 4.4.2 of this specification and to any or all requirements of the applicable drawings. 5 each of the nonmetallic parts (2 each if multiple cavity mold is used) shall be temperature conditioned at 180°F ± 10°F for 24 ± 1 hours and then held at room ambient temperature for 4 hours minimum prior to inspection.

4.3.3 Rejection.-See MIL-A-48078 (PA).

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Fulcrum Holder		9327331
			NEXT HIGHER ASSEMBLY
			9327325

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Switch locating diameter, maximum (max.)		0.40%	3.2	Gage
102	True position of switch locating diameter		0.40%	3.2	Gage
103	Thickness through switch seat		0.40%	3.2	Gage
104	Radius of locating spline, minimum (min.)		0.40%	3.2	Gage
105	True position of locating spline		0.40%	3.2	Gage
106	Dimension to top of ramp		0.40%	3.2	Gage
107	True position of ramp sides		0.40%	3.2	Gage
108	Angle of ramp, min.		0.40%	3.2	Gage
109	Hole diameter		0.40%	3.2	Gage
110	True position of hole diameter				
Minor					
201	Width of ramp, max.		0.65%	3.2	Gage
202	Angle of ramp, max.		0.65%	3.2	Gage
203	Outside diameter, (OD), min.		0.65%	3.2	Gage
204	Any feature missing		0.65%	3.2	Visual (Note 1)
205	Evidence of poor workmanship		0.65%	3.3	Visual
206	Ejector marks above flush		0.65%	3.2	Gage

NOTES: 1. Optional reduced inspection per para. 4.5.3 applicable to this defect.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Switch, Beam				9327326
					NEXT HIGHER ASSEMBLY 9327325
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gold plating defective		4.4.3.1	3.2	Test
102	Outside diameter, min.		0.40%	3.2	Gage
103	Width of tang		0.40%	3.2	Gage
104	True position of edge of tang		0.40%	3.2	Gage
105	Presence of burrs on tang		0.40%	3.2	Visual
106	Dimension from root to end of tang		0.40%	3.2	Gage
107	True position of inside diameter		0.40%	3.2	Gage
108	Width of tang releaf cuts		0.40%	3.2	Gage
109	Radius of locating cut, max.		0.40%	3.2	Gage
110	True position of locating cut		0.40%	3.2	Gage
111	Thickness		0.40%	3.2	Gage (Note 1)
112	Any feature or operation missing		0.40%	3.2	Visual
113	Direction of grain incorrect, prior to plating	Note 2		3.2	Visual
114	Length of tang		0.40%	3.2	Gage
Minor					
201	Protective finish missing or incomplete		0.65%	3.2	Visual
202	Inside diameter, (ID), max.		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES: 1. Optional reduced inspection not applicable.
2. One sample per unit of stock used. If sample fails, all parts from that unit of stock are rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Plate, Contact		9327329
			NEXT HIGHER ASSEMBLY
			9327325

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Protective finish missing or incomplete		0.40%	3.2	Visual
102	Height, overall		0.40%	3.2	Gage
103	Thickness of shoulder		0.40%	3.2	Gage
104	True position of minor OD		0.40%	3.2	Gage
105	Minor OD, min.		0.40%	3.2	Gage
106	Diameter at aft c'bore, max.		0.40%	3.2	Gage
107	True position of diameter at aft c'bore		0.40%	3.2	Gage
108	Depth of aft c'bore		0.40%	3.2	Gage
109	Radius of locating cut, max.		0.40%	3.2	Gage
110	Dimension to bottom of forward c'bore		0.40%	3.2	Gage
Minor					
201	Angle of aft c'bore sides		0.65%	3.2	Gage
202	Diameter of forward c'bore		0.65%	3.2	Gage
203	OD, min.		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Spacer, Insulator		9327327
			NEXT HIGHER ASSEMBLY 9327325

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	OD, Min		0.40%	3.2	Gage
102	Hole diameter, max		0.40%	3.2	Gage
103	True position of hole		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Thickness through shoulder		0.65%	3.2	Gage
203	Minor OD		0.65%	3.2	Gage
204	Chamfer missing		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Cover		9327330
			NEXT HIGHER ASSEMBLY
			9327325

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	ID, max.		0.40%	3.2	Gage
102	Thickness (through face and sidewall)		0.40%	3.2	Gage
Minor					
201	Minor ID, max.		0.65%	3.2	Gage
202	Height, min.		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Base, Fulcrum		9327419
			NEXT HIGHER ASSEMBLY 9327325

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Height of hub		0.40%	3.2	Gage
Minor					
201	Diameter of hub, min.		0.65%	3.2	Gage
202	Outside diameter, min.		0.65%	3.2	Gage
203	Height of outside diameter		0.65%	3.2	Gage
204	Angle incorrect		0.65%	3.2	Gage
205	Protective finish missing or incomplete		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Safety Switch Assembly				9327325
					NEXT HIGHER ASSEMBLY 9327328
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Resistance over max. at max. acceleration		100%	3.2	Test
Major					
101	Electrical resistance under min. allowable between plate contact and cover		100%	3.2	Test (Note 1)
102	Fulcrum holder loose or free to rotate within cover		0.40%	3.2	Manual
103	Crimp incomplete or missing		0.40%	3.2	Visual
104	Presence of foreign material on any part immediately prior to assembly		0.40%	3.2	Visual
105	Resistance under min, at min. acceleration		100%	3.2	Test
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES: 1. Shall be checked after Critical 1 and Major 105.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63295 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Plug, Fuze Lock				9327332
					NEXT HIGHER ASSEMBLY 9327328
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Metal defective		4.5.2	3.2	4.5.2
102	Thread(s) damaged or malformed		0.40%	3.2	Visual
103	Thread pitch diameter, min		0.40%	3.2	Gage
104	Thread major diameter, min		0.40%	3.2	Gage
105	Depth of cavity, max		0.40%	3.2	Gage
106	ID of cavity, max		0.40%	3.2	Gage
107	Thickness, min		0.40%	3.2	Gage
108	True position of cavity		0.40%	3.2	Gage
Minor					
201	Thread pitch diameter, max		0.65%	3.2	Gage
202	Thread major diameter, max		0.65%	3.2	Gage
203	Depth of cavity, min		0.65%	3.2	Gage
204	Height, max		0.65%	3.2	Gage
205	Height of chamfer		0.65%	3.2	Gage
206	True position of wrench slots		0.65%	3.2	Gage
207	Evidence of poor workmanship		0.65%	3.3	Visual
208	Any feature missing		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Plug, Lock Assembly				9327328
					NEXT HIGHER ASSEMBLY
					9312815
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Resistance between cup and plug in excess of requirement		100%	3.2	Test
Major					
101	Safety switch assembly free to rotate within fuze lock plug after stake		0.40%	3.2	Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Packing (See 5.1)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	One or more plugs missing from any layer		0.65%	3.1	
202	Packing loose		0.65%	3.1	
203	Packing damaged, improperly sealed or marked		0.65%	3.1	
204	Evidance of poor workmanship		0.65%	3.3	

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Testing of beam switch gold plate.-Testing of the gold plate on the beam switch shall be for thickness and adhesion. Sampling for this test shall be as follows:

a. Batch Type Process.-For plating batches of 1000 parts or less, 2 samples shall be randomly selected. For batches in excess of 1000 parts, one additional part shall be randomly selected from each 500 parts or fraction thereof. If any sample fails to comply with the applicable requirements, the batch represented by that sample shall be rejected.

b. Continuous Type Process.-Two parts shall be randomly selected from each 1000 parts or fraction thereof plated in a continuous process. If any sample fails to comply with the applicable requirements, all parts, plated prior to that sample, and subsequent to the last acceptable sample shall be rejected.

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Test method and procedures

4.5.1 Materials, components and processes.-Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection.-The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein.

4.5.2 Metal defects.-Three sample parts shall be selected from each piece of bar stock. Two parts shall be the first and the last cut from the bar. The third piece shall be selected from within $\pm$ 1 foot of the bar midpoint. Each part shall be examined for evidence of cracks, pipes, and porosity on both forward and aft surfaces, in accordance with MIL-I-6866, flourescent, method A. Examination may be conducted prior to final machining. If any part from a bar is found to have detectable cracks, pipes or porosity, that part shall be rejected and all parts from that bar shall be inspected for metal defects prior to acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

4.5.3 Dimensional control of cast, stamped, molded or automatic tool parts.-In place of the normal sampling associated with the classification of defects, and subject to approval of the Government procuring agency, the optional sampling plans in paragraphs 4.5.3.1, 4.5.3.2, 4.5.3.3 and 4.5.3.4 may be used for dimensional control of cast, stamped, molded, or automatic tool parts. Use of these optional plans is limited to those dimensions and features controlled by the tool, die, or mold cavity. For all specified tests, visual examinations, and examinations of dimensions or features not developed exclusively by the tool, die, or mold cavity, these optional plans are not applicable. In the event of in-process reject(s) during optional sampling, corrective action applicable to parts produced prior to the rejected, and subsequent to the last acceptable sample, shall require approval of the Government procuring agency.

4.5.3.1 Cast parts.-A sample of at least five parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 5000 parts. Individual cavity identification must be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test specified above.

4.5.3.2 Stamped parts.-A sample of at least ten parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above.

4.5.3.3 Molded parts.-A sample of five parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be dimensionally inspected after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned for corrective action. All cavities removed from production because of some fault, may, after reworking, be returned to production, providing they pass the qualification test above.

4.5.3.4 Automatic tool parts (see 6.6).-A sample of at least 10 parts shall be dimensionally inspected to qualify a new or adjusted setup for use in production. For multiple simultaneous setups (2 or more parts produced at once), at least 5 parts per setup shall be inspected. In addition, a random sample of 5 parts per setup shall be selected from the last portion of each hour's production for dimensional inspection as a control of the setup during production. If an hour's production is 250 parts per setup or less, the hourly sample may be reduced to 3 parts per setup.

If any defective parts are found during qualification of a setup, that setup shall not be used in production.

If any defective parts are found when inspection is performed for control of a setup, the setup producing the defective part shall be removed from production. Further, that portion of production since the last setup control check shall be returned for corrective action.

All setups removed from production because of some fault may, after adjustment or re-tooling as necessary, be returned to production providing they pass the qualification test above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

Automatic tools shall be considered for this reduced inspection only when equiped with devices to provide automatic shut-down or clear immediate warning if machine power input (electricity, air or oil pressure) falls below that minimum level necessary for normal machine operation. All parts in process when power input runs below minimum shall be inspected for dimensional requirements prior to acceptance. Such parts shall not be counted as qualification or control samples.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Plug, fuze lock and safety switch assembly, Level B.-The plugs shall be packaged in a Fiberboard Box w/partition. The box shall be Type CF, Class domestic, Variety SW, Grade 175, Style RSC, B-Flute Spec PPP-B-636 secured w/sealing strips - paper tape 2 inch wide, PPP-T-76 and the following requirements; the inside dimensions shall be 16 1/16 X 16 1/16 X 2 7/8 with ± 1/16 tolerance; advisory outside dimensions are 16 3/8 X 16 3/8 X 3 7/16. The Partition made from Fiberboard, Type SF, Class domestic, Grade 175, B Flute, Spec PPP-F-320 shall be 16.0 X 16.0 X 19/32 deep with a ± 1/16 tolerance; each cell shall be 1 21/32 X 1 21/32. The packing arrangement shall be four (4) layers of 9 X 9 for a total of 324 per box. Place short fillers along the ends, sides and top as required. Moisture content of all packing material within the moisture barrier shall not exceed 8 percent when tested in accordance with Method 205 of Fed. Test Method No. 101. Blunt all corners of the carton and insert in a heat sealed bag conforming to the requirements of MIL-B-117, Type I, Style I, Class E. Exhaust all excess air from the bag and close the opening by heat sealing. Seals shall meet the heat seal requirements of MIL-P-116. Bag dimensions are 20 5/8 min open face by 22 min deep. The interior carton in heat sealed bag shall be overpacked in a Fiberboard Box, Type CF, Class domestic, Variety SW, Grade 175, Style RSC, B Flute Spec PPP-B-636; inside dimensions for the box are 17 X 16 5/8 X 3 11/16 with a ± 1/8 tolerance.

5.2 Marking

5.2.1 Level B.-Marking shall be in accordance with Standard MIL-STD-1169.

6. NOTES

6.1 Intended use.-The parts covered by this specification are intended for use with the Fuze, PIBD, M509A2 as the fuzing system for Ctg, 105MM, HEAT-T-MP, M456A1E2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.-See MIL-A-48078 (PA).

6.3 Submission of designs for approval.-See 6.2.3 of MIL-A-48078 (PA). Submit equipment designs, as required, to:

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAR-I
Dover, New Jersey 07801

6.4 Inspection lot size.-It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of test or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.5 Visual examination.-When compliance with the applicable requirements is in doubt as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

6.6 Automatic tool.-An automatic tool is any self-regulating piece of assemblage of production equipment which is setup or programed to perform one or more operations on a part. The tool operator's functions shall not exceed part handling and input of a start signal. The tool setup shall provide positive, repetitive three plane positioning of the work piece.

Custodian:
ARMY - AR

Preparing Activity:
ARMY - AR

Project No.: FSC: 1390-A195

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-63295 Plug, Lock Assembly, Parts for, Assembly and Packing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.