INCH-POUND

MIL-S-82155B(MC)

28 MARCH 1991
SUPERSEDING
MIL-S-82155A(MC)
3 August 1979

MILITARY SPECIFICATION

STRIPE, TROUSERS, DRESS

This specification is approved for use by U. S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for scarlet stripes for dress trousers.

1.2 Classification. The stripe shall be the following types as specified (see 6.2):

Type I - 2 inches finished width (general officer).
Type II - 1-1/2 inches finished width (officer).
Type III - 1-1/8 inches finished width (noncommissioned officer).
Type IV - 9/16 inches finished width (JROTC).

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commanding General (PSE-C), Marine Corps Research, Development, and Acquisition Command, Washington, DC 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATION

FEDERAL

V-T-276 - Thread, Cotton.
UU-P-268 - Paper, Kraft, Wrapping

MILITARY

MIL-B-I7757 - Box, Shipping Fiberboard, (Modular Sizes)
MIL-C-29405 - Cloth, Broadcloth: Wool and Wool/Nylon

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robins Avenue, Philadelphia, PA 19111-5094)

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

LAWS AND REGULATIONS
U.S. Postal Service Manual

(Application for copies of the manual should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

Department of Defense (DoD) Standard Color Card of Official Standardized Shades for Sewing Threads 1968

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

(Copies may be obtained from the Color Association of the United States, Inc., 200 Madison Avenue, New York, New York 10016).

2.2 Non-government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

UNIFORM CLASSIFICATION COMMITTEE, AGENT
Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT
National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P. Street, N.W., Washington, D. C. 20026.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These douments also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard samples. Standard samples are furnished solely for guidance and information to the contractor (see 6.3). Variation from this specification may appear in the standard sample in which case the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to the first article inspection (see 6.4) in accordance with 4.4.

3.3 Materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

3.3.1 Basic material. The basic material shall be cloth, wool broadcloth, scarlet shade 2501, conforming to type I of MIL-C-29405.

3.3.2 Thread. The thread shall be cotton, soft finish, ticket No. 40, three-ply bleached white, conforming to type IA2 of V-T-276 for basting edges of stripes.

3.4 Construction.

3.4.1 Manufacturing requirements. The stripe shall be made of a single-ply of basic material, cut to widths of 4 inches for type I; 3 inches for type II, and 1-3/4 to 1-7/8 inches for type III and 1-1/8 inches for type IV.

3.4.2 Cutting. Cut the stripes in lengths of 100 ± 3/8 inches long.

3.4.3 Fold and baste edges. Fold under raw edges at both sides of the stripe, butting the turned under raw edge portion to a finished width of 2 inches for type I and 1-1/2 inches for type II. Type III stripe shall be folded under at both sides of the stripe approximately 3/8 inch to a finished width of 1-1/8 inches. Type IV stripe shall be folded under, butting the turned under raw edge portion to the finished 9/16 inch width. Baste along the folded edges with stitch type 101 and stitching type EFa-1 in accordance with FED-STD-751, 5 to 7 stitches per inch with a stitching margin of 1/4 inch ± 1/16 inch.

3.5 Workmanship. The finished stripe shall conform to the quality of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsibie for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.1 Certificate of compliance. Where certificates of compliance are permitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.4)
2. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. When specified in the contract or purchase order, all inspections shall be performed in accordance with MIL-STD-105.

4.4 First article inspection. When a first article is required (see 6.2), inspection and testing shall be made on a completed fabricated stripe for all provisions of this specification. The presence of any defect or failure to pass any of the test shall be cause for rejection of the first article. The number of units to be inspected shall be specified by the contracting officer.

4.5 Quality conformance inspection.

4.5.1 Testing of components. Testing of components shall be in accordance with the applicable subsidiary specifications and standards to the extent appiicable, except that this specification shall govern in the event of conflict. A contractor's certificate of compliance may be accepted in lieu of test results for cotton thread.

4.5.2 Examination of the end item. The end item shall be examined for the defects listed below. The unit of product shall be one stripe. The lot size shall be expressed in units of one stripe each. The sample size shall be in accordance with inspection level I of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

Examine	Defect
Material defects and damages	a. Cut, hole or tear. b. Abrasion mark. 1/
Folding (edges)	a. Improperly folded.
Stitching (basting)	a. Wrong stitch or stitching type. b. Less than 5 or more than 7 stitches per inch. c. Stitching exceeding specified tolerances.
Cleanness	a. Spot, stain or streak.1/

1/ Clearly visible at normal inspection distance (approximately 3 feet)

4.5.3 Finished measurements examination. The provisions for the finished measurements examination of the finished stripe shall be as specified in 3.4.2 and 3.4.3. The end item shall be examined for the defects listed below. The unit of product shall be one stripe. The lot size shall be expressed in units of one stripe each. The sample size shall be in accordance with inspection level S-4 of MIL-STD-105.

Dimension	Defect
(a) Length	exceeding specified tolerances.
(b) Width	exceeding specified tolerances.

4.5.4 Examination of packaging. Shipping containers fully prepared for delivery shall be examined for the defects listed below to determine conformance to packaging, packing and marking requirements. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 of MIL-STD-105. (see 6.5).

Examine	Defects
Marking	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

Examine	Defects
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling, bulging or distortion of container.
Content	Number of bundles per shipping container is more or less than required. Number of stripes per bundle is more or less than required 1/

1/ For this defect, one bundle shall be examined from each shipping container in the sample

5. PACKAGING

5.1 Packaging. Packaging shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each stripe shall be folded to one-eighth of its length. Twenty-five (25) stripes so folded shall be securely tied in a bundle with suitable twine or tape.

5.1.2 Commercial. Commercial packaging shall afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice provided it meets the requirements specified for commercial packing.

5.2 Packing. Packing shall be level A, B or commercial as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Method 1. Sixteen (16) bundles (400 stripes) packaged as specified in 5.1 shall be packed in a shipping container conforming to class-weather resistant, size No. 3A of MIL-B-17757 and assembled, closed, and reinforced as specified in the appendix to the box specification. In addition, each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

5.2.1.2 Method 2. When specified (see 6.2), three level B shipping containers (1200 stripes) shall be overpacked in a fiberboard shipping container conforming to class-weather resistant, size No. 4 of MIL-B-17757.

5.2.2 Level B. Sixteen (16) bundles (400 stripes) shall be packed as specified in 5.2.1.1 except the shipping containers shall conform to class-domestic, size No. 3A of MIL-B-17757. The fiberboard used in fabricating the box shall be grade 275.

5.2.3 Commercial. The stripes shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules, National Motor Freight Classification Rule and U.S. Postal Service Manual or reguiations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES
(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The stripes covered by this specification are intended for use on dress trousers worn by general officers, officers, and noncommissioned officers of the U.S. Marine Corps and Junior Reserve Officer Training Corps personnel.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) When first article is not required (see 3.2).
(d) Number of stripes required in first article (see 3.2).
(e) Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2)
(f) When level A, method 2 packing is required (see 5.2.1.2).
(g) Acceptance criteria

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

6.3 Standard sample. The standard sample and color sample may be obtained from the procuring activity or as directed by the contracting officer.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection and approval of the first article.

6.5 Acceptance criteria. The acceptance criteria below are recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.5.1 For end item visual examination. An acceptance quality level (AQL), expressed in terms of defects per hundred units, of 1.5 is recommended.

6.5.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 1.5 is recommended.

6.5.3 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to extensive changes.

6.7 Subject (Key word) listing.

Ornamentation
Trouser

Preparing Activity:
Navy - MC
Project Number 8455-N570

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATI(; DOCUMENT IMPROVEMEI PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-82155B(MC)	28 MARCH 1991

3. DOCUMENT TITLE

STRIPE, TROUSERS, DRESS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER		
a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY		
a. NAME Commanding General, Marine Corps Research, Development, and Acquisition Command (PSE-C)	b. TELEPHONE (Include Area Code) (1) Commercial (202) 696-1186/87/88	(2) AUTOVON 226-1186/87/88
c. ADDRESS (Include Zip Code) Washington, DC 20380-0001	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:48Z
Check the source to verify that this is the current version before use.