INCH-POUND

MIL-S-83806 (84)

27 Apr 90

MILITARY SPECIFICATION

SAW SET, CONCRETE AND ASPHALT, 70 HP, FOR RAPID RUNWAY REPAIR APPLICATIONS

This specification is approved for use within the WR-ALC Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers a saw set consisting of two concrete and asphalt saws and their associated support trailer. The set is designed to support Rapid Runway Repair operations using the concrete slab method of repair.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

STANDARDS

Federal

FED-STD-595	Colors.

Military

MIL-STD-209	Slinging and Tie Down Provisions For Lifting and Tying Down of Military Equipment.
MS-51336	Lunette-coupler, Drawbar, Ring.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMDETB, Robins AFB, GA 31098-5609 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 3895

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:45Z
Check the source to verify that this is the currentversion before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

The Society of Automotive Engineers, Inc. (SAE)

SAE J534	Lubrication Fittings.
SAE J1174	Operator Ear Sound Level Measurement Procedure for Small Engine Powered Equipment, Recommended Practice

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Dr. Warrendale PA 15096)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 Description.

3.1.1 Commerciality. The manufacturer shall be experienced in the design and manufacture of concrete saws of 50 hp or greater. Upon requests by the contracting officer, the offerors shall be required to submit evidence in the form of commercial brochures and the names and addresses of nongovernment organizations which have been supplied these saws (50 hp or larger) at least one year prior to the date of the solicitation.

3.2 Maintainability. All maintenance described in this specification shall be capable of being performed by one mechanic using common hand tools. Design and construction of the concrete saw shall permit ready accessibility to all parts for maintenance and repair in the field. Replacement and adjustment of component parts and accessories shall be accomplished with minimum drainage of fluids and disturbance to other parts.

3.2.1 Filling, draining, and checking provisions. All fluid systems shall possess a convenient means of filling, draining, and checking the level of the system. All drains shall conduct fluid directly to the ground in a stream with out spilling onto other components. Fluid level indicators or fill ports shall identify the type of fluid and identify appropriate add and full levels.

3.2.2 Lubrication points. Lubrication points shall be provided for all surfaces requiring lubrication. Pressure relief fittings shall be supplied where the use of pressure lubrication equipment may damage seals. Lubrication fittings shall be in accordance with SAE J534 and be located so as to be clearly visible and easily serviced with a grease gun with a 10 inch flexible hose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.

3.2.3 Positioning. All parts which could cause improper performance if positioned incorrectly shall possess asymmetrical mounting devices which prevent incorrect positioning.

3.2.4 Low blade coolant pressure cut-off. Saw shall automatically cease sawing should the flow of blade coolant water become too small for continued operation.

3.2.5 Maintenance operations list. Any four or more operations which are applicable to the unit shall be able to be performed by one person in the sum of times allotted for each operation.

a. Remove, replace and adjust all engine driven belts - 1 hour.
b. Remove and replace generator and adjust generator belts - 30 min.
c. Remove and replace all filter elements, screens, and strainers on the hydraulic system - 15 min.
d. Drain engine cooling system, remove and replace engine cooling hoses, and refill cooling system - 1 hour.
e. Drain engine lubricating oil, remove and replace oil filter element, and refill crankcase - 30 min.
f. Remove and replace fuel filter elements - 30 min.
g. Disconnect battery leads, remove and replace battery, and reconnect battery leads - 10 min.
j. Remove saw blade, change spindle drive ratio, and replace blade with one of a different size. Make any other required changes necessary to properly operate the saw with the new blade - 60 min.

3.2.6 Material. The components, pieces and parts incorporated in the saw set may be newly fabricated from recovered materials to the maximum extent practical, provided the saw set produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the saw set. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials.

3.3 Reliability. The contractor shall furnish a unit capable of providing the services specified in the contract under the specified conditions for the specified life. No unit shall be furnished which possesses parts or qualities known to or suspected of causing premature failure of the saw. Information regarding such parts or qualities shall be forwarded to the contracting officer as it is recognized throughout the contracting period and specified life of the saw. It is the contractors responsibility to correct and, when possible, prevent any damage to the unit caused by latent defects in material or production of the unit.

3.4 Safety.

3.4.1 Protection. All exposed parts subject to high operational temperatures or electrically energized shall be located, insulated, enclosed, or guarded so as to prevent hazards to operating personnel. All moving parts which present a hazard shall be guarded. The blade guard(s) shall protect all nearby personnel from debris and coolant from any saw blade from 18" to 36".

3.4.2 Noise level. Saw design shall minimize personnel exposure to noise. The engine shall possess a muffler located so as to minimize operator exposure to exhaust noise. Sheet metal shall be heavy gage to prevent excessive sheet metal rattle during saw operation.

3.4.3 Sharp edges. All nonfunctional edges shall be rounded or broken so as to not present a safety hazard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.

3.5 Engine. The saw shall be powered by a diesel engine rated at not less than 70 continuous horsepower (net flywheel HP) at 2000 RPM. The engine power rating shall be produced at governed engine speed using both standard grade 2 diesel fuel and JP-8. The engine shall not be harmed using JP-8 jet fuel. For assistance regarding JP-8 and commercial diesel engines, contact SA-ALC/MMPBRE, San Antonio, TX at 512-925-6708. The engine shall not be adversely affected by operating in ambient temperatures of 110°F with full impact of solar radiation. The engine shall possess an electric starting system capable of cranking the motor down to -20°f. The battery shall be protected from the weather and shall possess terminal guards to prevent accidental shorting.

3.6 Power train. Power transmission to the blade shall be via a belt and pulley arrangement or shall be entirely hydrostatic. There shall be a means to enable the saw rpm to be optimized for each of the three saw sizes specified (see 6.2) when the engine is operating at governed speed.

3.7 Blade shaft. Shaft shall be made of hardened steel material.

3.8 Alignment guides. The saws shall possess a means for following a chalk line or a string line. The pointer(s) for aligning the saw with the line and following the line shall be easily viewed by the operator from the operator's station.

3.9 Depth control and indicator. The saw shall have a depth of cut indicator which operates for any standard sized blade from 18" to 36".

3.10 Water system. The saw shall be equipped with a complete blade coolant system. The necessary pumps, valves, hoses, piping, and controls shall be furnished. Provisions shall be made to attach a 3/4 inch garden hose to the system (female fitting on saw). The system shall also mate up with the hoses on the hose reels. All water system fittings shall be solid brass. Piping shall be steel. Each saw shall possess a coolant pump and the ability to regulate the supply of coolant. The coolant spray mechanism shall be adjustable to suit the various saw sizes.

3.11 Propelling mechanism. The saw shall be propelled by the engine through a hydrostatic transmission. Power shall be transmitted from the engine to the drive wheels by power transmission chains or by gears. The travel speed shall be adjustable to any speed between 0 and 150 feet per minute.

3.12 Wheels. The saw shall be furnished with four non-castering wheels. The wheels shall be solid rubber, or cast iron with solid rubber, and shall be arranged with the axles to provide a rigid suspension. The driving forces shall be transmitted to the driving wheels through a point on the wheels that will not contact the surface of the roadway.

3.13. Parking brake. The saws shall possess a means for preventing saw roll-away on a 20 degree slope when the saw blade is raised. The brake system shall be such that the brake either automatically disengages when the drive system engages, or, there is an interlock which prevents the drive from engaging with the brake applied.

3.14 Controls and instrument panel. The following controls and indicators shall be provided. All shall be suitable for prolonged exposure to the weather.

a. Fuel gage - visible from operator's station.
b. Hourmeter - on engine or on instrument panel.
c. Engine tachometer or blade tachometer - on instrument panel.
d. Ignition - on instrument panel.
e. Feed control - lever type on instrument panel.
f. Blade raise/lower control - on instrument panel.
g. Hydraulic fluid level indicator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.

3.15 Performance.

3.15.1 Mobility. The saw shall be maneuverable by one person. It shall be capable of being unloaded from the trailer (with blade mounted), moved to the cut line, aligned, and operated by one person. With the blade raised, a castering wheel(s) shall bare the weight of the rear of the saw to permit easy positioning.

3.15.2 Operation. The saw shall be capable of driving blades suitable for cutting 5000 - 8000 psi concrete to a depth of 10 inches. The saw shall be capable of cutting shallower depths in softer concrete using blades as small as 18". The drive system shall enable optimum blade surface speed to be set for these conditions and saw sizes. There shall be adjustments to compensate for variable blade lead. Adjustment shall be sufficient to allow straight tracking when the blade is switched from one side of the saw to the other.

3.16 Support trailer. A support trailer shall be provided for every pair of saws. The trailer shall be capable of transporting two saws and all accessory gear needed to operate and maintain the saws. The trailer shall possess the necessary plumbing and hoses to take the blade coolant supply from a water truck (or trailer) and distribute it to both saws. The saws shall receive coolant water from the trailer by means of two .75 inch, 100 foot hose reels. The hoses shall possess solid brass fittings compatible with the saws. The trailer shall have a diesel powered self-priming pump capable of overcoming hose losses and supplying sufficient head to the saw coolant pumps. A high pressure suction hose at least 30 feet long shall be provided for obtaining water from the tank to the trailer. The trailer shall have a ramp(s) for easy loading and offloading of the saws. The trailer shall provide stowage for all tools and attachments, including saw blades. The trailer shall possess provisions for securing all equipment to the trailer bed. The trailer shall be equipped with a lunette conforming to MS-51336. The lunette shall be mounted on an adjustable tongue to permit being towed by vehicles with varying pintle hook heights (14 to 30 inches above the ground). The trailer shall have a winch rated for not less than 1200 lbs. The winch shall possess cable and hooks for easy loading of the saws on the trailer. The trailer shall possess a rigid framework to support a removable cover. The framework shall be capable of supporting 200 lbs suspended from any point by a rope. The cover shall be a durable, weather resistant and fungus resistant material of a color closely matching the rest of the trailer. The cover shall be attachable and stowable in five minutes without using any tools. The cover and supporting framework shall be capable of withstanding 50 mph winds without damage. The cover shall enclose the front, top, sides, and rear of the trailer. The rear shall be able to be opened to permit loading, unloading, or entrance of personnel in 30 seconds. The rear shall be able to be securely closed to minimize flapping and to protect the saws from the weather. The cover shall provide at least 78 inches of clearance over the entire width of the trailer floor. The trailer is not intended for high speed travel or for extended road travel and does not require lights. Rear and side reflectors shall be provided. If the trailer is a mid axle type (as opposed to a wagon configuration), it shall possess landing gear to level and stabilize the trailer when not attached to the towing unit.

3.17 Lifting provisions. Permanently affixed attachments that enable the saw trailer (with saws and associated equipment) to be lifted in its normal travel position shall be provided. Each attachment shall meet the requirements specified in MIL-STD-209 for type II equipment, class 1 or 3 provisions. Lifting attachments may also be used as tiedown attachments provided they also meet the requirements of 3.18.

3.18 Tie down provisions. Permanently affixed attachments that permit the saw trailer (with saws and associated equipment) to be fastened to the floor or deck of a transportation medium shall be provided. Each attachment shall meet the requirements specified in MIL-STD-209 for type II equipment, class 2 or 3 provisions. Tiedown attachments may also be used as lifting attachments provided they also meet the requirements of 3.17.

3.19 Data plates. The following plates shall be installed in a conspicuous location.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.

3.19.1 Identification plate. A corrosion resistant metal name plate shall be permanently and legibly marked with the following information (installed on trailer).

Nomenclature
Manufacturer model number
Manufacturer's serial number
Special characteristics (HP, RPM, etc.)
National stock number
Manufacturer's name
Date of manufacturer
Warranty expiration date
Curb weight and CG location

The Manufacturers standard commercial identification plate shall be installed on each saw.

3.19.2 Lubrication plates. Corrosion resistant metal lubrication plates shall illustrate the lubrication points on each saw and on the trailer and shall identify the type of lubricant and service interval for each point (install on each saw and on trailer).

3.19.3 Warning plates. Warning plates shall identify potentially hazardous conditions, locations and actions. Plates shall be sized and located so as to be conspicuous to the person at risk.

3.19.4 Instruction plates. All controls shall be labeled to identify the location and function of each control position. Instructions cast or stamped on or beside the controls are acceptable.

3.20 Treatment and painting. Saws and trailer shall be painted in accordance with standard commercial practice provided that the paint and primer is both lead and chromate free. Color shall be 24052 of FED-STD-595 unless otherwise specified in 6.2. The exterior finish shall show no evidence of uneven application, runs, sags, curtains, orange peel, lack of adhesion, or other defect. All exterior trim items shall be painted to match the chassis.

3.20.1 Markings. Markings will be applied on dark green vehicles utilizing black paint color number 37038. Size of letters and numerals shall be 1 1/2 inches tall. "INFLATE TO XX PSI", where the contractor provides the correct inflation pressure, shall be stenciled near each wheel. "LIFT HERE" AND "TIE DOWN HERE" shall be stenciled near each attachment point as applicable.

3.21 Workmanship. The workmanship shall be of the quality prevailing among manufacturers normally producing equipment of this type. Welded, bolted and riveted construction shall be in accordance with the highest industry standards. Installed hoses, electric cables, fittings, etc. shall be bundled and wrapped where practical, hoses shall be of the proper length.

3.22 First article. When specified (see 6.3), a sample shall be subjected to first article inspection in accordance with para 4.4.

4 QUALITY ASSURANCE.

4.1 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection and testing requirements as specified herein. Except as otherwise specified, the contractor may use any inspection facilities acceptable to the Government. Inspection records of the tests shall be kept complete and available to the Government. The Government reserves the right to perform any of the tests set forth in this specification where such tests are deemed necessary to assure that the vehicle conforms to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:45Z
Check the source to verify that this is the currentversion before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Notification of testing. The Government shall be notified of all testing to be performed in fulfillment of the requirements of this specification so that arrangements may be made to witness the testing. Addresses and specific requirements of such notifications shall be provided in the solicitation, contract, or by the government's contracting officer upon request.

4.2 Classification of tests. Testing shall be of three types, First Article testing performed by the contractor, user testing performed by the Government, and acceptance testing performed by the contractor.

4.2.1 First Article testing. First Article testing, when required (see 6.2), shall be performed on a unit prior to acceptance of any unit by the Government. The First Article test sample may be a preproduction item or a production item which meets the requirements of this specification. The sample shall be identical to the items procured under the contract. Approval of the First Article shall not constitute waiver by the Government of its rights under the contract. First Article testing shall consist of the requirements in section 4.4.

4.2.2 User testing. User testing, when required (see 6.2) shall be performed on the same unit as First Article testing. The contracting officer shall inform the contractor when shipment to the test site is approved. Generally, this will be after the contractor has taken care of any deficiencies revealed by First Article testing. User testing is further explained in section 4.5.

4.2.3 Acceptance testing. Acceptance testing shall be performed on each unit prior to acceptance of that unit. Acceptance testing shall consist of the requirements in section 4.6.

4.3 Test conditions.

4.3.1 Apparatus. The apparatus used in conjunction with the testing specified herein shall be of laboratory precision and shall be calibrated at proper intervals to ensure accuracy.

4.3.2 Preparation for tests. The vehicle, equipped with all specified auxiliary equipment, shall be fully serviced and all equipment shall be prepared for immediate operation.

4.3.3 Test rejection criteria. Throughout all tests specified herein, the vehicle shall be closely observed for the following conditions, any of which shall be cause for rejection.

a. Failure to conform to design or performance requirements specified herein.
b. Spillage or leakage of any fluid, including fuel, coolant, lubrication or hydraulic fluid, under any operation condition except as allowed herein.
c. Structural failure, evidence of impending failure, or permanent deformation of any component or joint.
d. Evidence of excessive wear.
e. Interference between saw components or between the saw and the ground (including all required obstacles.)
f. Misalignment of any component.
g. Evidence of undesirable handling characteristics, including the inability to correct for varying blade lead, excessive vibration, lack or momentary loss of power transmission to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.

blade or drive wheels, engine lugging or speed hunting, inability to follow a straight line, and excessive difficulty maneuvering the saw with the engine off and the blade up.

h. Conditions, which present a safety hazard to personnel during operation, service, or maintenance.

i. Overheating of the engine, transmission, or any other saw component.

4.4 First Article testing.

4.4.1 Examination. The First Article shall be examined for conformance to section 3.

4.4.2 Preliminary operation. This portion of testing shall be performed by one person. Load a saw on a trailer using the winch. Verify that there is sufficient room and sufficient tie down lugs to secure two saws. Tow the trailer at 20 mph for 1 hour (occasional reduced speeds are allowed.) Park the trailer by the test site. Unload the saw and maneuver the saw to the cut line. Set the blade, blade guard, and coolant system for a 3" deep cut in concrete. Connect the cooling system through the trailer and to the water source. Start all engines and pumps in accordance with manufactures recommendations. Saw a test strip 3" deep. Adjust the saw tracking to minimize operator effort in accordance with the procedures described in the operators manual. Note any tools used. Saw a strip 25 feet long by 3" deep following a chalkline. Cut off the coolant supply and verify that the low coolant shut down is operative. Verify that the saw kerf depth is the same as that indicated on the saw. Change the depth to 6". Saw a second test cut and readjust the saw tracking to minimize saw effort. Saw a strip 25 feet long by 6" deep following a chalkline. Verify that the saw kerf depth is the same as that indicated on the saw. Operate all controls stop to stop to verify proper function and ease of control. Difficulty or inability to set or hold a desired operating point with the controls shall be cause for failure.

4.4.3 Maintenance testing. After having performed the inspection according to 4.4.1, an authorized Government representative shall select between four and all of the tasks listed in 3.2.5. These tasks shall be performed sequentially by one person in the sum of the time allotted for each task. All tools, parts, and supplies shall be on hand at the start of the test. The list of tasks performed and the total time taken to perform the tasks shall be recorded. The use of any tools other than common hand tools shall be noted. Power tools shall not be used. The procedures used to perform the maintenance shall be in accordance with the manufacturer's maintenance manuals, a copy of which shall be made available to the Government inspector prior to this test.

4.4.4 Sound level testing. Testing shall be in accordance with the procedures described in SAE J1174, Operator Sound Level Measurement Procedure for Small Engine Powered Equipment. Operator sound level shall not exceed 104 dB(A). (We are aware that this procedure is designed for engines of lesser power.)

4.4.5 Final inspection. The unit shall be examined for signs of any conditions for failure listed in 4.3.3.

4.4.6 Test report. The following shall be incorporated as a part of the test report:

a. All failures, maintenance performed and other events recorded shall be identified by accumulated operation time, miles, cycles or position of the test procedure, as appropriate. Test conditions at the time of failures or irregular operations identified shall be recorded.

b. Summary of the engineering reasoning and of any tests conducted to determine assignable causes for all failures and irregular operations identified.

c. Summary of the engineering reasoning behind any corrections made, to be made, or proposed to be made, and the predicted effectiveness of those corrections.

d. Test activity and/or contractor comments on item features or requirements, that if modified, should improve the item.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:45Z
Check the source to verify that this is the current version before use.

e. Test activity and/or contractor comments on field conditions or operating procedures to be avoided or cultivated to increase the reliability and useful life of the item.
f. The contractor shall furnish the following commercial spec sheets as part of the First Article test report.
   (1) Engine spec sheet.
   (2) Chassis spec sheet.
g. Engine manufacturer's certification that the engine meets minimum horsepower requirements when running on JP-8 jet fuel; and that JP-8 will in no way adversely affect the performance of the engine.
h. The user testing log book resulting from the user testing (see 4.5).

4.5 User testing. The user test sample shall be delivered to Detachment 2, Field 4, Eglin AFB, FL for 35 days (seven days a week) of user testing. The 35 days shall be consecutive, except where interrupted for maintenance or repair downtime, as defined herein. The user test will not begin until after completion of the First Article tests. The user test sample shall not be shipped to Field 4 without prior 15 day notification in writing to the PCO. The test period shall begin the day after the saws, trailer, and associated equipment (if any) arrives at Field 4. The saws shall be available for any one period of 16 consecutive hours each day. The periods shall be scheduled by a Field 4 representative and shall be provided to the contractor at least 12 hours in advance. Any period of more than 4 hours which the saw is out of service for repair or maintenance shall not be considered an available day for the test period. The saw shall be operated and all scheduleed maintenance shall be performed by Air Force personnel using the operation and maintenance procedures contained in the preliminary technical data provided for the test. Any parts or corrective action shall be provided by the contractor. Any maintenance actions performed by the contractor shall not begin before notification to a Field 4 representative, and Government personnel shall be given the opportunity to observe the actions. The contractor shall provide on-site familiarization to the operators and mechanics as necessary to perform this test. Test operations will be used in or will simulate normal Air Force usage and will not exceed any performance criteria specified in section 3. Noncompliance with this purchase description shall be cause for rejection. The log shall be signed by an authorized Air Force representative and the contractor after each day of activity. The daily log shall document, but shall not be limited to the following:

a. Operating time.
b. Tasks completed
c. Technical manual errors or weaknesses.
d. All failures and corrective actions taken.
e. Operational problems encountered.
f. Hurlbert Field representative's comments.

The contractor shall report the user test results, including daily logs of activities, in the First Article test report.

4.6 Acceptance testing. Each unit shall be started and run through the manufacturer's recommended break-in procedure. All controls shall be operated through their full range to ensure proper function. Engage water pump and check blade cooling system. Inspect trailer to ensure pintle height is as specified.

4.7 Refurbishment. After successful completion of all testing and prior to delivery, each unit shall be refurbished to a like-new condition.

5. PACKAGING.

5.1 Preparation for delivery. Preparation for delivery shall be in accordance with the instructions of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:45Z
Check the source to verify that this is the current version before use.

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The saws are intended to be used for emergency repair of bomb damaged runways, for routine pavement work, and for training new operators. They are subject to being deployed world-wide using any standard mode of transportation, including aircraft.

6.2 Ordering data.

a. Title, Number and Date of this specification.
b. Name or Number of any applicable amendments or supplements.
c. Height of pintle with trailer level (see 3.16).
d. User testing required (see 4.4.2).

6.3 First Article. When First Article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a First Article sample, a first production item, or a standard production item from the contractor's current inventory and the number of items to be tested. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of First Article test results and disposition of First Articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for First Article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must finish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Data Requirements. The following Data Item Descriptions (DIDs) must be listed, as applicable, on the Contract Data Requirements List (DD Form 1423) when this specification is applied on a contract, in order to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

DID Number	DID Title	Suggested Tailoring
DI-T-4901	FAT Procedures	See DD Form 1423
DI-T-4902	FA Inspection Report	See DD Form 1423
DI-T-2373A/T	Notification of Test	See DD Form 1423

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Forms 1423.

6.5 Subject term (key word) listing.

Casters
Hydrostatic
Net flywheel horsepower
Pointer
Pump

Custodians:
Air Force - 99

Preparing activity:
Air Force - 84

Project No: 3895-F255

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. *Comments submitted on this form do not constitute or imply authorization to* waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-83806	90 APR 27

3. DOCUMENT TITLE Saw Set, Concrete and Asphalt, 70 HP, For Rapid Runway Repair Applications

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER		
a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY		
a. NAME WR-ALC/MMEDT Robins AFB, GA 31098-5609	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON	
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:45Z
Check the source to verify that this is the current version before use.