MIL-W-80019B
15 March 1976
SUPERSEDING
MIL-W-80019A
12 February 1968

MILITARY SPECIFICATION

* WELDING MACHINES, ARC, DC, GENERATOR, CONSTANT CURRENT, ELECTRIC MOTOR DRIVEN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers direct current, arc welding machines with a constant current arc characteristic and driven by electric motors.

* 1.2 Classification. This specification covers welding machines of the following sizes. The size supplied shall be as specified (see 6.2.1).

Size	Capacity
200	200 amperes
300	300 amperes
400	400 amperes

2. APPLICABLE DOCUMENTS

* 2.1 Military publications. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MIL-I-24092	Insulating Varnish, Electrical, Impregnating
MIL-W-45562	Welding and Soldering Equipment, Supplies and Accessories, Packaging of

FSC 3431

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

STANDARD

MIL-STD-130	Identification Marking of U. S. Military Property

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) OF 1970

Title 29, Code of Federal Regulations, Chapter XVII, Part 1910, and amendments.	Occupational Safety and Health Administration Standards

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION (NEMA) STANDARDS

EW-1	Electric Arc Welding Apparatus
IC-1	Industrial Controls

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th Street, New York, NY 10017.)

(Technical society and technical association standards and specifications are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First Article approval. If First Article approval is required (see 6.2.1 and 6.3), inspection therefor shall be in

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

accordance with Section 4. A First Article comprises a pre-production model or initial production sample; approval involves testing and evaluating the First Article for conformance with the requirements herein before, or in the initial stage of, production under a contract. The approved sample shall be used as the standard for all production items manufactured to fulfill the terms of the contract.

3.2 Design. The welding machines shall be designed so that an experienced weldor can strike and maintain a stable arc, and satisfactorily weld at any setting within the specified range of the machine without losing the welding arc more than once in every six inch (152 mm) weld bead. Unless otherwise specified herein, the welding machines shall conform to the requirements of NEMA EW-1 when applicable. The welding machine shall be completely assembled and compactly mounted. The motor rotor, generator, and rotating exciter armature shall be mounted on a single shaft. The bearings shall be ball, roller or sleeve, having design characteristics commensurable with that required for use in heavy duty industrial type equipment. Replacement bearings shall be commercially available, widely distributed and easy to procure. The welding machines shall supply direct current with a constant current (drooping) volt-ampere characteristic.

* 3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of all parts and components of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1).

* 3.2.2 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the machine presenting safety hazards which can be guarded without substantial interference to operation of the machine. All guards shall provide easy access to guarded parts. Except as otherwise specified by the procuring activity, the machine shall comply with the standards promulgated under OSHA applicable to the machine itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 3.2.3 Materials. Materials shall be as specified herein. Materials not specified herein shall be selected by the manufacturer to meet the requirements of this specification. Only new materials shall be used. Contact between dissimilar metals, especially brass, copper or steel in contact with aluminum or magnesium shall be avoided whenever possible. Materials shall be free from all defects and imperfections that might affect the serviceability and appearance of the finished product.

* 3.2.4 Insulation. Coils shall be insulated by Class A, B, F or H insulation system in accordance with NEMA EW-1 when applicable. Insulation distances and clearances, and ventilation ducts and paths within, shall be as liberal as is economically practicable in order to minimize the need for frequent cleaning.

* 3.2.5 Size and capacity. The sizes and capacities of the welding machines shall be in accordance with NEMA EW-1 Class I, DC, welding machines, when applicable.

3.2.6 Weight and dimensions. The welding machines shall be as lightweight as practical consistent with the strength and reliability as required herein. The welding machines shall not exceed the weights and dimensions (excluding accessories and mounting as required for portability) as specified in Table I.

TABLE I

Weights and Dimensions (maximum)

Size of Machine (Rated Amperes)	Weight of Machine Pounds (kg)	Dimensions, Inches (cm)		
		Length	Width	Height
200	800 (362.4)	46 (116.8)	22 (55.9)	40 (101.6)
300	1100 (498.3)	50 (127)	22 (55.9)	40 (101.6)
400	1200 (543.6)	52 (132.1)	22 (55.9)	40 (101.6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 3.2.7 Power supply. The welding machines shall operate from a power source of 230/460 volts, 60 Hz, 3 phase alternating current, and shall be connected for use on the 460 volt power supply prior to shipment.

* 3.2.8 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances which will permit installation of replacement parts without modification of parts or machines.

3.2.9 Accessibility. All major assemblies and installed attachments shall be accessible for maintenance, repair, and replacement without removal of other major assemblies and installed attachments. Covers or plates such as those on shrouds or housings which must be removed for adjustment or maintenance shall be equipped with screws or bolts.

3.2.10 Lubrication. All bearings (except the sealed for life type), and moving parts where lubrication is required, shall be provided with means for lubrication. If used, grease and oil fittings shall be accessible and have means of sealing the openings to prevent the entrance of dirt and foreign matter.

* 3.2.11 Portability. The welding machines shall be portable, and shall be base mounted. Running gears, if required (see 6.2.1), shall be as specified by the procuring activity. The welding machines shall be provided with a lifting device attached directly to the framework of the machine. The device shall be conveniently located for handling by crane or hoist, and shall be capable of supporting 2-1/2 times the weight of the machine. The center of gravity of the entire unit shall be as low as is consistent with economical design.

3.2.12 Cooling system. The generator and motor shall be forced air cooled by a blower mounted on the rotating shaft. The forced air shall pass around all of the components of the generator and motor to provide effective cooling at all times. Openings shall be so located and designed that water cannot be drawn into the machine with the intake air, and shall be protected by expanded metal screens or the equivalent. Ventilation shall be sufficient to permit continuous operation at rated load at a 60 percent duty cycle. The interior of the machine shall be nominally weatherproof. Any water or precipitation which may enter under extremely adverse weather conditions short of inundation shall cause no damage and result in no malfunction of the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 3.2.13 Temperature rise. The maximum allowable temperature rise of various parts of the machines for the given class of insulation used shall be in accordance with NEMA EW-1, when applicable.

3.3 Construction. The welding machine shall be constructed so that when installed and connected to the specified power supply, it can be used for any purpose for which it was designed. The machine shall be constructed of parts which are sound in structure and free from any repair.

* 3.3.1 Castings and forgings. All castings and forgings shall be free from such defects as scale and mismatching. In no event shall such processes as welding, peening, plugging, or filling with solders or pastes be used on castings or forgings to reclaim any defective parts for use on the machines.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where these operations are required in the original design. These operations shall not be employed as repair measures for defective parts.

* 3.3.3 Fastening devices. All screws, pins, bolts, and retaining fasteners shall be installed with means for preventing loss of tightness. Such parts subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

* 3.3.4 Surfaces. All surfaces of castings, forgings, molded parts, stampings, and welding parts shall be cleaned and free from sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials. External surfaces shall be smooth, and all edges shall be either rounded or beveled unless sharpness is required to perform a necessary function.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machines shall be painted in accordance with the manufacturer's standard commercial practice.

* 3.4 Performance. The welding machine shall provide a satisfactory power source at a 60% duty cycle for direct current welding, both straight and reverse polarity wherein a drooping volt-ampere characteristic is required. Efficiency, operating temperature, and welding current ranges of the welding machine shall conform to NEMA EW-1, when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

3.4.1 Open circuit voltage. The maximum open circuit voltage of the generator shall conform to the requirements of NEMA EW-1.

3.5 Components. The welding machine shall consist of, but not be limited to, the following components: enclosure, motor, generator, exciter, motor starter, and controls.

3.5.1 Enclosure. The welding machine enclosure shall be of the dripproof type so designed and constructed that drops of liquid or solid particles falling on the enclosure from above at angles up to 15 degrees from the vertical cannot enter the machine nor interfere with the satisfactory operation of the equipment within the enclosure. Means for convenient access to terminals and all working parts shall be provided. The machine shall be mounted on a rigid base that will prevent distortion or misalignment of machine and enclosure when placed on an uneven surface.

* 3.5.2 Electric motor. The electric motor shall operate from a power supply (see 3.2.7), and shall be capable of driving the generator to produce the full rated capacity at 60% duty cycle. The welding machine shall not be affected by a ± 10% line voltage fluctuation or ± 5% frequency variation. The rotor and stator shall be concentric with each other to allow uniform and proper air gap. A suitable thermal device or devices shall be provided to protect the motor. These devices shall operate to prevent attainment or continuation of injurious temperature. These devices may either remove the unit from the line or relieve it of its load.

3.5.3 Generator. The welding generator shall be the constant current type, and shall conform to the requirements of NEMA EW-1, when applicable. The commutator of the welding generator shall be designed for efficient commutation with adequate brush surface contact. The brushes shall be metal graphite type for designed long service life. The brush holders shall be designed for easy replacement of the brushes.

3.5.4 Exciter. The exciter for the welding generator shall be the static or the revolving type. The static type shall operate on an input of 110 volts, AC, 60 Hz, derived from a step down transformer installed in the primary circuit of the welding machine. The revolving type exciter shall be mounted or attached to the same common shaft with the motor rotor and generator armature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

3.5.5 Motor starter. The machine shall have an across the line magnetic starter. The starter shall conform to the requirements of NEMA IC-1, when applicable. The starter shall be controlled by a start-stop push button station located on the control side of the enclosure. The starter shall have overload protection on at least 2 of the 3 phases of the line, that will operate to disconnect the motor from the line in the event of an excessive overload. The starter shall disconnect the motor from the line in the event of low voltage or power failure. The restarting of the motor shall be manual. When specified (see 6.2.1), the machine shall have a reduced voltage starter, that will be either magnetically or manually operated. The starter shall be the means of changing the motor connections from a wye relationship to a delta relationship after the motor has reached its approximate operating speed. The magnetic type starter shall be automatic in operation. The manual type starter shall have a simple lever to change the setting of the control from the start to the run position. The instructions on the operation of the manual starter shall be permanently marked on the enclosure near the lever. The starter shall have the air break type contacts.

3.5.6 Controls and instruments. All controls to stop, start, and control the operation of the machine and all necessary instruments to indicate the voltage and amperage of the welding generator shall be mounted on a control panel. The instruments and controls shall be permanently and legibly marked to indicate purpose or setting. The instruments shall be in dust-proof cases, and shall be flush mounted and cushioned to insure long life. A combination volt-ammeter or separate volt meter and ammeter shall be provided. The accuracy of the instruments shall be plus or minus 2% on a full scale reading.

3.5.6.1 Current adjustment. Controls shall be provided so that the current at the applicable voltages can be adjusted to the values specified in NEMA EW-1. Two controls, one for coarse setting and one for fine setting, shall be provided to adjust the current between the minimum and maximum values specified in NEMA EW-1. Coarse settings shall be in increments of not more than 100 amperes. Fine settings shall be in increments of not more than 5 amperes within each coarse setting. Voltage and current adjustments from minimum to maximum values, as specified in NEMA EW-1, may be of the continuous variable type employing two controls, one for voltage and one for current.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

3.5.6.2 Polarity-reversing switch. The welding control shall include a positive action switch for reversing the polarity of the welding terminals. The switch shall be designed to eliminate accidental polarity reversal, and shall be marked to indicate the positions for straight and reverse polarity.

3.5.6.3 Output terminals. The machine shall have output terminals of sufficient size for connection to the terminals of cables capable of carrying the full rated capacity of the generator.

3.5.6.4 Remote current-adjusting device. When specified (see 6.2.1), a remote, current-adjusting device shall be provided. The device shall permit the operator, without leaving the welding position, to adjust the welding current within the selected range of the generator to the same values as those obtained by the fine setting control (see 3.5.6.1) on the generator control panel. The device shall be provided with a 50 foot cable with applicable plug for longer extensions. Provisions shall be made to store the remote control when not in use.

3.6 Special devices. When required (see 6.2.1), special devices shall be as specified.

3.7 Repair parts. When required (see 6.2.1), repair parts shall be as specified.

* 3.8 Fungus and moisture resistance. When specified (see 6.2.1), the equipment shall be treated to resist fungus and moisture as specified below:

a. Electrical components such as switches, fuses, and contacts shall not be treated. Other materials and components inherently fungus resistant or protected by hermetric sealing need not be treated.

b. Circuit elements not covered in (a), which have a temperature rise of not more than 24°C when operated at full load, shall be coated with a fungus resistant varnish. Circuit elements include, but are not limited to, cable, wire, terminal and junction blocks, junction boxes and condensers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

c. Circuit elements such as motor coils, transformer windings, and similar electrical components, which have a temperature rise exceeding 24°C when operated at full load, shall not be coated with a fungitoxic compound. Instead, such components shall be given two coats of varnish conforming to MIL-I-24092 when applicable. The coats shall be applied by vacuum pressure, immersion, centrifugal, pulsating pressure or built-up method so as to fill all interstices in the coils and preclude the entrapment of air or moisture. The sealer coat may also be applied by brushing or spraying.

3.9 Diagram of connections. A diagram of electrical connections shall be attached to the inside of the welding machines, and shall be coated with transparent varnish or a plastic covering.

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate, marked in accordance with MIL-STD-130 when applicable, shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix keyed to the manufacturer's permanent records.

Nomenclature

Manufacturer's name

Manufacturer's model designation

Manufacturer's serial number

Power input characteristics and ratings

Date of manufacture

Contract or order number

Federal Stock Number, National Stock Number or Plant Equipment Code

U S

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 3.11 Identification plate. When specified (see 6.2.1), a separate identification plate of corrosion resistant metal permanently and legibly marked in letters 3/16 inches (4.76 mm) high with the caption "Departmental Activity Identification" shall be securely attached to each machine. The plate shall have blank space for the Government to stamp 25 letters or numbers of the same size as the caption.

* 3.12 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.13 Workmanship. Workmanship of the machines and accessories shall be commensurate with the requirements specified herein and shall be of a quality prevailing among manufacturers normally producing equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First Article inspection. When First Article approval is required under 3.1, First Article inspection shall be performed. Unless otherwise specified (see 6.2.1), First Article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure of the item to pass any examination or test shall be cause for disapproval of the First Article.

* 4.3 Quality conformance inspection. Each item shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the test in 4.5.1, and the inspection in 4.6. Failure of the item to pass any examination, test, or inspection shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 4.4 Examination. Each welding unit shall be visually examined for design, construction, materials, components, electrical equipment, and workmanship to determine compliance with the requirements of 3.2 through 3.3.5 and 3.5 through 3.13.

* 4.5 Tests. Except as otherwise specified (see 6.2.1), all tests shall follow the procedures of NEMA EW-1, when applicable.

4.5.1 High potential test. The welding machine shall be subjected to a high potential test as described in Testing Standards of NEMA EW-1. When the First Article inspection is required, this test shall be performed after the rough handling test in 4.5.2.

* 4.5.2 Rough handling test. A chain or cable shall be attached to the lifting device of the welding machine. The welding machine shall be raised and then dropped to fall freely a distance between six inches (15.2 cm) minimum and ten inches (25.4 cm) maximum upon a solid concrete slab. The drop shall be repeated so that the impact is made on each of the three lower edges of the machine. There shall be no damage to the welding machine as a result of these tests other than minor denting of the cited lower edges.

* 4.5.3 Performance test. The output leads of the welding machine shall be connected to a resistance load bank that is rated in excess of the maximum potential of the welding machine. The welding machine shall be operated through successive periods of ten minutes each in increments of 25, 50, 75 and 100 percent of rated output to determine the output performance of the machine. Disconnect the load bank and make two six inch (152.4 mm) fillet welds using the GMAW process to demonstrate the arc stability of the machine. Evidence of difficulty in establishing or maintaining an arc during the welding shall constitute failure of test and rejection of welding machine.

4.5.4 Motor overload protection test. The welding machine shall be adjusted for maximum output and energized. With the thermostatic protection device temporarily disconnected, the motor overload protection shall operate to either remove the machine from the line or relieve it of its load on application of a dead short to the output terminals. No observable or measurable damage to the machine shall result.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 4.5.5 Temperature rise test. With machine at room temperature, the temperature of primary and secondary windings of the transformer shall be recorded. The welding machine shall be operated at rated load and rated duty cycle until stable temperatures are obtained. Temperatures of the windings shall be recorded at 10 minute intervals until stable temperatures are obtained. The load tests are to be run with resistance loading. Temperature rise shall be in accordance with requirements of 3.2.13.

* 4.5.6 Open circuit voltage test. The welding machine shall be energized at nominal rated primary voltage, and the open circuit voltage shall be in accordance with 3.4.1.

* 4.6 Inspection of preparation for delivery. Preservation, packing, and marking for shipment and storage shall be inspected to determine conformance to the requirements of Section 5.

5. PREPARATION FOR DELIVERY

* 5.1 Preservation, packing, and marking. Unless otherwise specified (see 6.2.1), preservation, packing, and marking shall be in accordance with the requirements of MIL-W-45562, when applicable. Level of preservation and packing shall be as specified.

6. NOTES

* 6.1 Intended use. The welding machines covered by this specification are intended for use where constant current (drooping) volt-ampere characteristic curve is required and where 230/460 volt, 60 Hz, 3 phase alternating current is available.

6.2 Ordering data.

* 6.2.1 Procurement requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

a. Title, number, and date of this specification.

b. Size required (see 1.2).

c. First Article, if required (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

d. Specific type measurement system, if required, specify either "U.S. Customary (US)" or "International System (SI)" (see 3.2.1).

e. Special safety devices, if required (see 3.2.2).

f. Portability if required, specify (see 3.2.11).

g. Painting, if different (see 3.3.5).

h. Motor starter, specify if reduced voltage magnetic starter is required (see 3.5.5).

i. Remote voltage control, if required, specify (see 3.5.6.4).

j. Special devices, if required, specify (see 3.6).

k. Repair parts, if required, specify (see 3.7).

l. Fungus and moisture resistance treatment, when required (see 3.8).

m. Nameplate, if different (see 3.10).

n. Identification, if required (see 3.11).

o. First Article inspection, if different (see 4.2).

p. Quality conformance inspection, if different (see 4.3).

q. Tests, if different (see 4.5).

r. Preparation for delivery, if different (see 5.1).

* 6.2.2 Contract data requirements. Required technical data such as operators manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

* 6.3 First Article. When First Article approval is required under 3.1, the solicitation should adhere to the applicable portions of Section 1, Part 19 of the Armed Services Procurement Regulation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

* 6.4 Safety and health determinations. In order that equipment integrated into the user's operational environment will comply with the standards promulgated under Occupational Safety and Health Act of 1970, limitation and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc. as applicable, specific requirements concerning guarding the points of operation, and other safety and health requirements should be specified.

* 6.5 Mercury restrictions. When the use of mercury or its compounds in the machine and its components and accessories is to be prohibited, procurement documents should include a statement to that effect.

* 6.6 Marginal notations. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous issue.

* 6.7 Supersession data. This revision supersedes MIL-W-80019A, and the classification of the welding machines in 1.2 was changed to delete Size 600 welding machines.

Custodians:
Army - WC
Navy - SH
Air Force - 84

Review Activities:
Army - WC
Navy - SH
Air Force - 84
DSA - GS

User Activities:
Army - WV, SM
Navy - MC, CG, YD, AS
DSA - GS

Preparing Activity:
DSA-IP

Project Number:
3431-0112

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/3349

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

FOLD

HEADQUARTERS
DEFENSE INDUSTRIAL PLANT EQUIPMENT CENTER
MEMPHIS, TENNESSEE 38114

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD-304

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TFM
Memphis, Tennessee 38114

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.