FED. SUP CLASS
6640

USER ACTIVITIES: ARMY - CE
REVIEWER ACTIVITIES: ARMY - ME, MD

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 29 SEP 1959 REVISED (A) 09 NOV 1967 (B) 21 JAN 1981 (C) 15 SEP 1988

PART NUMBER	CAPACITY (mL)	WEIGHT (g) CRUCIBLE	COVER
MS35974-3	10	8	2
MS35974-4	15	12	3
MS35974-1	20	16	4
MS35974-5	25	20	5
MS35974-2	30	24	6
MS35974-6	50	40	9

MATERIAL. Platinum, 99.9 percent pure, alloyed with not more than 0.4 percent iridium.

DESIGN. Crucibles shall be of one-piece construction.

Covers shall be flat, sunken in the center, and shall have an extention to serve as a handle. The sunken area in the center shall fit inside the crucible.

© NOTES:

1. The procurement document for MS35974-1 is ASTM E 785.
2. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.
3. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
4. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this standard to the extent specified herein.

P. A.	EA	INTERNATIONAL INTEREST	TITLE
Other Cust	MS 99		CRUCIBLE, IGNITION, LABORATORY platinum, with tongue-type cover
PROCUREMENT SPECIFICATION	See Note 1	SUPERSEDES:	

MILITARY STANDARD
MS 35974
SHEET 1 OF 1

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NUMBER 6640-1517-04

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:32Z
Check the source to verify that this is the current version before use.