REVIEW ACTIVITIES: AIR FORCE - 82

USER ACTIVITIES: ARMY - CE, ME, MI

FED. SUP CLASS
6640



PART NUMBER	NOMINAL DIMENSIONAL DATA (in.)			DELIVERY RATE (gpm)
	DELIVERY TUBE LENGTH	STOPPER SIZE		
		TOP OD	BOTTOM OD	
MS36080-1	44	2-1/2	1-3/8	2
MS36080-2				

MATERIAL: MS36080-1 inlet tube shall be lead.

MS36080-2 inlet tube shall be polyethylene.

Bulb and stopper shall be of new rubber, free from imperfections.

DESIGN: Pump shall have a pressure relief valve and shall be designed for use in glass carboys.

NOTE: Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements as specified herein.

APPROVED 21 JUN 1961 REVISED (A) 20 SEP 1968

(A) ENTIRE STANDARD REVISED

P.A.	MU	TITLE	MILITARY STANDARD
Other Cust	MS 82	PUMP, ACID, HAND	MS36080
Procurement Specification NONE		SUPERSEDES:	SHEET 1 OF 1

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

DD FORM 1 SEP 63 672 (Coordinated)

EDITION OF 1 SEP 57 MAY BE USED.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-512/A-1643

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:34Z
Check the source to verify that this is the current version before use.