FED. SUP CLASS
6640



PART NUMBER	OUTSIDE DIAMETER ± 0.5 mm	LENGTH ± 2.5 mm	WALL THICKNESS ± 0.2 mm	CAPACITY TO NECK ml
MS36191-1	13	100	1.2	7

MATERIAL: Borosilicate glass in accordance with Federal Specification DD-G-541, Type I, Class A.

DESIGN: Test tube shall be in accordance with Federal Specification NNN-T-189, Type I, Style IV.

Test tube shall be cylindrical, with a round bottom and with a standard taper joint to receive a number 8 or 9 glass pennyhead standard taper stopper.

NOTES:
1. A solid pennyhead glass stopper shall be furnished with each test tube.
2. For design feature purposes this standard takes precedence over procurement document referenced herein.
3. Referenced documents shall be of the issue in effect on date of invitations for bid.

APPROVED 30 DEC 1960 REVISED (A) 20 June 1969

USER ACTIVITIES: ARMY - EL, ME

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document

(A) ENTIRE STANDARD REVISED

P.A. MU Other Cust MS	TITLE TEST TUBE with pennyhead stopper		MILITARY STANDARD MS36191
Procurement Specification NNN-T-189	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 SEP 61 672 (Coordinated)

EDITION OF 1 SEP 57 MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:35Z
Check the source to verify that this is the current version before use.