INCH-POUND

MIL-M-28787/238A(SH)
AMENDMENT 2
8 March 1991
SUPERSEDING
AMENDMENT 1
23 April 1985

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, KEY CODE GHM

This amendment forms a part of Military Specification MIL-M-28787/238A(EC), dated 3 August 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* TABLE I, Test conditions D1-D24, Min columns: Delete "0.01" (five places) and substitute "0 0" (five places).

PAGE 5

TABLE I, Test conditions Q1-Q12, Max columns: Delete "900" (five places) and substitute "1200" (five places).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:52Z
Check the source to verify that this is the current version before use.

PAGE 6

* 4.4.2: Delete and substitute the following.

"4.4.2 Order of testing. Test conditions A through T shall be performed in any order with the following exceptions. Test conditions A, C, D, and E are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, C, D, and E where applicable, followed by the remaining tests in the sequence."

* 4.5.1, fifth line: Delete "E" and substitute "F".

* 4 5.3, third line: Delete "E" and substitute "F"

* 4.5.3, sixth line: Delete "E through T" and substitute "F through S".

PAGE 12

* FIGURE 5, NOTE. Delete and substitute the following:

"NOTES:
1. For test condition A, penetrate the anodized finish on the module frame with a sharply pointed probe connected to the negative terminal.

2. For test conditions B1 and B2, the megohm bridge voltage is 30Vdc ± 10%."

PAGES 15 AND 16

* TABLE VI, Test conditions D1-D24, Min columns: Delete "0.01" (two places) and substitute "0 0" (two places).

PAGES 45 AND 46

TABLE XVII, Test conditions Q1 through Q12, Max column Delete "900" (two places) and substitute "1200" (two places)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:52Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH

(Project 5963-N782)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:52Z
Check the source to verify that this is the current version before use.