INCH-POUND

MIL-M-28787/244A
AMENDMENT 1
30 September 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, AND, DIGITAL, KEY CODE DQJ

This amendment forms a part of Military Specification MIL-M-28787/244A(EC), dated 12 October 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions J1-J8, Test type column: Delete "X" and substitute "S".

PAGE 5

TABLE I, Test conditions Q1-Q8, Max columns: Delete "400" (five places) and substitute "550" (five places).

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through U shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and J are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or J are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and J where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "D through T" and substitute "E through H and K through T".

4.5.3, third line: Delete "D through U" and substitute "E through H and K through U".

4.5.3, sixth line: Delete "D through U" and substitute "E through H and K through U".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:54Z
Check the source to verify that this is the current version before use.

PAGE 44

TABLE XVI, Test conditions Q1 through Q8, Max column: Delete "400" (one place) and substitute "550" (one place).

PAGE 51

FIGURE 20, NOTE: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0200)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:54Z
Check the source to verify that this is the current version before use.