INCH-POUND

MIL-M-28787/245A(SH)
AMENDMENT 1
19 November 1990

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

AMPLIFIER, AGC, ANALOG, KEY CODE DPA

This amendment forms a part of Military Specification MIL-M-28787/245A(EC), dated 30 November 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I Delete and substitute new table I as printed on page 3 of this amendment.

PAGE 5

TABLE I. Delete test conditions M6 and M8.

PAGE 6

4 4 2, third line Delete "A, B, C" and substitute "C, A, B"

PAGE 28

TABLE XIII· Delete and substitute new table XIII as printed on page 4 of this amendment

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:55Z
Check the source to verify that this is the current version before use.

PAGE 29

FIGURE 15 Delete "and dissipation" from figure title

Preparing activity:
Navy - SH

(Project 5963-N803)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:55Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements

Test cond.	Parameter	Ref test table	Test type 1/-3/	Acceptance requirements 25 ± 5°C ambient temperature				Operating temperature 0 to 60°C				Unit
				Initial		End-of-life		Initial		End-of-life		
				Min	Max	Min	Max	Min	Max	Min	Max	
A	V_S stress	II	Q	-500	+500	-500	+500	-500	+500	-500	+500	mV
B1	Output short circuit current	III	S	1	40	1	40	1	40	1	40	mApk
B2	Output short circuit current	III	S	-1	-40	-1	-40	-1	-40	-1	-40	mApk
C1	Isolation, frame	IV	S	10	∞	10	∞	10	∞	10	∞	MΩ
C2-C26	Isolation	IV	X	10	∞	10	∞	10	∞	10	∞	MΩ
D1, D2	Power supply current	V	S	0.8	15.0	0.8	15.0	0.8	15 0	0.8	15 0	mA
E	Maximum gain	VI	X	0.75	1.25	0.50	1 50	0.75	1.25	0 50	1 50	V rms
F	Minimum gain	VII	X	0.75	1.25	0.50	1.50	0 75	1 25	0 50	1 50	V rms
G1	AGC time constant, attack	VIII	X	2	6	2	6	2	7	2	8	s
G2	AGC time constant, attack	VIII	X	0	5	0	5	0	5	0	6	s
G3	AGC time constant, decay	VIII	X	5	11	5	11	4	12	4	12	s
G4	AGC time constant, decay	VIII	X	0	6	0	6	0	6	0	6	s
H	Supply voltage rejection	IX	S	0	100	0	100	0	100	0	100	mV
J1	Bandwidth	X	S	20	100	20	100	20	100	20	100	kHz
J2	Bandwidth	X	S	1	20	1	20	1	20	1	20	Hz
K1	Output voltage swing	XI	X	8.5	13.5	8.5	13.5	8.5	13 5	8 5	13 5	V
K2	Output voltage swing	XI	X	-8.5	+13.5	-8 5	-13 5	-8.5	-13 5	-8 5	-13 5	V
I	Noise	XII	X	0	100	0	100	0	100	0	100	mV rms
M1, M2	Capacitance	XIII	S	0.075	0.125	0 075	0 125	0 075	0 125	0 075	0 125	µF
M3	Capacitance	XIII	S	0.9	1 1	0.9	1.1	0.9	1.1	0 9	1 1	µF
M4	Capacitance	XIII	S	3,330	4,480	3,330	4,480	3,330	4,480	3,000	5,000	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:55Z
Check the source to verify that this is the current version before use.

TABLE XIII. Capacitance test.

Test condition	Parameter	Connect		Initial limits 25 ± 5°C, ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
M1	C1 capacitance	20	8	0 075	0.125	µF	15
M2	C2 capacitance	1	8	0 075	0 125	µF	15
M3	C3 capacitance	6	8	0 9	1 1	µF	15
M4	C4 capacitance	7	8	3,330	4,480	pF	15

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers