INCH-POUND

MIL-DTL-32139/4
w/AMENDMENT 1
21 July 2004
SUPERSEDING
MIL-DTL-32139/4
16 December 2003

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, NANOMINIATURE, DUAL ROW, RECEPTACLE, POLARIZED SHELL, SOCKET CONTACTS, CRIMP TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32139.




FIGURE 1. Nano connector dimensions and configurations


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

Insert arrangement	A	B BSC	C BSC
9	.375 (9.52)	.270 (6.86)	.163 (4.14)
15	.450 (11.43)	.345 (8.76)	.238 (6.04)
21	.525 (13.33)	.420 (10.67)	.313 (7.95)
25	.575 (14.60)	.470 11.94)	.363 (9.22)
31	.650 (16.51)	.545 (13.84)	.438 (11.12)
37	.725 (18.41)	.620 (15.75)	.513 (13.03)
51	.900 (22.86)	.795 (20.19)	.688 (17.47)

Inches	mm	Inches	mm
.0015	0.038	.040	1.02
.003	0.08	.037	0.94
.004	0.10	.042	1.07
.005	0.13	.0575	1.460
.010	0.25	.068	1.73
.0125	0.317	.072	1.83
.0135	0.343	.090	2.29
.018	0.46	.110	2.80
.0185	0.470	.125	3.18
.020	0.51	.225	5.71
.025	0.63		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm) angular tolerance ±2°.
4. Surface from which the lead length is measured.
5. Shell shall be flush to insulator within ±.004 inch (0.10 mm).
6. 30 AWG wire is the largest wire size that can be used in the connector assembly.

FIGURE 1. Nano connector dimensions and configurations - Continued.




Inches	mm
.0015	0.038
.033	0.84
.075	1.90
.098	2.49
.108	2.743
.110	2.79

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm).

FIGURE 2. Nano connector interface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.



NOTES:
1. Engaging face of insert shown.
2. Cavity identification numbers are for reference only and do not appear on the part.

FIGURE 3. Nano connector insert arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration see figures 1, 2, and 3.


This specification sheet describes the socket side of a rectangular connector. This connector uses reverse gender contacts, i.e., the live pin is recessed in the insulator with the static socket protruding from a shrouded interface.

Contact connection: The socket contact, which is exposed in the insulator, is normally connected to the neutral side of the circuit.

Sockets are terminated with 30 AWG wire.

Mating plug: Shall be in accordance with MIL-DTL-32139/3.

Part or Identifying Number (PIN):



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

Insert arrangement	Wire type 1/	
A = 9	01 = NEMA HP3-ETXBBB9	6 inches (152 mm) long
B = 15	02 = NEMA HP3-ETXBBB9	18 inches (457 mm) long
C = 21	03 = NEMA HP3-ETXBBB9	36 inches (914 mm) long
D = 25	04 = NEMA HP3-ETXBBB( )	6 inches long 2/
E = 31	05 = NEMA HP3-ETXBBB( )	18 inches long 2/
F = 37	06 = NEMA HP3-ETXBBB( )	36 inches long 2/
G = 51	07 = MIL-W-22759/33-30-9	6 inches (152 mm) long 3/
	08 = MIL-W-22759/33-30-9	18 inches (457 mm) long 3/
	09 = MIL-W-22759/33-30-9	36 inches (914 mm) long 3/
	10 = MIL-W-22759/33-30-( )	6 inches (152 mm) long 2/ 3/
	11 = MIL-W-22759/33-30-( )	18 inches (457 mm) long 2/ 3/
	12 = MIL-W-22759/33-30-( )	36 inches (914 mm) long 2/ 3/
	13 = 04047-30A-9	6 inches (152 mm) long
	14 = 04047-30A-9	18 inches (457 mm) long
	15 = 04047-30A-9	36 inches (914 mm) long
	16 = 04047-30A-( )	6 inches (152 mm) long 2/
	17 = 04047-30A-( )	18 inches (457 mm) long 2/
	18 = 04047-30A-( )	36 inches long 2/

Hardware 4/	Shell finish	Space class
T = Thread hole	C = Aluminum cadmium finish	Blank for non space applications.
	N = Aluminum electroless nickel finish 5/	S = Space class
	S = Passivated stainless steel	
	T = Titanium	

1/ Pig tail wire lead tolerance is +1.00 inch/-0.0 inch (25.4/-0.0 mm).
2/ Color coding in accordance with MIL-STD-681, system 1, except using ten solid colors only in repeating sequence.
3/ Corrosion has been experienced on M32139 connectors that are prewired with MIL-W-22759/33 wires and stored in a sealed environment. CAUTION SHOULD BE EXERCISED WHEN USING THIS WIRE.
4/ Supplied installed.
5/ When aluminum shells are required for space applications electroless nickel finish is the only finish acceptable for space applications (see MIL-DTL-32139).

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents: In addition to MIL-DTL-32139, this document references the following:

MIL-W-22759/33	DSCC 04047
MIL-DTL-32139/3	NEMA HP3
MIL-STD-681	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA -CC

Preparing activity:
DLA - CC

(Project 5935-4678-000)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://www.dodssp.daps.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.