DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, NANOMINIATURE, SINGLE ROW, PLUG, POLARIZED SHELL, PIN CONTACTS, HORIZONTAL PCB THROUGH-HOLE TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32139.




FIGURE 1. Nano connector dimensions and configurations.


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

Insert arrangement	A	B BSC	C BSC	D MAX
9	.500 (12.70)	.395 (10.03)	.284 (7.21)	.295 (7.49)
15	.650 (16.51)	.545 (13.84)	.434 (11.02)	.445 (11.30)
21	.800 (20.32)	.695 (17.65)	.584 (14.83)	.595 (15.11)
25	.900 (22.86)	.795 (20.19)	.684 (17.37)	.695 (17.65)
31	1.050 (26.67)	.945 (24.00)	.834 (21.18)	.845 (21.46)
37	1.200 (30.48)	1.095 (27.81)	.984 (24.99)	.995 (25.27)
51	1.550 (39.37)	1.445 (36.70)	1.334 (33.88)	1.345 (34.16)

Inches	mm
.001	0.03
.003	0.08
.005	0.13
.007	0.18
.010	0.25
.012	0.30
.020	0.51
.0725	1.842
.105	2.67
.110	2.79
.130	3.30
.365	9.27

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .005 inch (0.13 mm) angular tolerance ±2°.
4. Surface from which the lead length is measured.
5. Shell shall be flush to insulator within ± .004 inch (0.10 mm).
6. Tail finish is tin/lead or gold

FIGURE 1. Nano connector dimensions and configurations – Continued.




INTERFACE DETAIL

Inches	mm
.0015	0.038
.033	0.84
.074	1.88
.084	2.13

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .005 inch (0.13 mm).

FIGURE 2. Nano connector interface.


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.



NOTES:
1. Engaging face of insert shown.
2. Cavity identification numbers are for reference only and do not appear on the part.

FIGURE 3. Nano connector insert arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.



Insert arrangement	E
9	.200 (5.08)
15	.350 (8.89)
21	.500 (12.70)
25	.600 (15.24)
31	.750 (19.05)
37	.900 (22.86)
51	1.250 (31.75)

Inches	mm
.001	0.03
.013	0.33
.016	0.41
.025	0.64
.050	1.27

NOTES:
1. Reference figure 1 for hole pattern alignment orientation detail.
2. Dimensions are in inches.
3. Metric equivalents are given for information only.
4. Unless otherwise specified tolerances are ± .005 inch (0.13 mm) angular tolerance ±2°.

FIGURE 4. Nano connector suggested PCB hole pattern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration see figures 1, 2, and 3.


This specification sheet describes the pin side of a rectangular connector. This connector uses reverse gender contacts, i.e., the live pin is recessed in the insulator with the static socket protruding from a shrouded interface.

Contact connection: The pin contact, which is recessed in the insulator, is normally connected to the live side of the circuit.

Pins are terminated to a printed circuit board (PCB) as defined in figure 4.

Mating receptacle: Shall be in accordance with MIL-DTL-32139/2, MIL-DTL-32139/6, and MIL-DTL32139/8.

Part or Identifying Number (PIN):



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

Insert Arrangement	Tail Finish
A = 9	01 = Tin/Lead
B = 15	02 = Gold
C = 21	
D = 25	
E = 31	
F = 37	
G = 51	

Hardware [1/]	Shell and Finish	Space class
S = Jackscrew captivated	C = Aluminum shell, cadmium finish	Blank for non-space applications
	N = Aluminum shell, electroless nickel finish [2/]	S = Space class
	S = Passivated stainless steel shell	
	T = Titanium shell	
	A = Pure Electrodeposited Aluminum	
	Z = Zinc Nickel	
	F = Nickel Fluorocarbon Polymer	

1/ Supplied installed.
2/ When aluminum shells are required for space applications, electroless nickel shall be used. Cadmium finish is not acceptable (see MIL-DTL-32139).

Alternate shell finishes:

Pure Electrodeposited Aluminum. Pure dense electrodeposited aluminum shall be in accordance MIL-DTL-83488, type II shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Nickel Fluorocarbon Polymer. High phosphate nickel with fluorocarbon polymer additive, over suitable underplate shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Zinc Nickel. Zinc Nickel Alloy shall be in accordance with ASTM B841, over a suitable underplate shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.

Referenced documents: In addition to MIL-DTL-32139, this document references the following:

MIL-DTL-32139/2
MIL-DTL-32139/6
MIL-DTL-32139/8
MIL-DTL-83488
ASME B18.3
ASTM B841

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AV, MI
Air Force - 99

Preparing activity:
DLA - CC

(Project 5935-2013-177)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:54Z
Check the source to verify that this is the current version before use.