INCH-POUND

MIL-M-28787/212A(SH)
AMENDMENT 1
8 March 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

STANDARD SERIAL OUTPUT, DIGITAL, KEY CODE DQD

This amendment forms a part of Military Specification MIL-M-28787/212A(EC), dated 24 June 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

4.4.2 Delete and substitute the following.

"4 4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and F where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "D through V" and substitute "E and G through V"

PAGE 5

TABLE I, Test conditions D1-D15 and D16, Test type column. Delete "X" and substitute "S".

TABLE I, Test conditions F1-F10, F12-F21 and F11, Test type column: Delete "X" and substitute "S".

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:41Z
Check the source to verify that this is the current version before use.

PAGE 10

4 5.3, third line. Delete "D through V" and substitute "E and G through V".

4.5.3, sixth line. Delete "D through X" and substitute "E and G through V and X".

Preparing activity:
Navy - SH

(Project 5963-N778)

Agent. NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:41Z
Check the source to verify that this is the current version before use.