INCH-POUND

MIL-M-28787/213A(SH)
AMENDMENT 1
8 March 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

CONVERTER, PARALLEL/SERIAL, KEY CODE EQG

This amendment forms a part of Military Specification MIL-M-28787/213A(EC), dated 7 August 1979, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

TABLE II, Test condition E, Min columns: Delete "-6" (four places) and substitute "-130" (four places).

TABLE II, Test condition E, Max columns: Delete "-130" (four places) and substitute "-6" (four places).

TABLE II, Test conditions G1-G37, Min columns: Delete "-" (four places) and substitute "-1.5" (four places).

TABLE II, Test conditions G1-G37, Max columns: Delete "-1.5" (four places) and substitute "0" (four places).

TABLE II, Test conditions L1-L32, Min columns: Delete "-0.1" (four places) and substitute "-0.4" (four places).

TABLE II, Test conditions L1-L32, Max columns: Delete "-0.4" (four places) and substitute "-0.1" (four places).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-20T16:42Z
Check the source to verify that this is the current version before use.

TABLE II, Test condition L33, Min columns: Delete "-0.1" (four places) and substitute "-1.6" (four places).

TABLE II, Test condition L33, Max columns: Delete "-1.6" (four places) and substitute "-0.1" (four places).

PAGE 8

TABLE II, Test conditions L34, L35, Min columns: Delete "-0.10" (four places) and substitute "-3.91" (four places).

TABLE II, Test conditions L34, L35, Max columns: Delete "-3.91" (four places) and substitute "-0.10" (four places).

TABLE II, Test conditions L36, L37, Min columns: Delete "-0.1" (four places) and substitute "-3.2" (four places).

TABLE II, Test conditions L36, L37, Max columns: Delete "-3.2" (four places) and substitute "-0.1" (four places).

TABLE II, Test condition N1, Min columns: Delete "5" (four places) and substitute "2" (four places).

TABLE II, Test condition N2, Min columns: Delete "6" (four places) and substitute "3" (four places).

PAGE 12

4.4.2: After the first sentence, insert the following sentence: "Test conditions A, B, C, D, E and G are stress tests and shall be performed only at 25 ± 5°C."

Source: https://assist.dla.mil -- Downloaded: 20261O-20T16:42Z
Check the source to verify that this is the currentversion before use.

PAGE 29

TABLE VII, Test condition E, Min column: Delete "-6" (one place) and substitute "-130" (one place).

TABLE VII, Test condition E, Max column: Delete "-130" (one place) and substitute "-6" (one place).

PAGES 45 AND 46

TABLE IX, Test conditions G1 through G37, Min columns: Delete "-" (all test conditions) and substitute "-1.5" (all test conditions).

TABLE IX, Test conditions G1 through G37, Max columns: Delete "-1.5" (all test conditions) and substitute "0" (all test conditions).

PAGES 58 AND 59

TABLE XIII, Test conditions L1 through L32, Min columns: Delete "-0.1" (all test conditions) and substitute "-0.4" (all test conditions).

TABLE XIII, Test conditions L1 through L32, Max columns: Delete "-0.4" (all test conditions) and substitute "-0.1" (all test conditions).

PAGE 59

TABLE XIII, Test condition L33, Min column: Delete "-0.1" (one place) and substitute "-1.6" (one place).

TABLE XIII, Test condition L33, Max column: Delete "-1.6" (one place) and substitute "-0.1" (one place).

TABLE XIII, Test conditions L34 and L35, Min column: Delete "-0.10" (two places) and substitute "-3.91" (two places).

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T16:42Z
Check the source to verify that this is the currentversion before use.

TABLE XIII, Test conditions L34 and L35, Max column: Delete "-3.91" (two places) and substitute "-0.10" (two places).

TABLE XIII, Test conditions L36 and L37, Min column: Delete "-0.1" (two places) and substitute "-3.2" (two places).

TABLE XIII, Test conditions L36 and L37, Max column: Delete "-3.2" (two places) and substitute "-0.1" (two places).

PAGE 63

TABLE XV, Test condition N1, Min column: Delete "5" (one place) and substitute "2" (one place).

TABLE XV, Test condition N2, Min column: Delete "6" (one place) and substitute "3" (one place).

Preparing activity:
Navy - SH

(Project 5963-N800)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:42Z
Check the source to verify that this is the current version before use.