INCH-POUND

MIL-M-28787/216B(SH)
AMENDMENT 1
19 July 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RESISTOR, PULLUP, POWER, KEY CODE ADL

This amendment forms a part of Military Specification MIL-M-28787/216B(EC), dated 13 March 1986, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I: Delete and substitute new table I as printed on page 3 of this amendment

PAGE 5

4.4.2· Delete and substitute the following:

"4 4.2 Order of testing Test conditions A through D shall be performed in any order with the following exceptions. Test condition A is a stress test and shall be performed only at 25 ± 5°C. If test condition A is part of a sequence of tests, the order of testing shall be as follows· A where applicable, followed by the remaining tests in the sequence "

4 5 1, fifth line· Delete "B through D" and substitute "B through C"

4.5 3, third line Delete "B through D" and substitute "B through C".

4.5.3, sixth line· Delete "A through D" and substitute "B through D".

Preparing activity:
Navy - SH

(Project 5963-N757)

Agent: NW

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:44Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	25 ± 5°C 4/		Class I 4/				Class II 4/				Unit
						0 ± 5°C		60 ± 5°C		-55 ± 5°C		85 ± 5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
A1	Isolation, circuit to circuit													
	Initial	II	X	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
	End-of-life	II	X	1	∞	1	∞	1	∞	1	∞	1	∞	MΩ
A2	Isolation, frame													
	Initial	II	S	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
	End-of-life	II	S	1	∞	1	∞	1	∞	1	∞	1	∞	MΩ
B1-B36	Resistance													
	Initial	III	X	2,090	2,310	2,050	2,350	2,050	2,350	2,050	2,350	2,050	2,350	Ω
	End-of-life	III	X	2,035	2,365	2,024	2,376	2,024	2,376	2,024	2,376	2,024	2,376	Ω
C1, C2	Capacitance	IV	X	0.037	0.057	0 037	0.057	0.037	0.057	0.037	0.057	0 037	0.057	μF
C3, C4	Dissipation factor	IV	X	0	5	0	5	0	5	0	5	0	5	%
D1-D36	Crosstalk	V	Q	0	10	0	10	0	10	0	10	0	10	mV rms

1/ "X" parameters shall be 100 percent tested during module acceptance tests.
2/ "S" parameters shall be sample acceptance tested (1 percent or two modules from each inspection lot, whichever is greater) at 25°C
3/ "Q" parameters shall be tested during qualification testing only.
4/ Unless otherwise specified, limits are for initial and end-of-life.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:44Z
Check the source to verify that this is the current version before use.