MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

FLIP-FLOP, JK, DIGITAL, KEY CODE JDF

This amendment forms a part of Military Specification MIL-M-28787/224A(EC), dated 29 June 1982, and is approved for use by the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

* 4.4.2, delete and substitute the following:

"4.4.2 Order of testing. Test condition A through BB shall be performed in any order with the following exceptions. Test conditions A, B, and C are stress tests and will be performed at 25°C ±5°C. If test conditions A, B, C, or D are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D where applicable, followed by the remaining tests in the sequence."

PAGE 8

6.4, Output drive current maximum capability, Low level (V_{OL} = 0.4 V): Delete "20 mA" and substitute "16 mA".

PAGE 59

FIGURE 25, notes 1 and 2(c): Delete "120" (two places) and substitute "75" (two places).

PAGE 69

* FIGURE 30, note 3(a): Delete "120 Hz" and substitute "1 kHz".

NOTE: The margin of this amendment is marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N665)

FSC 5963

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:47Z
Check the source to verify that this is the current version before use.