MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC
TRANSFORMER, SCOTT-T, ANALOG, KEY CODE PTE

This amendment forms a part of Military Specification MIL-M-28787/226A(EC). dated 25 September 1980, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions F23 and F32, Min columns: Delete "-0.020", "-0.020", "-0.025", and "-0.025" (two places) and substitute "-0.040", "-0.040", "-0.045", and "-0.045" (two places) respectively.

TABLE I, Test conditions F23 and F32, Max columns: Delete "0.020", "0.020", "0.025", and "0.025" (two places) and substitute "0.040", "0.040", "0.045", and "0.045" (two places) respectively.

PAGE 19

TABLE VII, Test conditions F23 and F32, Min column: Delete "44.980" (two places) and substitute "44.960" (two places).

TABLE VII, Test conditions F23 and F32, Max column: Delete "45.020" (two places) and substitute "45.040" (two places).

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N439)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:47Z --
Check the source to verify that this is the current version before use.