MILITARY SPECIFICATION

LINER, UTILITY PAIL, PLASTIC, CONDUCTIVE, DISPOSABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and two sizes of disposable, conductive, plastic, utility pail, liners.

1.2 Classification. The liners shall be of the following sizes, as specified (6.2):

Size I	- 20 inches by 24 inches
Size II	- 24 inches by 30 inches

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-585	- Boxes, Wood, Wirebound.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-676	- Boxes, Set-Up, Paperboard.

MILITARY

MIL-L-10547	- Liners, Case, and Sheet, Overwrap; Water-Vaperproof or Waterproof, Flexible.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Headquarters, Defense Personnel Support Center, ATTN: Directorate of Medical Materiel, Code ATT, 2800 South 20th Street, Philadelphia, Pa. 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 56A Standard for the Use of Inhalation Anesthetics

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

3. REQUIREMENTS

3.1 First article. When specified in the procurement document, the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.1.2.1 and 6.2).

3.2 Materials. The utility pail liners shall be fabricated of permanently-conductive, 0.002 inch (nominal) thick plastic.

3.3 Construction. Each liner shall have an opening in one edge. The opening shall extend across the full width of the liner. The other three edges shall contain no openings, cuts, tears, rips or intermittent heat seals. The liners shall show no evidence of leakage when tested as specified in 4.4.2.

3.3.1 Size I. The finished dimensions of the size I liners, with the liners laying flat, shall be 20±1/2 inches wide by 24±1/2 inches long.

3.3.2 Size II. The finished dimensions of the size II liners, with the liners laying flat, shall be 24±1/2 inches wide by 30±1/2 inches long.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:55Z
Check the source to verify that this is the current version before use.

3.4 Electrical conductivity. The liners shall meet the requirements for Reduction of Electrostatic Hazard-Accessories as specified in NFPA 56A when tested as specified in 4.4.1.

3.5 Identification marking. Each liner may be marked permanently and legibly with the name or registered trademark of the manufacturer.

3.6 Workmanship. Workmanship shall be first class throughout. Liners shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual and auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection.
b. Quality conformance inspection.

4.1.2.1.1 First article inspection. First article inspection shall be performed on the liners when a first article sample is required (see 3.1). This inspection shall include examination of 4.3 and tests of 4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:55Z
Check the source to verify that this is the current version before use.

4.1.2.1.2 Quality conformance inspection. Quality conformance inspection shall include the examination of 4.3 and tests of 4.4.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the materials may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificates shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the Item Identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, and table I. The unit of product for sampling purposes shall be one liner.

TABLE I. Sampling for examination

	Inspection level	AQL (defects per hundred units)
For visual examination		
Major defects	II	2.5
For dimensional examination	S-1	6.5

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and table II. The unit of product for sampling purposes shall be one liner.

TABLE II. Sampling for tests

Component (Unit of product)	Characteristic	Requirement	Test Procedure	Inspection level	AQL defects per hundred units
Liner	Electrical conductivity	3.2 and 3.4	4.4.1	S-1	Zero
	Leakage	3.3	4.4.2	S-2	1.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

4.3 Examination. The liners shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the following classification of defects listed in table III. Examination shall not be restricted to the classified possible defects listed below.

TABLE III. Classification of defects.

Categories	Defects
Major	
101	Liners not free of tears, damages.
102	Liners not clean.
103	Heat seals not continuous or not straight.

4.3.2 Dimensional examination. The liners shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein shall be classified as a defect.

4.3.3 Packaging inspection. The inspection of the unit, intermediate package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Electrical conductivity. The liners shall be tested as described in Reduction of Electrostatic Hazards-Accessories of NFPA No. 56A.

4.4.2 Leakage. The liner shall be filled with water in the amount shown in table IV. The top edge of the liner shall be tied into a knot and the liner shall then be suspended by the knot for a period of at least 3 minutes.

TABLE IV. Water volume for leakage test.

Size	Volume (Litres)
I	6
II	8

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

5. PACKAGING.

5.1 Packaging. Packaging shall be Level A or C as specified.

5.1.1 Unit of issue. One package containing 100 liners, as specified, constitutes one unit of issue.

5.1.2 Level A.

5.1.2.1 Unit package. Each unit (100 liners) shall be packaged in a box of appropriate size and design constructed in accordance with PPP-B-566, PPP-B-676 or PPP-B-636, type CF, class domestic, except that commercial colors shall be acceptable. Closure shall be adequate to prevent accidental opening.

5.1.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be Level A, B, or C (See 6.2).

5.2.1 Level A. Six (6) unit packages shall be overpacked in an exterior container designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3C. Closure and strapping shall be in accordance with the appendix of the applicable box specification.

5.2.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragrapns of appendix thereto. Case liner shall not be required for fiberboard boxes. Fiberboard box shall be waterproofed in accordance with the appendix of PPP-B-636.

5.2.2 Level B.

5.2.2.1 Exterior container. Six (6) unit packages shall be overpacked in an exterior container designed for type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, type CF, class domestic. Closure of box shall be as specified in the appendix of the applicable box specification.

5.2.3 Level C. Units shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Unit package. Each unit package shall be marked in accordance with MIL-STD-129. Contract or purchase order number shall be shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

5.3.2 Exterior containers. Exterior containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The liners covered by this specification are intended for use with surgical utility pails in areas of military medical facilities where flammable liquids or gases are utilized.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

a. Title, number and date of this specification.
b. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
c. Size required (see 1.2).
d. When a first article is required (see 3.1, 4.1.2.1 and 6.3).

6.3 First article. When a first article is required, it shall be tested under the appropriate provisions of 7-104.55 of Armed Services Procurement Regulation. The contract or purchase order specifies the quantity, procedure for delivery and other specific instructions for inspection and approval of the first article.

6.4 This specification covers the following items appearing in the Federal Supply Catalog:

National Stock Number	Item Identification
7240-00-178-7632	LINER, UTILITY PAIL, Plastic, Conductive, Disposable, 20 By 24 Inches, 100s.
7240-00-151-9301	LINER, UTILITY PAIL, Plastic, Conductive, Disposable, 24 By 30 Inches, 100s.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 7240-0204

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-L-37530 LINER, UTILITY PAIL, PLASTIC, CONDUCTIVE, DISPOSABLE

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:55Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, PA 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:55Z
Check the source to verify that this is the current version before use.