MIL-L-45923A (AR)
AMENDMENT 4
7 June 1984
SUPERSEDING
AMENDMENT 3
1 October 1981

MILITARY SPECIFICATION

LINK, CARTRIDGE, METALLIC BELT, CALIBER .50, M9

This amendment forms a part of Military Specification MIL-L-45923A (WC), dated 16 April 1976 and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, STANDARDS: Add: "MIL-STD-1168 - Ammunition Lot Numbering"

PAGE 2

3.2.1: Delete in its entirety and substitute the following:

"3.2.1. Function. The links, when assembled into belts caliber .50 ammunition or mandrels of cartridge form shall meet the following functional requirements."

PAGE 3

3.2.1.1: Delete in its entirety and substitute the following:

"3.2.1.1. Free hinging. Links, when assembled into belts, shall hinge freely and fold over without binding, kinking, breaking, cracking, separating, or deforming. Testing shall be as specified in 4.5.3.5."

3.2.1.2: Delete in its entirety and substitute the following:

"3.2.1.2 Machine gun function. The belts shall operate during the firing cycle of a caliber .50, M2, heavy barrel, turret type machine gun without breaking, separating, causing a malfunction or creating an interference to proper gun operation. Testing shall be as specified in 4.4"

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

3.2.1.3: Delete in its entirety and substitute the following:

"3.2.1.3 Twisting (fanwise). A belt of 22 rounds shall be twisted in a fanwise direction around a 6 inch diameter cylinder. When the point of the first round is touching the cylinder, a pull of 5 pounds shall be sufficient to pull the points of all other rounds in the belt to within 1/8 inch of the cylinder without damaging, separating or deforming the links. Testing shall be as specified in 4.5.3.6."

* 4.5.1: Delete "with MIL-STD-105 and MIL-W-13855." and substitute "with MIL-STD-105, MIL-STD-1168 and MIL-W-13855."

PAGE 5

4.5.2.1.1:

Delete "Drawing 7140393" and substitute "Drawing 7140393"

Major 101: Delete "diameter" and substitute "dimension"

Add Major 113 and 114 as follows:

"113	Distance along vertical centerline from the bottom of the connecting loop to the top of the tab.	.65	SMTE
114	Min. height of turned up edges at section J-J when connecting and bodyrings are held tangent to flat surface (2 places)	.65	SMTE

PAGE 8

4.5.6, line 11: Delete "the other cartridges to within 1/32 inch of cylinder" and substitute "the other cartridges to within 1/8 inch of the cylinder."

4.6.5: Delete "The links shall be examined for evidence of damage or separation." and substitute "The links shall be examined for evidence of damage, distortion or separation."

PAGE 12

Figure 2: Delete "1/32 inch" and substitute "1/8 inch".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, or deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-A973)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.