INCH-POUND

MIL-L-45923B (AR)
19 August 1993
SUPERSEDING
MIL-L-45923A (AR)
16 April 1976

MILITARY SPECIFICATION

LINK, CARTRIDGES: METALLIC BELT, CALIBER .50, M9

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of metallic belt cartridge link intended to hold caliber .50 ammunition in the form of flexible belts for use in the M2 Heavy Barrel (HB) Caliber .50 Machine Gun (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-W-13855 - Weapons: Small Arms and Aircraft Armament Subsystems, General Specification for
DOD-P-16232 - Phosphate Coating, Heavy, Manganese or Zinc Base (for Ferrous Metals)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1305
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:15Z
Check the source to verify that this is the current version before use.

MIL-W-63150 - Weapons and Support Materiel, Standard Quality Assurance Provisions for

STANDARDS

MILITARY

MIL-STD-109 Quality Assurance Terms and Definitions

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.5)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

7140393 - Link, Metallic Belt, Caliber .50, M9
SPI-7140393 - Packaging Data Sheet for Link, Metallic Belt, Caliber .50, M9

(Copies of other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-E18 - Standard Methods of Test for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Metals

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

ASTM-D3951 - Packaging, Commercial

(Application for copies should be addressed to The American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.2 Materials, construction and design. The links shall conform to the materials, construction and design specified herein, on applicable drawings and MIL-W-13855.

3.3 Functioning. The M9 links shall be capable of being assembled into belts with caliber .50 ammunition or mandrels of requirements.

3.3.1 Free hinging. Links, when assembled into belts shall hinge freely and fold over without binding, kinking, breaking, cracking, separating or deforming. Testing shall be as specified in 4.5.1.

3.3.2 Machine gun function. The belts shall operate during the firing cycle of a caliber .50, M2 Heavy Barrel, turret type machine gun without breaking, separating, causing a malfunction or creating an interference to proper gun operation. Testing shall be as specified in 4.5.2.

3.3.3 Belt pull. A belt consisting of 100 caliber .50 cartridges shall be capable of withstanding a tensile load of 100 pounds (lbs) + 15 lbs without breaking, cracking, separating or deforming. Testing shall be as specified in 4.5.3.

3.3.4 Extraction force. The force required to extract the steel plug, drawing 6516242, when the plug is inserted to the assembled cartridge depth, shall be 10 to 25 lbs. Testing shall be as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

3.4 Marking. The links shall be clearly marked in accordance with dwg. 7140393 and MIL-W-13855.

3.5 Workmanship. Workmanship shall be in accordance with MIL-W-63150.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-W-63150 or other general specification apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities indicated.

Name	Drawing	Quantity
Link, Metallic Belt	7140393	1780

4.3.2 Inspections to be performed. First Article materiel shall be tested in accordance with Table I. Any test samples may be subjected, by the Government, to any or all of the examinations and tests specified herein, in the contract or on the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.1.1 Lot identification. The cover and body assemblies of each container of the lot shall be identified as specified by Dwgs 12576152 and 12576144 supplemented as directed by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:15Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Link, Metallic Belt, Caliber .50, M9	1 OF 1	7140393
			NEXT HIGHER ASSEMBLY: Not applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA		REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
		Acc	Rej		
	Examination for defects	200	0-1	3.2	4.4.2.1
	Free hinging	800	0-1	3.3.1	4.5.1
	Machine gun function	400	0-1	3.3.2	4.5.2
	Belt pull	100	0-1	3.3.3	4.5.3
	Extraction force	200	0-1	3.3.4	4.5.4
	Protective finish				
	Salt Spray	10	0-1	3.2	4.5.5.1
	Supplementary wax coating	10	0-1	3.2	4.5.5.2
	Decarburization	10	0-1	3.2	4.6
	Hardness	50	0-1	3.2	4.7

NOTES:

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70998(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Container Assembly	1 OF 1	12576143
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Temperature 1/	7	3.3	4.6.1
	Performance 1/	7	3.4	4.6.2
	Airtightness 1/	7	3.5	4.6.3
	Pretreatment - 3 standard panels per TT-C-490 1/	7	3.7.1	4.6.4
	Paint adhesion 1/	7	3.7.2	4.6.5
	Corrosion resistance 1/	7	3.7.3	4.6.6
	Gasket compression 1/	7	3.8	4.6.7
	Weld security		3.9	4.6.8
	1/	7		
	Hasp 1/	7	3.9.1	
	Handle 1/	7	3.9.2	
	Latch		3.9.3	
	Concavity and convexity		3.10	4.6.9
	Cover assembly 1/	7	3.10.1	
	Body assembly 1/	7	3.10.2	

NOTES:

1/ Accept on zero defects, reject on one defect.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

MIL-L-45923B (AR)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection.

	Inspection Levels					
Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.x). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Link, Metallic Belt, Caliber .50, M9	1 OF 1	7140393
			NEXT HIGHER ASSEMBLY: Not applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined			
MAJOR				
101.	Link profile	Level III	3.2	6057840
102.	Connecting ring, outside dimension	Level III	3.2	8409356
103.	Connecting ring, inside dimension	Level III	3.2	8409361
104.	Offset of bridge	Level III	3.2	8440932
105.	Distance between the centerline of the body and neck loops and the centerline of the connecting ring	Level III	3.2	7127273
106.	Overall length, link (over loop)	Level III	3.2	Gage
107.	Distance between loop faces	Level III	3.2	Gage
108.	Length, connecting ring	Level III	3.2	Gage
109.	Outside shoulder diameter, neck loop	Level III	3.2	Gage
110.	Inside diameter, neck loop	Level III	3.2	Gage
111.	Length, front loop	Level III	3.2	Gage
112.	Length, rear loop	Level III	3.2	Gage
113.	Distance along vertical centerline from the bottom of the connecting loop to the top of the tab	Level III	3.2	Gage
114.	Taper of body loop	Level III	3.2	Gage
115.	Protective finish missing or non-uniform	Level III	3.2	Visual
MINOR				
201.	Missing of correct identification	Level V	3.4	Visual
202.	Poor workmanship	Level V	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-L-45923B(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.2	Link, Metallic Belt, Caliber .50 Packaging Data Sheet		PS-7140393
			NEXT HIGHER ASSEMBLY: Not applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined			
MAJOR				
101.	Improper level of preservation and packaging	Level III	3.2	Visual
102.	Missing, incorrect or illegible marking	Level III	3.2	Visual
103.	Contaminated links	Level III	3.2	Visual
104.	Improper containers	Level III	3.2	Visual
105.	Container interior contaminated with dirt, lint or other foreign matter	Level III	3.2	Visual
106.	Improperly oriented links in link cartons	Level III	3.2	Visual
107.	Improperly oriented link cartons in shipping container	Level III	3.2	Visual
108.	Incorrect quantity of links per shipping container	Level III	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.2	TITLE Link, Metallic Belt, Caliber .50 Packaging Data Sheet	SHEET 2 OF 2		DRAWING NUMBER PS-7140393
				NEXT HIGHER ASSEMBLY Not applicable
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
109.	Improper closure of shipping containers	Level III	3.2	Visual
110.	Incorrect or missing inspection lot number on each carton of links	Level III	3.2	Visual
MINOR 201	Poor workmanship	Level V	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.1	Link, Metallic Belt, Caliber .50	1 OF 2	7140393
			NEXT HIGHER ASSEMBLY: Not applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	TESTS	Acc-Rej		
	Free hinging test	800 0-1	3.3.1	4.5.1
	Belt pull test	200 0-1	3.3.3	4.5.3
	Extraction force	200 2-3	3.3.4	4.5.4
	Protective finish			
	Salt Spray	1/	3.2	4.5.5.1
	Supplementary wax coating	0-1 2/	3.2	4.5.5.2
	Decarburization	0-1 3/	3.2	4.5.6
	Hardness	0-1 3/	3.2	4.5.7

NOTES:

See next page for Notes.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T04:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.3.1	Link, Metallic Belt, Caliber .50,	SHEET 2 OF 2	7140393
			NEXT HIGHER ASSEMBLY: Not applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	1/ Sampling and testing for compliance of requirements shall be in accordance with DOD-P-16232. 2/ A sample of 10 links with supplementary wax coating shall be taken from each shifts production, from each production machine shall be tested for supplementary wax coating weight. Failure of links to meet the specified requirements shall be cause for rejection of the representative lot. 3/ A sample of 5 links shall be selected at random from each heat treat lot and tested for decarburization. Failure of any links to meet the specified requirements shall be cause for rejection of the heat treat lot. The links shall be scraped after completion of the testing.			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-27 04:15Z
Check the source to verify that this is the current version before use.

MIL-L-45923B (AR)

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and test prescribed herein is described in the PARAGRAPH REFERENCE/INSPECTION METHOD column in the Tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

4.5.1 Free hinging test. The links shall be tested by assembling into 50 round belts using dummy cartridges simulating Government standard caliber .50 cartridges. The belt shall be laid out horizontally to its full length and one end shall be drawn back and forth upon the remainder of the belt. The belt shall not bind, kink or break.

4.5.2 Machine gun functioning test. The sample links shall be tested by assembling with Government standard caliber .50 cartridges into four belts of 100 linked cartridges and fired in a caliber .50, Heavy Barrel, Turret Type machine gun. Two belts shall be fed from the right side feed and two belts fed from the left side feed.

4.5.3 The sample links shall be tested using a Government approved test fixture. Links shall be assembled into a 100 round belt and placed in test fixture. The 100 lbs + 15 lbs load shall be applied at a uniform rate and the belt shall remain under tension for minimum of 30 seconds after the 100 lbs + 15 lbs load is attained. Upon removal of the load, the links shall show no evidence of separation, stretching or cracking.

4.5.4 Extraction force test. The links shall be tested using a steel plug (mandrel) and test equipment specified on drawing 6516242. The link shall be properly placed in the test fixture, the steel plug inserted and a force gradually applied to extract the plug from the link. If extraction forces measured 25 pounds to 40 pounds two more tests shall be conducted on the same link to verify the first test. The force required to extract the plug from each link tested shall be recorded as extraction force.

4.5.5 Protective finish.

4.5.5.1 Salt spray test. Sample links shall be tested for corrosion resistance of the applied protective coating using tests specified in DOD-P-16232.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:15Z
Check the source to verify that this is the currentversion before use.

4.5.5.2 Supplementary wax coating weight test. The sample links shall be tested by weighing the links together to the nearest milligram. The supplementary wax coating shall be completely removed from the links by trichloroethylene of trichloroethane vapor degreasing and the links dried and weighed. The difference between the total weights before and after removal of supplementary wax coating divided by the number of links tested shall be considered as the weight of the supplementary wax coating of each link.

4.5.6 Decarburization test. A cross section of the sample loops shall be polished, etched with a 2 to 5 percent nital solution and examined under a microscope of not less than 500 power to determine compliance with decarburization requirements of Dwg 7140393.

4.5.7 Hardness test. The sample links shall be tested for hardness requirements using ASTM-E18 and fixture specified on Dwg. 8409387. Two hardness readings shall be taken in close proximity of each other. The hardness shall be the average of the two readings. If either reading is not within the specified hardness requirement, three more readings shall be taken at positions approximately 120 degrees from each other with one of the three readings taken approximately 1/8 inch from the initial two readings. The three readings shall not vary from each other, by more than two Rockwell C points and shall be within specified requirements.

5. PACKAGING

5.1 Pilot pack. A pilot pack shall consist of links preserved in accordance with Packaging Data Sheet SPI-7140393 for the level of protection specified in the contract (see 6.1).

5.2 Levels A and B. Preservation, packing and marking shall be in accordance with Packaging Data Sheet SPI-71040393 for the level of protection specified in the contract (see 6.1).

5.3 Commercial packaging. Preservation, packing and marking shall be in accordance with ASTM-D3951.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:15Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The item covered by this specification is one type of metallic link intended to hold Caliber .50 ammunition in the form of flexible belts for use in the M2 HB Caliber Machine Gun.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for submission of first article sample.

d. Applicable stock number.

e. Packaging requirements, if other than specified in Section 5.

f. Serialization requirements, if applicable.

g. Certificate of conformance for each lot or shipment of product.

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract, per the Contract Data Requirements List, DD Form 1423.

6.4 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Flexible belt
Machine gun
Ammunition holder
Expendable

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AD71)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-L-45923B (AR)	930819

3. DOCUMENT TITLE: LINK, CARTRIDGES: METALLIC BELT, CALIBER .50, M9

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 — *Previous editions are obsolete.* — 198/200

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:15Z
Check the source to verify that this is the current version before use.