MIL-D-45929(WC)
AMENDMENT 2
11 June 1976
SUPERSEDING
AMENDMENT 1
18 December 1975

MILITARY SPECIFICATION

DRUM, AMMUNITION, ROTARY, 7.62MM

This amendment forms a part of Military Specification MIL-D-45929(WC) dated 28 January 1975.

Page 1

Paragraph 2.1 - Under "STANDARDS" add the following standard:

"MIL-STD-781 - Reliability tests: Exponential Distribution"

Page 5

Paragraph 4.4:

Line 6 - After "contract" add "(see 6.2)".
Line 7 - Delete "(see 3.6)" and substitute "(see 3.6 and 4.6.5)".

Page 15

Paragraph 4.6.4 - At beginning of first sentence, add "When specified (see 6.2),".

Add the following paragraph:

"4.6.5 Environmental conditions test. When specified (see 6.2), tests shall be performed for each environmental condition in accordance with the applicable method and procedure specified in MIL-A-45967. The drum shall be operated during these tests in accordance with the functional test method of 4.6.1 with the following exceptions:

a. Dummy ammunition may be used in lieu of live ammunition.
b. Vibration testing performed on the empty drum shall be limited to a resonance search and a dwell on each of the two most severe resonant frequencies found during the search.

FSC 1090

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:17Z
Check the source to verify that this is the current version before use.

c. Vibration testing performed on the fully loaded (4000 rounds) drum shall consist of a resonance search. During the next two and one-half hours, one burst of ammunition shall be cycled every five minutes, whether the drum is undergoing resonance dwell or sinusoidal cycling. A burst of ammunition, as cycled every five minutes, shall be alternated between a two second HI-RATE burst and a four second LOW-RATE burst. The resonant dwell period shall be limited to the four most severe resonant frequencies found.
d. Shock tests shall be conducted with the drum fully loaded (4000 rounds) with ammunition."

Page 16

Paragraph 6.2.1 (e) - Delete in its entirety and substitute the following:

"e. Reliability and environmental conditions requirements and tests, when required (see 3.5, 3.6, 4.4, 4.6.4 and 4.6.5)."

Custodian:
Army - WC

Preparing Activity:
Army - WC

Project No. 1090-A041

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:17Z
Check the source to verify that this is the current version before use.