[NOT MEASUREMENT
SENSITIVE]
A-A-59333
16 November 1998
SUPERSEDING
MIL-T-52809A
19 December 1986

COMMERCIAL ITEM DESCRIPTION

TRUCKS, HAND, LIFT; PALLET, MANUAL-HYDRAULIC

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers three sizes and three classes of general purpose, heavy-duty, manually operated, industrial-type hand lift pallet trucks.

1.1 Intended use. Hand-lift pallet trucks are used by warehouse workers to manually move a single palletized load up to one hundred yards in and around warehouses, loading platforms, highway trucks, and railroad cars.

2. CLASSIFICATION. The hand lift pallet trucks are of the following sizes and classes as specified in 7.3.

2.1 Size. Size A - 4,000-pound (1814.4 kg) pallet load capacity.
Size B - 6,000-pound (2721.6 kg) pallet load capacity.
Size C - 5,500-pound (2494.8 kg) pallet load capacity.

2.2 Class. Class 2 - 48-inch (121.9 cm) fork length.
Class 3 - 36-inch (91.4 cm) fork length.
Class 4 - 42-inch (106.7 cm) fork length.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center, Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 General requirements. The hand lift pallet trucks (hereinafter called "trucks") shall be heavy-duty industrial-type. Components shall consist of manually propelled and manually operated hydraulic lift, multiple stroke; front wheels and rear wheels with durable, solid tires capable of operating at maximum load capacity without damage or excessive wear. The trucks shall be new and capable of operation in accordance with the requirements herein.

3.2 Maintenance and servicing. Customary and normally available maintenance and service of the hand truck shall include provisions for adjustment, service, and replacement of wheels, axles, wearing parts of lift mechanism, steering assembly, and hydraulic pumps. Any frequently adjusted or replaced items shall be easily accessible. The hydraulic system of the truck shall use oil conforming to MIL-PRF-2104. The truck's components and grease shall be compatible with the automotive and artillery grease (GAA) that conforms to MIL-G-10924. Components requiring grease lubrication shall be provided with pressure grease fittings in accordance with SAE J534, "Lubrication Fittings".

3.3 Component requirements.

3.3.1 Forks. Forks shall be constructed to facilitate entry and withdrawal from standard military pallets as defined in the classification section of MIL-P-15011. The length of the fork shall be 36, 42, or 48 inches (see 7.3). The tolerance on fork length shall be plus or minus 1/2 inch (12.7 mm). Minimum under-clearance, with forks lowered, shall be 1 inch (25.4 mm). The lowered fork height shall not exceed 3 inches (76.2 mm). At any elevation, forks shall be horizontal within a tolerance of plus 1/16 inch (1.6 mm) and minus 1/8 inch (3.2 mm) at the ends and in alignment within a tolerance of plus or minus 1/4 inch (6.4 mm).

3.3.2 Wheels and rollers. Unless otherwise specified (see 7.3), the wheels shall be the contractor's standard.

3.3.2.1 Front wheels (steer wheels). Wheels shall be equipped with permanent lifetime grease-sealed bearings or accessible pressure lubrication fittings. Front wheels shall be not less than 6.9 inches (175.3 mm) in diameter by not less than 2 inches (50.8 mm) wide.

3.3.2.2 Rear wheels (load wheels). Wheels shall be equipped with ball or roller bearings. Wheels shall be provided with permanent lifetime grease-sealed bearings or accessible pressure lubrication fittings. Each wheel shall be not less than 2.75 inches (69.9 mm) in diameter by not less than 3.25 inches (82.6 mm) in width for size A truck and not less than 3.6 inches (91.4 mm) in width for sizes B and C trucks.

3.3.2.3 Entry and withdrawal devices. Pallet entry and withdrawal devices shall be provided and shall have an under-clearance of not less than 1/8 inch (3.2mm).

3.3.3 Hydraulic system. The hydraulic system of the trucks, including the pump, ram, and reservoir, shall be the sealed type unit(s). The sealed type unit(s) shall be demountable. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

hydraulic system fluid shall conform to MIL-PRF-2104. A totally enclosed pressure-relief device shall be provided which shall automatically preclude any damage to the hydraulic system due to overload and continuous operation of the lift mechanism after the load is lifted to maximum height.

3.3.3.1 Ram. The ram shall be protected against corrosion and rust. The ram assembly shall prevent grit from entering the hydraulic system.

3.3.3.2 Lifting and lowering mechanism. The lifting mechanism shall be controlled and operated by either the handle of the truck, a lever separate and independent of the handle, or by a foot pedal. The lowering mechanism shall be a pressure-release device that is independent of the lifting mechanism. The mechanism shall be so located that the operator will not be endangered when lowering a load.

3.4 Performance.

3.4.1 Load carrying capacity. The rated load-carrying capacities of the trucks shall be Size A -4,000, Size B -6,000, or Size C -5,500 pounds. (see 7.3 and 2.1)

3.4.2 Lifting operation. The lift mechanism shall be capable of raising and lowering the forks at the rated load capacity and shall hold the rated load in any position without exceeding a downward drift rate of 1/8 inch (3.2mm) per hour.

3.4.3 Lowering mechanism. The lowering mechanism shall control lowering speed to prevent jarring.

3.4.4 Maximum load. The truck shall show no evidence of damage, leakage or permanent deformation exceeding 1/16 inch (1.6 mm) when loaded to 200 percent of rated capacity (3.4.1), the pressure relief valve made inoperable, and the forks elevated to maximum lift height.

3.4.5 Shock load. The truck shall show no evidence of damage, leakage, distortion or binding of the wheel bearings or permanent deformation exceeding 1/16 inch (1.6 mm) when subjected to a shock resulting from a 1 inch (25.4 mm) drop onto a concrete surface, when loaded to 125 percent of rated capacity, and the pressure relief valve made inoperable.

3.4.6 Pallet entry and withdrawal. The truck shall be capable of complete entry into and withdrawal from an empty double faced, 4-way standard military pallet conforming to MIL-P-15011, without moving the pallet more than 6 inches in either direction.

3.4.7 Steering. The trucks shall be steered through the front wheels by a steering handle. The steering handle shall be capable of turning the steering assembly not less than 100 degrees to the left and 100 degrees to the right of dead center. The steering assembly shall have permanent lifetime grease-sealed bearings, or provisions for lubrication by accessible pressure fittings. The truck with rated load and the handle in the towing position shall require a force not to exceed 10 pounds (4.5 kg) for size A trucks, and 15 pounds (6.8 kg) for sizes B and C trucks to turn the steering assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

3.4.7.1 Steering handle. The steering handle shall be capable of remaining in a vertical position. The handle shall not have a snap action back to the vertical position when extended to any position. The handle shall withstand a minimum force of 200 pounds (90.7 kg) applied horizontally to the handle, with handle being pulled toward the forks from the handle's normal upright position without damage or permanent deformation. The steering handle shall be removable from the steering mechanism with the use of common hand tools.

3.5 Painting. The finish coat shall be the manufacturer's standard color unless otherwise specified (see 7.3).

3.6 Identification plate. A nameplate shall be securely attached to the truck. Unless otherwise specified (see 7.3), the nameplate shall contain the following information:

TRUCK , HAND, LIFT: PALLET, MANUAL-HYDRAULIC
CAPACITY
NAME OF MANUFACTURER
SERIAL NUMBER
MODEL NUMBER
NATIONAL STOCK NUMBER
PART IDENTIFICATION NUMBER (see 7.4)

3.7 Equipment manual. Unless otherwise specified (see 7.3), the contractor shall furnish one copy of an equipment manual with each truck. The equipment manual shall contain complete instructions for operation and maintenance, and illustrated repair parts section. The repair parts section shall include actual manufacturer's name and part number and quantity of each part required. The repair part illustration may be a drawing or picture.

3.8 Workmanship. The truck shall be constructed, assembled and finished in a manner to assure good quality equipment of a neat general appearance, and free from imperfections which may affect durability, serviceability, and appearance.

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered or environmentally preferable materials. Recycled, recovered or environmentally preferable materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements and promotes economically advantageous life cycle costs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The hand pallet trucks provided shall meet the salient characteristics of this CID; conform to the manufacturer's own drawings, specifications, standards, and quality assurance practices; and be produced using the same practices and procedures used to produce hand pallet trucks offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The manufacturer should be a current producer of hand pallet trucks to help ensure up-to-date technology, serviceability, reliability and quality of materials.

5.3 Inspection. The hand pallet truck shall be inspected to determine compliance with all requirements specified in this CID.

6. PACKAGING

6.1 Packaging requirements. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Sources of documents.

7.1.1 Military documents may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.1.2 SAE standards may be obtained from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pa. 15096-0001.

7.2 Choice of wheels. The contract may specify the type of wheels for environmental reasons, for example, chose polyurethane or nylon wheels to protect flooring, use steel wheels when needed to travel over steel grates, or non-metallic wheels when in a spark free environment.

7.3 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this CID.
b. Size and class truck required (see 2.1and 2.2).
c. Type of wheels, when other than contractor's standard. (see 3.3.2 and 7.2).
d. When a bid sample is required, the following information will be provided: the size, class, and number of samples, delivery location, the responsibility for transport, delivery and the disposition of samples after evaluation is complete.
e. Color of finish coat if other than as specified (see 3.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

f. When additional copies of equipment manual are required.
g. NSNs, when available.

7.4 Part identification number (PIN) and national stock numbers (NSNs). The following part identification numbering procedure in Table I is for government purposes and does not constitute a requirement for the contractor. Table I includes a list of NSNs and CAGE Codes which correspond to this CID.

Table I. PIN, NSN and related data.

CID PIN	CID CLASSIFICATION		MIL SPEC (MIL-T-52809A) CLASSIFICATION		NSN	CAGE
	SIZE	CLASS	SIZE	CLASS		
AA52809-A2	A	2	A	2	3920-00-202-2223	33123 56250 OU6X9
AA52809-A3	A	3	A	3		OU6X9 33123
AA52809-A4	A	4	A	4	3920-01-258-1213	33123 56250 OU6X9
AA52809-B2	B	2	B	2	3920-00-242-5764	33123 OU6X9
AA52809-B3	B	3	B	3		OU6X9 33123
AA52809-B4	B	4	B	4	3920-01-141-1457	56250 OU6X9 33123
AA52809-C2	C	2	C	2		OU6X9 33123
AA52809-C3	C	3	C	3		OU6X9 33123
AA52809-C4	C	4	C	4		OU6X9 33123

MILITARY INTERESTS:

Custodian
Army - AT

PREPARING ACTIVITY
DLA - GS
(Project 3920-0019)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.