A-A-1992
May 30, 1984

COMMERCIAL ITEM DESCRIPTION

CLEANING COMPOUND, HARD SURFACE-FLOOR

(POWDERED, HEAVY DUTY)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification P-C-435.

Salient Characteristics.

The product shall be a heavy duty powdered general purpose cleaning compound suitable for the removal of heavy deposits of oil, grease, and similar soils from hard surfaces such as terrazzo, ceramic tile, marble, concrete, metal and similar washable surfaces.

The product shall consist primarily of inorganic detergents and conform to the following requirements:

| Characteristic: | Requirement: | Test Method: |
|---|---|---|
| Moisture | 28 percent, maximum | ASTM D 820 #5 & 6 |
| Matter insoluble in water | 0.3 percent, maximum | ASTM D 820 #15 |
| Total alkalinity as sodium carbonate | 90 percent, minimum | ASTM D 820 #16 & 17 |
| pH of one percent solution | 9.0 - 10.5 | ASTM D 1172 |

Cleaning efficiency. When tested as specified in the cleaning efficiency test method in Federal Specification P-D-1747, a 0.5 percent by weight solution of the product shall have a cleaning efficiency greater than or equal to the cleaning efficiency of a 0.5 percent by weight solution of the reference formualtion below. Both dilutions shall be made with synthetic hard water containing 0.246 g calcium chloride dihydrate and 0.295 g of magnesium sulfate septahydrate per liter at 25 degrees C.

Reference Formulation

| Ingredient | Percent by Weight |
|---|---|
| Sodium Sequiicarbonate | 82.5 |
| Tetrasodium Pyrophosphate | 17.0 |
| Diammonium Phosphate | 0.5 |

Rinsing properties. The product shall be free rinsing and leave no deposit or sediment when tested as specified in ASTM D 3399, section 7.

Deleterious action on tile. A 0.2 percent by weight solution of the product shall cause no more than one-half the loss in the 60 degree specular gloss of white, polished but unsealed terrazzo tile caused by a 0.2 percent by weight solution of trisodium phosphate, when tested as specified in ASTM D 3399 Section 8, except that terrazzo tile shall be used in place of the painted surfaces.

Directions for use and hazard precautions. The containers shall be labelled with directions for use, and hazard precautions in accordance with the Federal Hazardous Substances Act Regulations (Code of Federal Regulations, Title 16, Part 1500).

The issues of the referenced test methods in effect on the date of the solicitation shall be used to determine compliance with stated requirements

Preservation, Packaging, Packing, Labeling and Marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or order.

Notes:

ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Users of this commercial item description shall state in the contract the size containers of the cleaning compound required.

PREPARING ACTIVITY: GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.