A-A-2010A
October 3, 1983
Superseding
A-A-2010
June 1, 1982

COMMERICAL ITEM DESCRIPTION

REFRIGERATORS, MECHANICAL, HOUSEHOLD COMPACT (ELECTRICAL, SELF CONTAINED)

The General Services Administration has authorized the use of the commercial item description.

This commercial item description covers self-contained household compact refrigerators with electric-motor-driven condensing units.

Salient characteristics:

Compact refrigerators covered by this CID will be of the following dimensions and capacities:

Max. Over Dimensions			Min. Capacity	Min. Shelf Area
Width	Height	Depth	5.5 cu. ft.	7.9 sq. ft.
24"	36"	25-1/2"		

The method of computing total regigerated volume and total shelf area of compact refrigerators shall be as specified in ANSI/AHAM HRF-1.

The compact refrigerators shall operate on a 115 volt, 60 Hz, A.C. electrical system. A three-wire cord with a three-prong attachment plug shall provide grounding of the refrigerators and shall extend at least 5 feet but not more than 9 feet beyond the point at which it is attached to the back of the cabinet.

When 50 Hz operation is specified, the refrigerator must be wired for 220 volts 50 Hz use and will not utilize an internally or externally mounted transformer. A UL approved 3-wire electrical cable intended for power supply cord use shall be provided.

The refrigerators shall be capable of producing average cabinet air temperatures in the general food storage compartment of 36°(F) in an ambient of 70°(F), 38°(F) in an ambient of 90°(F) and 43°(F) in an ambient of 110°(F). When operating in the ambient temperatures listed above, the average package temperatures in the low temperature food compartment shall be lower then 32°F. The performance test procedures shall be as specified in ANSI/AHAM HRF-1.

The average energy consumption per cycle, type and net refrigerated volume shall be tested in accordance with the Federal Register Vol. 42, No. 178, Wednesday, September 14, 1977.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Refrigerators shall conform to the applicable requirements of ANSI/UL 250. Acceptable evidence of meeting the requirements of this standard shall be the UL label, UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government, indicating that the refrigerator offered has been tested and conforms to the applicable requirements of the UL standard.

The refrigerators shall include an adjustable temperature control, an automatic interior light with shield, a minimum of two copolymer, polyethylene plastic or metal/partial metal ice cube trays, an interior metal or acrylonitrile butadiene styrene (ABS) plastic freezer door with metal hinges, a manual defrost feature, a minimum of two adjustable leg levelers and be free standing.

The refrigerator shall have a counter top of plastic and/or plastic laminated on wood.

Each door shall be equipped with a magnetic gasket and unless otherwise specified, doors shall swing to the right. A right-hand swing shall be described as having hinges located on the right side of door when facing the refrigerator.

The outer shall (including the door) shall be carbon-steel sheet finished in baked synthetic enamel.

The inner liners of the general storage area shall be carbon steel sheet or molded plastic. The carbon steel sheet inner liners shall have porcelain enamel or baked synthetic enamel finish. The color shall be white or pastel.

The insulation for the cabinet and door must be foamed-in-place polyurethane foam insulation. When plastic liners are used in the general storage compartment and the exterior door and the insulation is foamed-in-place polyurethane employing fluorinated hydrocarbons, the liner material must be made of (ABS).

Plastic compartment liners and plastic door liners when assembled to outer doors, shall not show any cracks or crazing when tested under Environmental Cracking Resistance Test specified in ANSI/AHAM HRF-1.

Workmanship. Welding and brazing shall be complete, uniform, and properly fused having no burn holes, slag inclusion, scale or flux deposits and shall not be cracked, fractured, or undercut. Soldering shall be complete, clean, adherent, without pinholes. Bolts, nuts, screws, studs, and other types of fasteners, when used, shall not be broken, fractured, stripped, or loose and shall have lock washers or shall be self-locking type when used on structural parts subject to vibrations.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:18Z
Check the source to verify that this is the current version before use.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with PL 94-580 to the maximum extent practicable.

Packaging, packing and marking. Packaging, packing and marking shall be as specified in the contract and order.

ANSI/UL 250 is available from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, Illinois 60062.

Copies of ANSI/AHAM HRF-1 are available from Assocation of Home Appliance Manufacturers, 20 North Wacker Drive, Chicago, Illinois 60606.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.