A-A-2144
August 6, 1983

COMMERCIAL ITEM DESCRIPTION

LAMP, INCANDESCENT
(SEALED BEAM. TRADE NO. 4652)

The General Services Administratoon has authorized the use of this commercial item description.

This description covers a rectangular sealed beam, low beam, headlamp for a four headlamp system, type 2A1.

Salient characteristics:

Rectangular bulb - 100 mm x 165 mm

Design volts - 12.8 volts for each filament

Watts - 40 watts for high beam; 60 watts for low beam

Three (3) contact lugs

Filament designation - C6/C6

Rated average lab life, at 14 volts, in hours - 200 for upper beam; 320 for lower beam

The rectangular headlamp shall be in accordance with the Society of Automotive Engineers (SAE) Standards J571 - Dimensional Specifications for Sealed Beam Headlamp Units and; J573 - Lamp Bulb and Sealed Beam Headlamp Units.

Workmanship. The lamp shall not have bent contacts, slight or complete discoloration of the lens or reflective coating, small bubbles in the glass, cracked glass, peeled reflective coating, and open or shorted filaments.

The issues of SAE Standards J571 and J573 in effect on the date of solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

NOTE: When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

SAE Standards J571 and J573 are available from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

DoD has determined that no military activity has an official interest in this commercial item description

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.