A-A-2147
August 6, 1983

COMMERCIAL ITEM DESCRIPTION

LAMP, METAL HALIDE
(REPLACEMENT, TRADE NO. M59PJ-R400/I/U)

The General Services Administration has authorized the use of this commercial item description.

This description covers metal halide lamps to be used as a replacement on mercury vapor lamps using 400W CW/CWA single-lamp mercury ballasts. (Will also operate on ANSI M59 metal halide ballasts.)

Salient characteristics:

E-37 (117 mm) bulb

Mogul base

Burning position - Any, but in positions other than vertical base-up or base-down ± 15 degrees, use only in enclosed fixtures

Maximum overall length = 11-5/16 inches (287.9 mm)

Light center length - 7 inches (177.8 mm)

Rated life - 15,000 hours

Approximate lumens, initial - 36,000

Approximate lumens, mean - 21,600 on CW/CWA single lamp mercury ballasts, at 10 hours per start

The metal-halide lamp shall be in accordance with ANSI Standard C78.1375

Workmanship. The lamp shall have no defects that affect serviceability or appearance.

The issue of ANSI C78.1375 in effect on the date of solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

NOTES: NSN 6240-01-125-6902. When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

ANSI Standard C78.1375 is available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

DoD has determined that no military activity has an official interest in this commercial item description.

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.