A-A-444
October 15, 1979

COMMERCIAL ITEM DESCRIPTION

DRIVER, PROJECTILE UNIT, .27 CALIBER

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Conform to ANSI A10.3 1972, per the low velocity class.
Powered by a .27-caliber, short, rim fired, crimped power load.
Built-in safety device to prevent the unit from being actuated unless the driver has a fastener in it and muzzle end is against the work surface.
Piston and fastener recessed in the tool guide by a ramrod to produce low recoil and reduce fastener stress.
Designed to permit disassembly and assembly for cleaning purposes without the need for special tools.
Pistol grip handle with a full handle trigger to permit operation with the user wearing heavy work gloves and to improve operator's comfort.
Recessed pistons to accept the threaded portion of studs, to provide fastener guidance, and to insure that the threads are not driven into the work surface.
Accessories: Servicing tools.
Lubricant.
Stop rings.
Safety goggles.
Instruction manual.
Metal compartmented carrying case.
Compatible with Hilti type fasteners.
Marked with manufacturer's name or trademark and part number.

5130-00-041-6584 General purpose driver.
Designed to install the following fasteners in concrete or steel (as applicable):
Nails, smooth shank up to 3 inches long for concrete.
Nails, knurled shank up to 2 1/2 inches long for steel.
Threaded studs, smooth shank 1/4-20 up to 1 1/2 inches long thread for concrete.
With broad base plate.

5130-00-165-3907 Designed for fastening into dense concrete or steel with minimum recoil.
Capable of properly installing the following fasteners as applicable:
Nails, smooth shank up to 3 inches long for concrete.
Nails, knurled shank up to 2 1/2 inches long for steel.
Threaded studs, smooth shank 1/4-20 up to 1 1/2 inch long thread for concrete.
With tapered base plate to allow it to be used in tight places.

5130-00-800-4866 Designed for heavy duty use.
Capable of properly installing 3/8-, 5/16-, and 1/4-inch diameter threaded studs and nails into concrete or steel.
With front end stabilizer.
Capable of driving Hilti "Conic" pins and studs.

Workmanship. Driver shall be free of defects or imperfections that may impair serviceability and durability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. The drivers, with accessory parts, shall be preserved, packaged, and packed in accordance with normal commercial practice to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

ANSI Standards are available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

FSC 5130

GSA DC-01002459

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.