
MIL-B-81935/2D
1 June 1987
SUPERSEDING
MIL-B-81935/2C
24 June 1983

MILITARY SPECIFICATION SHEET

BEARING, PLAIN, ROD END, SELF-ALIGNING, SELF-LUBRICATING, WIDE, INTERNALLY THREADED, -65°F TO +325°F

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the bearings described herein shall consist of this specification and the latest issue of MIL-B-81935.




(a) For -3 thru -6, the keyslot shall be oriented perpendicular to the plane made by the face of the rod end hoop (see page 2 for additional details).

AMSC N/A
FSC 3120
DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.



Keyslot designation "K."
Sizes -3 thru -8 (Rounded slot).
Keyslot, when specified, is compatible with MIL-B-81935/3 Locking Device.
2 Slots shall be oriented perpendicular to rod end hoop face.




Keyslot designation "K."
Sizes -10 thru -16 (Square slot).
Keyslot, when specified, is compatible with MS14227, NAS 513 and NAS 1193.
2 Slots shall be oriented perpendicular to rod end hoop face.

Dash No. (Ref)	K +.005 -.000	P +.005 -.000
-10	.125	.077
-12	.125	.077
-14	.156	.086
-16	.187	.116

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.

Keyslot designation "W" (Deep Square Slot).
Sizes -3 thru -16

Keyslot, when specified is compatible with MS 14198, MS 14227, NAS 1193, NAS 513 and NAS 559. NOTE: Design usage restrictions apply against NAS 513 and NAS 559.



Dash No.	Terminal Thread	K +.005 -.000	P +.005 -.000
3 & 4	5/16 - 24UNJF-3A	.062	.110
5 & 6	3/8 - 24UNJF-3A	.093	.110
7	7/16 - 20UNJF-3A	.093	.110
8	1/2 - 20UNJF-3A	.093	.110
10	5/8 - 18UNJF-3A	.125	.110
12	3/4 - 16UNJF-3A	.125	.110
14	7/8 - 14UNJF-3A	.156	.110
16	1-1/4 - 12UNJF-3A	.187	.116

TABLE I. Dimensions.

Dash No.	B Bore +.0000 -.0005	D Outside Dia ±.010	L Completed Thread Min	E Thread Size UNJF-3B	F Ctr Line Ball to End ±.010	G Ctr Line Drill to End ±.020	N Shank Dia ±.010	W Ball Width +.000 -.002	H Body Width ±.005	A Min	J Max Housing I.D.	M Max	C Ht of Wrenching Surfaces +.010 -.062	R Width Across Flats +.002 -.010	Q Min	S Ref. Across Corners or Dia.
-3	.1900	.806	.750	.3125-24	1.375	.375	.422	.437	.337	.30	.6250	.875	.188	.437	15	.500
-4	.2500				1.469											
-5	.3125	.900	.875	.3750-24	1.625	.437	.485		.327	.36	.6875	1.000	.250	.500	14	.580
-6	.3750	1.025	1.000		1.812		.547	.500	.416	.47	.8125	1.125		.562	8	.660
-7	.4375	1.150	1.125	.4375-20	2.000	.500	.610	.562	.452	.54	.9062	1.250		.625	10	.720
-8	.5000	1.337	1.250	.5000-20	2.250	.562	.735	.625	.515	.61	1.0000	1.375		.750	9	.880
-10	.6250	1.525	1.375	.6250-18	2.500	.687	.860	.750	.577	.75	1.1875	1.500	.375	.875	12	1.020
-12	.7500	1.775	1.625	.7500-16	2.875	.812	.985	.875	.640	.85	1.3750	1.750		1.000	13	1.160
-14	.8750	2.025	1.875	.8750-14	3.375	.937	1.110	.875	.765	1.00	1.6250	2.062	.500	1.125	6	1.300
-16	1.0000	2.775	2.125	1.2500-12	4.125	1.312	1.688	1.375	1.015	1.27	2.1250	2.312	.563	1.750	12	2.020

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.

TABLE II. Load values.

Dash No.	Ultimate Static Load (Lbs)	Fatigue Load (Lbs)	Axial Proof Load (Lbs)	Weight Max (Lbs)	No Load Rotational Breakaway Torque (In-Lbs) Min	Max
-3	2,360	1,470(b)	1,000	.080	.5	6
-4	4,860	2,380	1,000	.084		
-5	7,180	3,020	1,100	.102	1	15
-6	8,550	3,570	1,660	.161		
-7	12,000	4,800	1,850	.212		
-8	19,500	8,260	2,040	.325		
-10	21,900	9,180	2,430	.481		
-12	29,300	11,600	2,810	.673		
-14	34,500	13,100	3,320	.959	1	24
-16	80,300	30,400	4,340	2.717		

(b) Based on bolt bending fatigue strength 180,000 PSI.

REQUIREMENTS:

Material:

Body: Alloy steel per MIL-S-5000 (4340)

Bearing Cartridge: MS14103-XX

Hardness:

Body: R_C 39-42

Heat Treatment: In accordance with MIL-H-6875.

Surface Texture: Per ANSI B46.1

Body: Bore, R_a 32 max.
Sides of thread and root area, R_a 32.
Thread relief, R_a 63.
All other machined surfaces, R_a 125 max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (Continued)

Plating: Cadmium plating per QQ-P-416, Type II, Class 2, on all surfaces including body bore.

Tolerances: Unless otherwise specified, decimals ±.010, angles ±1/2°.

Dimensions in inches, unless otherwise specified.

Break sharp edges and corners and remove all burrs and slivers.

Part Number:

M81935/2- XX X X Example of part number: M81935/2-16KL

- X: Add "L" for left hand thread when specified.
- X: Keyway (code "K" or "W") when specified.
- XX: Bore diameter code in multiples of 1/16 inch.
- M81935/2-: Basic part number.

Custodians:
Army - AV
Navy - AS
Air Force - 11

Review Activities:
Army - AR
Navy - SH
Air Force - 99
DLA - IS

Preparing Activity:
Navy - AS
(Project No. 3120-0667-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-81935/2D	Bearing, Plain, Rod End, Self-Aligning

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(FOLD ON THIS LINE, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

ommanding Officer
aval Air Engineering Center
ystems Engineering and Standardization Department
(SESD), Code 93
akehurst, NJ 08733-5100

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering and Standardization Department
(SESD), Code 93
Lakehurst, NJ 08733-5100

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:26Z
Check the source to verify that this is the current version before use.