MIL-C-55120(SigC)
Amendment 4
24 July 1967
Superseding
Amendment 3
6 August 1962

MILITARY SPECIFICATION

CAMERA, STILL PICTURE KA-30( )

This amendment forms a part of MIL-C-55120(SigC), dated 14 March 1961.

1. Paragraph 2.1 Documents, SPECIFICATIONS:

a. Add the following:

Under FEDERAL:

"PPP-B-585	Boxes, Wood, Wirebound
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood Cleated Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiberboard
PPP-T-97	Tape, Pressure-Sensitive Adhesive, Filament Reinforced."

Under MILITARY:

"MIL-B-10377	Box, Wood, Cleated, Veneer, Paper-Overlaid."

b. Delete under MILITARY, "MIL-C-4150 Case, Carrying and Storage, Shock and waterproof."

2. Paragraph 2.1 under "STANDARDS MILITARY" add the following:

"MIL-STD-129	Marking for Shipment and Storage."

3. Paragraph 2.1 under "DRAWINGS SIGNAL CORPS" change title of SC-A-362100 to read:

"Requirements for preparation of packaging and packing. Illustrations and Bills of Material."

4. Paragraph 2.1 "DRAWINGS SIGNAL CORPS" add the following:

"SC-DL-410800	Body Drive, Aerial Camera LA-134( )
SC-DL-410810	Magazine, Film, Cassette Type LA-135( )
SC-DL-410820	Case, Camera Equipment LA-139( )
SC-DL-410830	Lens Cone, Aerial Camera LA-131( )
SC-DL-410840	Case, Lens Cone LA-138( )."

FSC 6720

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

5. Paragraph 3.3 Procurement model.- Replace the paragraph with the following:

"3.3 Construction.- The equipment shall be constructed in accordance with the following Signal Corps Drawing Lists:

"SC-DL-410800	Body Drive, Aerial Camera LA-134( )
SC-DL-410810	Magazine, Film, Cassette Type LA-135( )
SC-DL-410820	Case, Camera Equipment LA-139( )
SC-DL-410830	Lens Cone, Aerial Camera LA-131( )
SC-DL-410840	Case, Lens Cone LA-138( )

6. Paragraph 3.5.3 Focal plane plate.- In second line delete "as specified in Figure 1."

7. Paragraph 3.5.4 Format size.- Replace with the following:

"3.5.4 Format size.- The camera body shall be provided with a format mask, located at the focal plane."

8. Delete Figure 1.

9. Delete Figure 2.

10. Paragraph 3.6.3 Mounting provision.- Delete second sentence.

11. Delete Figure 3.

12. Paragraph 3.6.7.1 Lens resolution.- Replace with the following:

"3.6.7.1 Lens resolution.- The 6-inch lens shall have an Area Weighted Average Resolution (AWAR) of no less than 40 lines/mm with a minimum of 20 lines/mm at any position within the format area, when tested in accordance with Method II of Standard MIL-STD-150. (See 4.9.)

13. Paragraph 3.9 Carrying Cases LA-138( ) and LA-139( ).- In the first sentence delete "in accordance with Specification MIL-C-4150." Add to the end of the paragraph. "(See 3.3)."

14. Paragraph 3.20 Dimensions.- Delete the entire paragraph.

15. Delete Figure 4.

16. Paragraph 3.23.4 Drip-proof.- Delete the paragraph in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

17. Paragraph 3.26.1.2 Exposure control.- Add the following to the end of the paragraph:

"The following table shall be used as a basis for checking exposure control:

Brightness Level (foot-lamberts)	Exposure Command Voltage (volts)	6-Inch Lens Cone S/C	f Nr	Shutter Speed
2048	79.1	7.2	4	1/400
2048	79.1	100	14.9	1/400
1024	71.9	115	11	1/400
512	64.7	115	8	1/400
256	57.5	115	5.6	1/400
128	50.3	115	4	1/400
128	50.3	460	8	1/400
64	43.1	115	2.8	1/400
32	36.0	115	2.8	1/200
16	28.8	115	2.8	1/100
8	21.6	115	2.8	1/50
4	14.4 "			

18. Paragraph 4.3 Table III Preproduction Inspection.- Replace the table with the following:

"Table III.- Preproduction inspection

Inspection (For additional preproduction inspection see 4.3)	Req Para	Insp Para
Explosion proof	3.23.1g	4.12
Fungus	3.23.2d	4.15
Moisture resistance	3.23.1c	
	3.23.2c	4.18

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

19. Paragraphs 4.5.3 Group C inspection through 4.5.3.3 Noncompliance inclusive.- Replace the paragraphs in their entirety including Tables VI and VII with the following:

"4.5.3 Group C inspection.- This inspection shall consist of the tests specified in Table VI and shall be performed on sample units that have been subjected to and met Groups A and B inspection. Sample units shall be selected in accordance with paragraph 4.5.3.1.

"Table VI.- Group C inspection

Inspection	Req Para	Insp Para
Acceleration		
Equipment Operating	3.23.1e	4.6.1
Equipment non-operating	3.23.2g	4.6.2
Attitude	3.23.3	4.7
Durability	3.25.4	4.11 *
Radio Interference	3.23.1f	4.19
Solderless terminal-lug connections	3.19.8.2	4.22
Temperature-Altitude	3.23.1a) 3.23.1b) 3.23.2a) 3.23.2b)	4.23
Vibration	3.23.1d	4.24
Shock	3.23.2f	4.20

* Sample units subjected to this inspection shall not be furnished on contract.

"4.5.3.1 Sampling for inspection.- One Camera, Still Picture KA-30( ) shall be selected at random as specified in Table VII for all inspections listed in Table VI.

"Table VII.- Sampling for Group C inspection

Quantity of Equipment on Order	Quantity Requiring Inspection
0 to 50 inclusive	1 unit from first 25 produced
0 to 100 inclusive	1 unit from first 50 produced
0 to 500 inclusive	1 unit from first 250 produced and 1 unit from second 250 produced
0 to 1000 inclusive	1 unit quarterly (i.e., every three months)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

"4.5.3.2 Sampling for inspection of Solderless-terminal-Lug connections.- Five specimens of each combination of wire and terminal shall be prepared each week for inspection. A specimen is a 1-foot length of wire on which a terminal lug has been applied, using the same tools and procedures used in crimping the terminal lugs in production.

"4.5.3.3 Noncompliance.- The contractor shall immediately report in writing each Group C failure occurrence, including details of the failure and characteristics affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (i) the process and materials, as applicable, and, (ii) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to Group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and Groups A and B inspection may be reinstituted; however, final acceptance and shipment will be withheld until the Group C reinspection results have shown that the corrective action was effective."

20. Paragraph 4.5.4 Reinspection of conforming Group B sample units.- Replace the paragraph with the following:

"4.5.4 Reinspection of conforming Group B and Group C sample units.- Unless otherwise specified, sample units which have been subjected to and passed Group B or Group C inspection, or both, may be accepted on contract, provided that they are resubjected to and pass Group A inspection after repair of all visible damage."

21. Paragraph 4.8 Camera operation.- Replace the second sentence with the following:

"The resulting photographs shall conform to the performance requirements specified in paragraph 3.25."

22. Paragraph 4.9 Camera resolution.- Delete the following sentence from the paragraph:

"The exposure shall be made by controlling the duration of the target illumination."

23. Paragraph 4.10 Drip-proof test.- Delete the entire paragraph.

24. Paragraph 4.11.1 Camera body and cassette, line 4.- Replace "5000 cycles in each mode of operation" with "2500 cycles in each mode of operation for each cassette."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

25. Paragraph 5. PREPARATION FOR DELIVERY.- Replace the Section with the following:

"5. PREPARATION FOR DELIVERY

"5.1 Preservation and packaging.-

"5.1.1 Level A.- Camera, Still Picture, KA-30( ) shall be preserved, packaged and tested in accordance with the applicable provisions of Specification MIL-P-116 and in a manner that will afford adequate protection against corrosion, deterioration and damage during worldwide shipment, handling and open storage.

"5.1.2 Level C.- Camera, Still Picture KA-30( ) shall be afforded preservation and packaging in accordance with the suppliers' normal commercial practice.

"5.2 Packing.- Camera, Still Picture KA-30( ), packaged as specified, shall be packed in shipping containers conforming to the requirements of the specifications referenced below for the designated level. The gross weight shall not exceed the weight shown unless an individually packed item exceeds that amount. Closure and strapping shall be as prescribed in the applicable box specification or appendix thereto, except that bands of reinforced, pressure-sensitive adhesive tape, 1/2-inch wide and conforming to Specification PPP-T-97 for Grade IV, shall be used for fiberboard boxes in lieu of metal strapping.

"5.2.1 Level A.-

BOX SPECIFICATION		MAX. GROSS WT.
Fiberboard (Type 1, Class 2)	PPP-B-636	Table VI
Nailed Wood (Style 4, Class 2)	PPP-B-621	200 lbs.
Wirewound (Style 2 or 3, Class 2)	PPP-B-585	200 lbs.
Wood Cleated Fiberboard (Overseas)	PPP-B-591	200 lbs.
Wood Cleated Plywood (Overseas)	PPP-B-601	200 lbs.
Wood Cleated, Veneer, Paper Overlaid (Overseas)	MIL-B-10377	200 lbs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

"5.2.2 Level B.-

BOX SPECIFICATION		MAX. GROSS WT.
Fiberboard (Type I, Class1)	PPP-B-636	Table I
Nailed Wood (Style 4, Class 1)	PPP-B-621	200 lbs.
Wirebound (Style 3, Class 1)	PPP-B-585	200 lbs.
Wood Cleated Fiberboard (Domestic)	PPP-B-591	200 lbs.
Wood Cleated Plywood (Domestic)	PPP-B-601	200 lbs.
Wood Cleated, Veneer, Paper Overlaid (Overseas)	MIL-B-10377	200 lbs.

"5.2.3 Level C.- Camera, Still Picture KA-30( ) shall be packed in shipping containers of the type, size and kind commonly used for the purpose in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the rules or regulations of the common carrier, applicable to the mode of transportation.

"5.2.4 Pilot Pack.- When Level "A" packaging and packing is specified above, one acceptable model of Camera, Still Picture KA-30( ) will be pilot packed in a manner that will pass the preproduction tests prescribed in Specification MIL-P-116. Illustrations of the packaging and packing procedure, together with Bills of Material, will be prepared and furnished in accordance with the provisions of Signal Corps Drawing No. SC-A-362100.

"5.3 Marking.- In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Standard MIL-STD-129."

CUSTODIAN
Army-EL

PREPARING ACTIVITY
Army-EL

Project Number 6740-A073

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
HEADQUARTERS
U.S.ARMY ELECTRONICS COMMAND
FORT MONMOUTH, NEW JERSEY 07703

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding General
U. S. Army Electronics Command
ATTN: AMSEL-PP-
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

ESC-FM 2011-66

To detach this form, cut along this line.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.