MILITARY SPECIFICATION

GROMMET ASSEMBLY

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of grommet assembly for M422 and M424 projectiles.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8795677 ------ Body
8795678 ------ Spacer
8795680 ------ Grommet Assembly

FSC 1110

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

THIS DOCUMENT CONTAINS 8 PAGES.

8808362 ------ Packing and Marking for Storage and Shipments
8858986 ------ Carton, Packing, Ammunition, for Band, Protective

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The grommet assembly shall comply with all requirements specified on the drawing (dwg) 8795680, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Burrs. Parts shall be free from burrs.

3.3.2 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.3 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed, as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Table I

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II

Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Spacer (see dwg 8795678, part numbers 8795678 and 8795679) covering details of dwg 8795680.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:	None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Minor
201. Internal diameter ..... Gage
202. External diameter ..... Gage
203. Width, min. ..... Gage
204. Material (see 3.1) ..... Visual
205. Workmanship (see 3.3) ..... Visual/Manual

4.3.2.1.2 Body (see dwg 8795677) covering a detail of dwg 8795680.

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major: None defined		
Minor		
201.	Internal diameter	Gage
202.	External diameter	Gage
203.	Width, min.	Gage
204.	Location of holes	Gage
205.	Diameter of holes, max.	Gage
206.	Material (see 3.1)	Visual
207.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.3 Grommet assembly (see dwg 8795680).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major		
101.	Material (see 3.1)	Visual
Minor		
201.	Width of cut, max.	Gage
202.	Presence of proper adhesive	Visual
203.	Outside edges feathered	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

204.	Position of spacers	Visual
205.	Tie in cords	Visual
206.	Material free of broken surfaces, punctures and dents	Visual
207.	Staples (5 per spacer) firm and undamaged. Staple below surface of material on inside diameters (alternate method)	Visual
208.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.4 Carton, packing, ammunition, for band, protective (see dwg 8858986) and section 5.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Length before packing, min.	*Measure
102.	Width before packing, min.	*Measure
103.	Height before packing, min.	*Measure
104.	Properly packed	Visual/Manual
105.	Properly sealed	Visual

*Measure with suitable scale.

Minor		
201.	Marking legible and correct	Visual
202.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.5 Packing and marking for storage and shipments (see 8808362) and section 5.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Gross load weight	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17
Check the source to verify that this is the current version before

Minor
201. Marking, legible and correct ..... Visual
202. Workmanship (see 3.3) ..... Visual/Manual

4.3.3 Testing: Not applicable.
4.3.4 Acceptance inspection equipment.
4.3.4.1 Critical and major characteristics and tests. Not applicable.
4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring activity.
4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.1).
5.1.1 Level A. The grommet assembly shall be packaged in accordance with dwg 8858986 and 8808362, using the specified moisture barrier.
5.1.2 Level C. The grommet assembly shall be packaged in accordance with dwg 8858986 and 8808362, except that the moisture barrier may be omitted.
5.2 Packing.
5.2.1 Levels A and C. The grommet assembly shall be packed in accordance with dwg 8858986 and 8808362.
5.3 Marking. Marking shall be as specified in accordance with dwg 8858986 and 8808362, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:
a. Title, number and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1110-A035

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use