MIL-G-80048C
22 July 1983
SUPERSEDING
MIL-G-80048B
1 December 1972

MILITARY SPECIFICATION

GRINDING MACHINES, CENTERLESS, EXTERNAL, CYLINDRICAL

"This specification is approved for use by all Departments and Agencies of the Department of Defense".

1. SCOPE

1.1 Scope. This specification covers one type of external cylindrical, centerless, grinding machine with equipment and accessories specified herein.

1.2 Classification. This specification covers grinding machines of the following sizes. The size required for a specific acquisition shall be as specified (see 6.2.1).

Size	Work Capacity Range (Inches diameter) (mm)	Wheel Width (inches) (mm)
1	0" to 1-1/2" (38.1 mm)	4" (101.6 mm)
2	1/16 to 3" (76.2 mm)	8" (203.2 mm)
3	1/2" to 3" (76.2 mm)	12" (304.8 mm)
4	1" to 4" (101.6 mm)	12" (304.8 mm)

When other sizes are required, the machine size and its corresponding characteristics shall be as specified, (see table I).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, Memphis, TN 38114, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

☆U.S.GOVERNMENT PRINTING OFFICE 1983-605-034/4425

FSC 3415

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENT'S

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metalworking, Packaging of

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services

(Copies of specifications, standards, drawings and publications required by supplier in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer,)

2,1.2 Other Government documents, drawings and publications. The following other Government documents form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910)

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following other documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B11.9 - Safety Requirements for the Construction, Care and Use of Grinding Machines
ANSI/NFPA No. 79 - Electrical Standards for Metalworking Machine Tools
ANSI/IEEE 268 - Metric Practices

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM-D-3951 - Commerical packaging of supplies and equipment

(Copies should be obtained from American Society for Testing Materials, 1916 Race St., Philadelphia, PA 19103)

Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish one complete grinding machine for first article inspection and approval (see 4.2 and 6.3).

3.2 Design. The machine shall be new and one of the manufacturer's current models. The machine shall be capable of both infeed and thrufeed grinding and shall be capable of precision grinding of cylindrical centerless or solid workplaces to tolerances specified herein. The machine design shall include all components, parts and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage or distortion shall be accessible for adjustment, replacement and repair.

3.2.1 Reclaimed materials. The machine manufacturer is encouraged to use reclaimed materials to the maximum extent possible without jeopardizing the chemical composition and physical properties of the materials originally selected for the machine construction.

3.2.2 Controls. All operating controls shall be located conveniently to the operator except as otherwise specified herein.

3.2.3 Safety measures. Covers or other safety devices shall be provided for all parts of the machine that present safety hazards. The safety devices shall not interfere with operations of the machine and shall be removable to facilitate inspection, maintenance and repair. Except as otherwise specified by the preparing activity, the machine shall comply with the standards promulgated under OSHA, applicable to the machine itself. In addition, the machine shall comply with all of the requirements of ANSI B11.9 that are designated therein as the responsibility of the machine manufacturer. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

3.2.4 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes and capacities are given in the U.S. Customary System of Units (US). These measurements may be converted to the International System of Units (SI) through the use of the conversion factors and methods specified in ANSI/IEEE 268.

3.2.5 Lubrication. Means shall be provided for lubrication of all sliding and moving parts. Recirculating systems, when provided, shall include filters which are cleanable or replaceable. Each lubricant-reservoir shall have means for determining the fluid level. All oil holes, grease fittings and filler caps shall be readily accessible.

3.2.6 Interchangeability. . To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances which will permit installation of replacement parts without modification of part or machine.

3.3 Construction. The machine shall be constructed of parts which are new, without defects and are free of repair. The structure shall be capable of withstanding all forces encountered during the operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Casting and forgings. All castings and forgings shall be free of scale and mismatching. No process such as peening, plugging or filling with paste shall be used for reclaiming any defective part.

3.3.2 Welding, brazing or soldering. Welding, brazing or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts and other fasteners shall be installed in a manner to prevent change of tightness. Fasteners that are subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be cleaned and free of sand, dirt, fins, sprues, flash, scale, flux and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer’s standard commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with the manufacturer’s standard commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable detailed standard section referenced therein.

3.3.7 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed or stamped in boldface on a contrasting background.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

3.4 Components. The machine shall consist primarily of a bed, grinding and regulating wheelhead assemblies, workrests, grinding and regulating wheel dressers, wheel guards, driving mechanisms and operating controls.

3,4.1 Bed. The bed shall be a one-piece rectangular box section ribbed and brace to minimize distortion, deflection and vibration under normal workloads. Guideways shall be provided for supporting either the grinding wheelhead assembly or the regulating wheelhead assembly according to machine design. The hydraulic oil and coolant reservoirs may be integral parts of the bed or furnished as separate units. Means for leveling shall be provided around the periphery of the base. When applicable, an access door(s) or removable plate(s) shall be provided for servicing components housed within the bed.

3.4.2 Grinding wheelhead assembly. The grinding wheelhead assembly shall include a grinding wheel spindle, wheel dresser, and driving mechanism. The wheelhead assembly shall be either fixed or adjustable, according to design. When an adjustable wheelhead assembly is incorporated in the machine design, unless otherwise specified (see 6.2.1), manual infeed shall be provided. Manual adjustment shall be controlled by a graduated handwheel with a wheelfeed index; each graduation shall indicate not more than 0.001 inch on work diameter. An adjustable coolant nozzle with means for controlling coolant flow shall be provided.

3.4.2,1 Grinding wheel spindle. The grinding wheel spindle shall be of alloy steel arranged with a spindle nose at one end and means for accepting a driving mechanism at the other end. The design of the spindle and the configuration of the bearing support system shall minimize sag caused by the weight of the spindle and wheel deflection caused by all forces operating on the spindle. The spindle shall be mounted in lubricated bearings unless sealed-for-life type or otherwise permanently lubricated bearings are utilized. Spindle noses shall be designed to securely accept wheel mount assemblies.

3.4.2.2 Grinding wheel drive. The grinding wheel shall be driven through a motor and belt(s) and pulley arrangement. Motor speed shall he constant. Means for adjusting belt tension shall be provided.

3.4.2.3 Grinding wheel dresser. The grinding wheel dresser shall be attached to the bed or wheel housing casting. A micro-meter type indicator or dial graduated in 0.001 inch increments shall be provided for designating movement.. Range of dressing shall be not less than O to 2-1/2 inches bar movement on Size 1 machines, and not less than O to 3-1/2 inches bar movement on Size 2, 3 and 4 machines. A hydraulic feeding mechanism shall be provided for traversing the diamond across the wheel. The dresser shall be capable of contour dressing as well as straight dressing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

3.4.3 Regulating wheelhead assembly. The regulating wheelhead assembly shall include a regulating wheel, spindle, wheel dresser, and driving mechanism. The wheelhead shall be either fixed or adjustable, according to machine design. When an adjustable regulating wheelhead is incorporated, unless otherwise specified, (see 6.2.1), manual infeed shall be -provided. Manual adjustment shall be controlled by a handwheel with graduated dial. The tilting and swiveling action shall be adjustable, with positive clamping. A scale, graduated in degrees, shall be provided for measuring tilt. Means for correcting taper shall be provided in the wheelhead base.

3.4.3.1 Regulating wheel spindle. The regulating wheel spindle drive shall include a drive motor, belt and pulley arrangement, spindle speed adjustment system, and a dial type speed indicating device, calibrated in revolutions per minute over the applicable speed range. Means for adjusting belt tension shall be provided.

3.4.3.2 Regulating wheel dresser. The regulating wheel dresser shall be attached to the wheelhead and unless otherwise specified (see 6.2.1), shall be manually operated. A micrometer type indicator or dial, graduated in 0.001 inch increments, shall be provided for designating movement. Range of dressing shall be not less than O to 1 inch bar movement for Size 1 machines, and not less than O to 1-3/4 inches bar movement for Size 2, 3 and 4. When specified (see 6.2.1), the dresser shall be capable of contour dressing as well as straight dressing.

3.5 Workrests. Each workrest shall be machined, and shall be mounted on the bed or on the lower slide of the regulating wheelhead base. One workrest shall be provided for thrufeed operation, and one for infeed operation. When the design of the machine includes only one workrest, necessary interchangeable components for infeed grinding and thrufeed grinding shall be furnished.

3.6 Sizes and capacities. The sizes and capacities of the machine shall meet the requirements of table I. Options shall be furnished only when specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

TABLE I
Sizes and capacities

CHARACTERISTIC	REQUIREMENT			
	Size 1	Size 2	Size 3	Size 4
Work capacity, diameter range, inches	0" to 1 1/2	1/16 to 3	1/2 to 3	1" to 4"
Optional range	--	2 to 4-3/4	2 to 6	
Taper grinding, degrees (included angle)	7	7	7	7
Wheel sizes, inches				
Grinding wheel width capacity	4	8	12	12
Grinding wheel diameter and hole size	16 x 8	20 x 12	24x12	24 x 12
Worn grinding wheel diameter, usable to not more than	12	18	18	18
Regulating wheel width capacity	4	8	12	15
Regulating wheel diameter and hole size	8 x 3	12 x 5	12 x 6	14 x 6
Worn regulating wheel diameter, usable to not more than	7-3/4	11-1/2	11-1/2	13-1/2
Regulating wheelhead				
Angle of tilt for thru-feed grinding, degrees	7	7	7	7
Angle of reverse tilt for thrufeed grinding,degrees	1-3/4	2	2	2
Regulating wheel speeds				
Spindle speeds, number	infinite	infinite	infinite	infinite
Spindle speed range,RPM	15 to 300	15 to 300	15 to 300	15 to 300
Motors, horsepower				
Grinding wheel drive	7-1/2	15	25	30
Optional	--	20 or 30	30 or 40	40
Regulating wheel drive	1/2	1-1/2	2	2
Coolant Pump	1/4	1/2	3/4	3/4
Hydraulic oil pump	1/2	1	1-1/2	2

Requirements are not less than those shown, unless otherwise in indicated Where a range is shown, the performance shall encompass a range from the stated minimum or less to the stated maximum or greater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

3.7 Performance. Each machine shall be capable of grit ding three (3) test rods of the size required in 4.5.2. Roundness, diamete- variation and surface finish shall be in accordance with the requirements in 4.5.2.

3.8 Alignment tolerances. Each machine shall meet the alignment tolerances designated in 4.5.3.

3.9 Motors. Motors shall have ball or roller bearings. Continuous duty horsepower ratings shall conform to the requirements of table I. Unless otherwise specified (see 6.2.1) each motor shall meet the requirements of a totally enclosed, fan cooled (TEFC) motor.

3.10 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to the requirements of ANS1/NFPA-79. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit having a fused safety disconnect switch. The grinder shall be Initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in Table 240/A of ANSI/NFPA-79 for the disconnect fuse rating.

3.11 Coolant system. A coolant system shall be furnished. otherwise specified (see 6.2.1), it shall be of the flood type. The flood type system shall include a sump or reservoir, a power driven pump and piping. The coolant reservoir shall be of sufficient capacity to permit full flow cooling. The coolant system shall include a baffle(s) or strainer which is easily removable for cleaning. The reservoir shall be equipped with means for emptying and cleaning. A coolant delivery nozzel and valve shall be provided to permit the operator to direct and control the amount of coolant flow.

3,12 Hydraulic system. The hydraulic system, if furnished, shall be complete including pumps, valves, piping, cylinders and pressure controls. Overpressure protection shall be provided on the high pressure line from the hydraulic pump to prevent damage to components. A filter system shall be provided to insure delivery of clean fluid to the hydraulic system. The hydraulic reservoir shall have a sight gage to indicate the fluid level.

3.13 Standard equipment. Unless otherwise specified (see 6.2.1), each machine shall be furnished with all standard equipment, including all maintenance tools normally furnished by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

3.14 Optional equipment. Optional equipment shall be furnished as specified and fully described, (see 6.2.1).

3.15 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be securely attached to the machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application
Service interval
Type of lubricant
Viscosity

3.16 Nameplate. A corrosion-resistant metal nameplate marked with the following information shall be securely attached to each machine. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix keyed to the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each such caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Size_____
Workpiece capacity range_____to_____ inch diameter

3.17 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.18 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of-all inspection requirements as specified herein. Except as otherwise specified, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of-the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

4.2 First article inspection When first article approval is required under 3.1, first article inspection shall be performed. Unless otherwise specified (see 6.2.1), first article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure to pass the examination or any part of the test shall be cause for disapproval of the first article.

4.3 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the test in 4.5.1 and the inspection in 4.6. Failure of an item to pass any examination or test shall be cause for rejection.

4.4 Examination. The machine and equipment shall be examined for compliance with the requirements in 3.2 through 3.6 and 3.9 through 3.19.

4.5 Tests.

4.5.1 Operational tests. The machine shall be operated at no load for not less than 60 minutes. Proper operation of all controls, motors. adjusting mechanisms and other accessories shall be verified during the trial period.

4.5.2 Performance tests. Each machine shall be tested by grinding 3 rods from C-1045 steel. For size 1 machines, each rod shall be 1 inch “n diameter by 3 inches in length. For size 2 and 3 machines, each rod shall be 2 inches in diameter and 4 inches in length. For size 4 machines, each rod shall be 4 inches in diameter by 6 inches in length. The. grinding wheel and machine settings shall be at the discretion of the supplier. Stock removal shall be not less than 0.010 inch on the diameter. After grinding, end-to-end variation in diameter measurement shall not be more than .0002 inch at any point, with a surface finish not rougher than 30 micro-inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

4.5.3 Alignment tests. Each machine and its components shall be tested for alignment accuracies. Unless otherwise specified (see 6.2.1), the alignment accuracies shall be in accordance with table II. The Instruments and methods used in performing the tests shall be at the option of the supplier provided they accurately determine the tolerances of the machine.

TABLE 11

Alignment accuracy test

TEST TO BE APPLIED	PERMISSIBLE DEVIATION
Grinding wheel spindle for true running	0.0005 inch TIR
Grinding wheel spindle for axial slip	0.0005 inch TIR
Regulating wheel spindle for true running	0.0008 inch TIR
Regulating wheel spindle for axial slip	0.0008 inch TIR
# Regulating wheelhead slide longitudinal movement parallel with bed surface	0.001 inch in 12 inches
# Grinding wheelhead slide longitudinal movement parallel with bed surface	0.001 inch in 12 inches
Workrest parallel with axis of grinding and regulating wheel spindles	0.005 inch in 12 inches

As applicale.

4.6 Inspection of preparation for delivery. Preservation-packaging, packing and marking shall be inspected to determine compliance with the requirements of Section 5.

5, PACKAGING

5.1 Packaging, packing and markings. Unless otherwise specified, packaging, packing and marking shall be in accordance with ASTM Standard D 3951. When required, level A packaging and level A or B packing and marking shall be in accordance with the applicable requirements of MIL-M-10858. The required levels and special marking, if required shall be as specified (see 6.2.1).

6. NOTES.

6.1 Intended use. The grinding machines covered by this specification are intended to be used for the precision cylindrical grinding of centerless and solid sections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

a. Title, number, and date of this specification.
b. Size required (see 1.2).
c. First article approval, if required (see 3.1).
d. Additional safety and health requirements (see 3.2.3).
e. Specify automatic infeed, if required on the adjustable wheelhead assembly (see 3.4.2 and 3.4.3).
f. Printing, if different (see 3.3.5).
g. Regulating wheel dresser operation, if different (see 3.4.3.2).
h. Contour dressing, if required (see 3.4.3.2).
i. Options, if required and machine requirements, if different (see table 1).
j. Type of enclosure for motors, if different (see 3.9).
k. Electrical system, if different (see 3.10).
1. Voltage for initial wiring (see 3.10).
m. Coolant system type, if different (see 3.11).
n. Standard equipment, if different (see 3.13).
o. Optional equipment, if required (see 3.14).
p. Lubrication chart, if different (see 3.15).
q. First article inspection, if different (see 4.2).
r. Quality conformance inspection, if different (see 4.3).
s. Alignment accuracies, if different (see 4.5.3).
t. Preparation for delivery, if different (see 5.1). (Specify level A packaging, specify level A or B packing and specify special marking if required.)

6.2.2 Data requirements. Required technical data such as operator's manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance as identified on a numbered DD Form 1664 should be specified on a DD Form 1423 incorporated into the contract.

6.3 First article. When a first article is required it shall be tested and approved under appropriate provisions of 7-104, 55 of the Defense Acquisition Regulation. The first article should be a preproduction sample or a standard production item from the contractor's current inventory. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examinations, tests, and approval of the first article. Military packaging, packing and special marking, if required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

6.4 Safety and health requirements. Paragraph 3.2.4 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with OSHA requirements that concern "the machine in its operating 'environment" such 'as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total hazard level of these hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. If specific point-of operation guarding is required, the procuring agency should specify the exact configuration of the guard required, as in most cases, the guard configuration is dependent on the size and configuration of the workplaces. The above, and any other additional safety and health requirements should be specified in detail under 6.2.1.

6.5 Changes from previous issue. Astericks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.6 Cross-reference of classification changes. Machine classification changes from the previous issue of this specification are as follows:

MIL-G-80048B	MIL-G-80048C
Size 1	Size 1
Size 2	Size 2
Size 3	Size 3
	Size 4 (New Size)
Custodians:	Preparing Activity:
AL-(39	IP
Reviewing Activities:	Project Number
GS-84-AL	3415-0119

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, wa too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to wa ve any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY
Headquarters
se Industrial Plant Equipment Center
Memphis, Tennessee 38114

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATE

O, FICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TES
Memphis, Tennessee 38114

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-80048C	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* — Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* — Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* — Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:34Z
Check the source to verify that this is the current version before use.