INCH-POUND
MIL-PRF-49470/2D
19 January 2011
SUPERSEDING
MIL-PRF-49470/2C
08 December 2006

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, FIXED, CERAMIC DIELECTRIC, SWITCH MODE POWER SUPPLY (GENERAL PURPOSE AND TEMPERATURE STABLE), STANDARD RELIABILITY AND HIGH RELIABILITY, ENCAPSULATED, HORIZONTALLY STACKED, STYLE PS02

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-49470.




FIGURE 1. Style PS02 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

Dimensions				
Case code	C ± .025	D ± .025	E (max)	Number of leads per side
1	.450	2.155	.580	20
2	.800	1.615	.950	15
3	.450	1.155	.580	10
4	.400	.485	.485	4
5	.250	.355	.355	3
6	1.250	2.155	1.430	20

Inches	mm
.002	0.05
.010	0.25
.020	0.51
.025	0.64
.050	1.27
.055	1.40
.070	1.78
.100	2.54
.224	5.69
.250	6.35
.275	6.98
.300	7.62
.350	8.89
.400	10.16
.425	10.80
.440	11.18
.450	11.43
.500	12.70
.800	20.32
.870	22.10
.950	24.13
1.075	27.30
1.250	31.75
1.350	34.29
1.450	36.83
1.535	38.99
1.950	49.53
2.075	52.70

Symbol (last digit of PIN)	Lead style	Height profile (Dimension A)	Formed lead length, L (inches)
N	N (straight)	Standard	N/A
L	L (formed)	Standard	.070 ± .010
M	L (formed)	Standard	.045 ± .010
J	J (formed)	Standard	.070 ± .010
K	J (formed)	Standard	.045 ± .010
A	N (straight)	Low	N/A
B	L (formed)	Low	.070 ± .010
D	L (formed)	Low	.045 ± .010
C	J (formed)	Low	.070 ± .010
F	J (formed)	Low	.045 ± .010

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 inch (0.25 mm).
4. See table I for specific maximum A dimension. For all lead styles, the number of chips is determined by the capacitance and voltage rating.
5. Lead alignment within pin rows shall be within ±.005 inch (0.13 mm).

FIGURE 1. Style PS02 capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Precautionary note: Capacitors covered by this specification sheet are very susceptible to thermal shock damage due to their large ceramic mass. Temperature profiles used should provide adequate temperature rise and cool-down time to prevent damage from thermal shock.

Dimensions and configurations: See figure 1.

Case type: Encapsulated, horizontally stacked.

Capacitance: See table I.

Capacitance tolerance: J = ±5 percent, K = ±10 percent, M = ±20 percent.

Operating temperature range: -55°C to +125°C.

Voltage rating: See table I.

Dielectric types: BP, BQ, BR, and BX in accordance with MIL-PRF-49470.

Temperature coefficient: 0 ppm/°C ±30 ppm/°C (BP), ±15 percent (BQ, BR, BX).

Voltage-temperature limits: In accordance with MIL-PRF-49470.

Symbol	Capacitance change with reference to +25°C	
	Step A through step D of voltage-temperature limit cycle table of MIL-PRF-49470	Step E through step G of voltage-temperature limit cycle table of MIL-PRF-49470
BP	0 ppm/°C ± 30 ppm/°C	0 ppm/°C ± 30 ppm/°C
BQ	±15 percent	+15, -50 percent
BR	±15 percent	+15, -40 percent
BX	±15 percent	+15, -25 percent

Marking: In accordance with MIL-PRF-49470.

Body insulation: In accordance with MIL-PRF-49470.

Solderability: The leads shall be solderable up to .050 inch (1.27 mm) from the seating plane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
25 V						
-49470X01155-Z-	1.5	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470X01185-Z-	1.8	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470X01225-Z-	2.2	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470X01275-Z-	2.7	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470X01335-Z-	3.3	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470X01395-Z-	3.9	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470X01475-Z-	4.7	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470X01565-Z-	5.6	K, M	BX	5	N, L, M, J, K	.530 (13.46)
-49470X01685-Z-	6.8	K, M	BX	5	N, L, M, J, K	.530 (13.46)
-49470X01685-Z-	6.8	K, M	BX	4	A, B, D, C, F	.270 (6.86)
-49470X01825-Z-	8.2	K, M	BX	5	N, L, M, J, K	.660 (16.76)
-49470X01825-Z-	8.2	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470X01106-Z-	10	K, M	BX	5	N, L, M, J, K	.800 (20.32)
-49470X01106-Z-	10	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470X01126-Z-	12	K, M	BX	4	N, L, M, J, K	.390 (9.91)
-49470X01156-Z-	15	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470X01156-Z-	15	K, M	BX	3	A, B, D, C, F	.270 (6.86)
-49470X01186-Z-	18	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470X01186-Z-	18	K, M	BX	3	A, B, D, C, F	.270 (6.86)
-49470X01226-Z-	22	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470X01226-Z-	22	K, M	BX	3	A, B, D, C, F	.390 (9.91)
-49470X01276-Z-	27	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470X01276-Z-	27	K, M	BX	3	A, B, D, C, F	.390 (9.91)
-49470X01336-Z-	33	K, M	BX	4	N, L, M, J, K	.800 (20.32)
-49470X01336-Z-	33	K, M	BX	3	A, B, D, C, F	.390 (9.91)
-49470X01396-Z-	39	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X01396-Z-	39	K, M	BX	1	A, B, D, C, F	.390 (9.91)
-49470X01476-Z-	47	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X01476-Z-	47	K, M	BX	1	A, B, D, C, F	.390 (9.91)
-49470X01566-Z-	56	K, M	BX	3	N, L, M, J, K	.660 (16.76)
-49470X01566-Z-	56	K, M	BX	1	A, B, D, C, F	.530 (13.46)
-49470X01686-Z-	68	K, M	BX	3	N, L, M, J, K	.660 (16.76)
-49470X01686-Z-	68	K, M	BX	1	A, B, D, C, F	.530 (13.46)
-49470X01826-Z-	82	K, M	BX	3	N, L, M, J, K	.800 (20.32)
-49470X01826-Z-	82	K, M	BX	1	A, B, D, C, F	.530 (13.46)
-49470X01107-Z-	100	K, M	BX	1	N, L, M, J, K	.660 (16.76)
-49470X01107-Z-	100	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X01127-Z-	120	K, M	BX	1	N, L, M, J, K	.800 (20.32)
-49470X01127-Z-	120	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X01157-Z-	150	K, M	BX	2	N, L, M, J, K	.660 (16.76)
-49470X01157-Z-	150	K, M	BX	6	A, B, D, C, F	.390 (9.91)
-49470X01187-Z-	180	K, M	BX	2	N, L, M, J, K	.800 (20.32)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
25 V						
-49470X01187-Z-	180	K, M	BX	6	A, B, D, C, F	.530 (13.46)
-49470X01227-Z-	220	K, M	BX	6	N, L, M, J, K	.530 (13.46)
-49470X01277-Z-	270	K, M	BX	6	N, L, M, J, K	.660 (16.76)
-49470X01337-Z-	330	K, M	BX	6	N, L, M, J, K	.800 (20.32)
-49470X01397-Z-	390	K, M	BX	6	N, L, M, J, K	.800 (20.32)
50 V						
-49470P02563-A-	0.056	J, K	BP	5	N, L, M, J, K	.270 (6.86)
-49470P02683-A-	0.068	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02823-A-	0.082	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02104-A-	0.1	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02124-A-	0.12	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02154-A-	0.15	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02184-A-	0.18	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02184-A-	0.18	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02224-A-	0.22	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02224-A-	0.22	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02274-A-	0.27	J, K	BP	5	N, L, M, J, K	.800 (20.32)
-49470P02274-A-	0.27	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02334-A-	0.33	J, K	BP	4	N, L, M, J, K	.530 (13.46)
-49470P02394-A-	0.39	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02474-A-	0.47	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02564-A-	0.56	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02564-A-	0.56	J, K	BP	3	A, B, D, C, F	.390 (9.91)
-49470P02684-A-	0.68	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470P02824-A-	0.82	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470P02105-A-	1	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470X02105-A-	1	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470P02125-A-	1.2	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470X02125-A-	1.2	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470P02155-A-	1.5	J, K	BP	3	N, L, M, J, K	.600 (15.24)
-49470X02155-A-	1.5	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02185-A-	1.8	J, K	BP	3	N, L, M, J, K	.660 (16.76)
-49470X02185-A-	1.8	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02225-A-	2.2	J, K	BP	3	N, L, M, J, K	.800 (20.32)
-49470P02225-A-	2.2	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470X02225-A-	2.2	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02275-A-	2.7	J, K	BP	1	N, L, M, J, K	.530 (13.46)
-49470P02275-A-	2.7	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470X02275-A-	2.7	K, M	BX	5	N, L, M, J, K	.530 (13.46)
-49470P02335-A-	3.3	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02335-A-	3.3	J, K	BP	2	A, B, D, C, F	.530 (13.46)
-49470X02335-A-	3.3	K, M	BX	5	N, L, M, J, K	.530 (13.46)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
50 V						
-49470P02395-A-	3.9	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02395-A-	3.9	J, K	BP	2	A, B, D, C, F	.660 (16.76)
-49470X02395-A-	3.9	K, M	BX	5	N, L, M, J, K	.660 (16.76)
-49470P02475-A-	4.7	J, K	BP	1	N, L, M, J, K	.800 (20.32)
-49470P02475-A-	4.7	J, K	BP	2	A, B, D, C, F	.660 (16.76)
-49470X02475-A-	4.7	K, M	BX	5	N, L, M, J, K	.660 (16.76)
-49470X02475-A-	4.7	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470P02565-A-	5.6	J, K	BP	2	N, L, M, J, K	.800 (20.32)
-49470X02565-A-	5.6	K, M	BX	5	N, L, M, J, K	.800 (20.32)
-49470X02565-A-	5.6	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470P02685-A-	6.8	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470X02685-A-	6.8	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470P02825-A-	8.2	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470X02825-A-	8.2	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470P02106-A-	10	J, K	BP	6	N, L, M, J, K	.660 (16.76)
-49470X02106-A-	10	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470P02126-A-	12	J, K	BP	6	N, L, M, J, K	.660 (16.76)
-49470X02126-A-	12	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470P02156-A-	15	J, K	BP	6	N, L, M, J, K	.800 (20.32)
-49470X02156-A-	15	K, M	BX	4	N, L, M, J, K	.800 (20.32)
-49470X02156-A-	15	K, M	BX	3	A, B, D, C, F	.390 (9.91)
-49470X02186-A-	18	K, M	BX	3	N, L, M, J, K	.390 (9.91)
-49470X02226-A-	22	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X02276-A-	27	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X02336-A-	33	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X02396-A-	39	K, M	BX	3	N, L, M, J, K	.660 (16.76)
-49470X02476-A-	47	K, M	BX	3	N, L, M, J, K	.800 (20.32)
-49470X02476-A-	47	K, M	BX	2	A, B, D, C, F	.390 (9.91)
-49470X02566-A-	56	K, M	BX	1	N, L, M, J, K	.530 (13.46)
-49470X02566-A-	56	K, M	BX	2	A, B, D, C, F	.390 (9.91)
-49470X02686-A-	68	K, M	BX	1	N, L, M, J, K	.660 (16.76)
-49470X02686-A-	68	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X02826-A-	82	K, M	BX	1	N, L, M, J, K	.660 (16.76)
-49470X02826-A-	82	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X02107-A-	100	K, M	BX	1	N, L, M, J, K	.800 (20.32)
-49470X02107-A-	100	K, M	BX	2	A, B, D, C, F	.660 (16.76)
-49470X02127-A-	120	K, M	BX	2	N, L, M, J, K	.660 (16.76)
-49470X02157-A-	150	K, M	BX	2	N, L, M, J, K	.800 (20.32)
-49470X02187-A-	180	K, M	BX	6	N, L, M, J, K	.660 (16.76)
-49470X02227-A-	220	K, M	BX	6	N, L, M, J, K	.660 (16.76)
-49470X02277-A-	270	K, M	BX	6	N, L, M, J, K	.800 (20.32)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
100 V						
-49470P02473-B-	0.047	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02563-B-	0.056	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02683-B-	0.068	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02823-B-	0.082	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02104-B-	0.1	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02124-B-	0.12	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02154-B-	0.15	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02154-B-	0.15	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02184-B-	0.18	J, K	BP	5	N, L, M, J, K	.800 (20.32)
-49470P02184-B-	0.18	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02224-B-	0.22	J, K	BP	5	N, L, M, J, K	.800 (20.32)
-49470P02224-B-	0.22	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02274-B-	0.27	J, K	BP	4	N, L, M, J, K	.530 (13.46)
-49470P02334-B-	0.33	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02394-B-	0.39	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02474-B-	0.47	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02474-B-	0.47	J, K	BP	3	A, B, D, C, F	.390 (9.91)
-49470P02564-B-	0.56	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02564-B-	0.56	J, K	BP	3	A, B, D, C, F	.390 (9.91)
-49470P02684-B-	0.68	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470X02684-B-	0.68	K, M	BX	5	N, L, M, J, K	.270 (6.86)
-49470P02824-B-	0.82	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470X02824-B-	0.82	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02105-B-	1	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470X02105-B-	1	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02125-B-	1.2	J, K	BP	3	N, L, M, J, K	.660 (16.76)
-49470X02125-B-	1.2	K, M	BX	5	N, L, M, J, K	.390 (9.91)
-49470P02155-B-	1.5	J, K	BP	3	N, L, M, J, K	.660 (16.76)
-49470X02155-B-	1.5	K, M	BX	5	N, L, M, J, K	.530 (13.46)
-49470P02185-B-	1.8	J, K	BP	3	N, L, M, J, K	.800 (20.32)
-49470P02185-B-	1.8	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470X02185-B-	1.8	K, M	BX	5	N, L, M, J, K	.530 (13.46)
-49470P02225-B-	2.2	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470X02225-B-	2.2	K, M	BX	5	N, L, M, J, K	.660 (16.76)
-49470X02225-B-	2.2	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470P02275-B-	2.7	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470X02275-B-	2.7	K, M	BX	5	N, L, M, J, K	.660 (16.76)
-49470P02335-B-	3.3	J, K	BP	1	N, L, M, J, K	.800 (20.32)
-49470P02335-B-	3.3	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470X02335-B-	3.3	K, M	BX	5	N, L, M, J, K	.800 (20.32)
-49470X02335-B-	3.3	K, M	BX	4	A, B, D, C, F	.390 (9.91)
-49470P02395-B-	3.9	J, K	BP	2	N, L, M, J, K	.660 (16.76)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
100 V						
-49470X02395-B-	3.9	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470P02475-B-	4.7	J, K	BP	2	N, L, M, J, K	.800 (20.32)
-49470X02475-B-	4.7	K, M	BX	4	N, L, M, J, K	.530 (13.46)
-49470P02565-B-	5.6	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470X02565-B-	5.6	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470P02685-B-	6.8	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470X02685-B-	6.8	K, M	BX	4	N, L, M, J, K	.660 (16.76)
-49470P02825-B-	8.2	J, K	BP	6	N, L, M, J, K	.660 (16.76)
-49470X02825-B-	8.2	K, M	BX	4	N, L, M, J, K	.800 (20.32)
-49470X02825-B-	8.2	K, M	BX	3	A, B, D, C, F	.390 (9.91)
-49470P02106-B-	10	J, K	BP	6	N, L, M, J, K	.800 (20.32)
-49470X02106-B-	10	K, M	BX	3	N, L, M, J, K	.390 (9.91)
-49470P02126-B-	12	J, K	BP	6	N, L, M, J, K	.800 (20.32)
-49470X02126-B-	12	K, M	BX	3	N, L, M, J, K	.390 (9.91)
-49470X02156-B-	15	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X02186-B-	18	K, M	BX	3	N, L, M, J, K	.530 (13.46)
-49470X02226-B-	22	K, M	BX	3	N, L, M, J, K	.660 (16.76)
-49470X02276-B-	27	K, M	BX	3	N, L, M, J, K	.800 (20.32)
-49470X02276-B-	27	K, M	BX	2	A, B, D, C, F	.390 (9.91)
-49470X02336-B-	33	K, M	BX	1	N, L, M, J, K	.530 (13.46)
-49470X02336-B-	33	K, M	BX	2	A, B, D, C, F	.390 (9.91)
-49470X02396-B-	39	K, M	BX	1	N, L, M, J, K	.660 (16.76)
-49470X02396-B-	39	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X02476-B-	47	K, M	BX	1	N, L, M, J, K	.660 (16.76)
-49470X02476-B-	47	K, M	BX	2	A, B, D, C, F	.530 (13.46)
-49470X02566-B-	56	K, M	BX	1	N, L, M, J, K	.800 (20.32)
-49470X02686-B-	68	K, M	BX	2	N, L, M, J, K	.660 (16.76)
-49470X02826-B-	82	K, M	BX	2	N, L, M, J, K	.800 (20.32)
-49470X02107-B-	100	K, M	BX	6	N, L, M, J, K	.530 (13.46)
-49470X02127-B-	120	K, M	BX	6	N, L, M, J, K	.530 (13.46)
-49470X02157-B-	150	K, M	BX	6	N, L, M, J, K	.660 (16.76)
-49470X02187-B-	180	K, M	BX	6	N, L, M, J, K	.800 (20.32)
200V						
-49470P02223-C-	0.022	J, K	BP	5	N, L, M, J, K	.270 (6.86)
-49470P02273-C-	0.027	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02333-C-	0.033	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02393-C-	0.039	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02473-C-	0.047	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02563-C-	0.056	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02683-C-	0.068	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02683-C-	0.068	J, K	BP	4	A, B, D, C, F	.270 (6.86)
-49470P02823-C-	0.082	J, K	BP	5	N, L, M, J, K	.800 (20.32)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
200 V						
-49470P02823-C-	0.082	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02104-C-	0.1	J, K	BP	5	N, L, M, J, K	.800 (20.32)
-49470P02104-C-	0.1	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02124-C-	0.12	J, K	BP	4	N, L, M, J, K	.530 (13.46)
-49470P02154-C-	0.15	J, K	BP	4	N, L, M, J, K	.530 (13.46)
-49470P02184-C-	0.18	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02224-C-	0.22	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02274-C-	0.27	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02274-C-	0.27	J, K	BP	3	A, B, D, C, F	.390 (9.91)
-49470P02334-C-	0.33	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470P02394-C-	0.39	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470P02474-C-	0.47	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470R02474-C-	0.47	K, M	BR	5	N, L, M, J, K	.390 (9.91)
-49470P02564-C-	0.56	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470R02564-C-	0.56	K, M	BR	5	N, L, M, J, K	.390 (9.91)
-49470P02684-C-	0.68	J, K	BP	3	N, L, M, J, K	.660 (16.76)
-49470R02684-C-	0.68	K, M	BR	5	N, L, M, J, K	.530 (13.46)
-49470P02824-C-	0.82	J, K	BP	3	N, L, M, J, K	.800 (20.32)
-49470P02824-C-	0.82	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470R02824-C-	0.82	K, M	BR	5	N, L, M, J, K	.530 (13.46)
-49470P02105-C-	1	J, K	BP	3	N, L, M, J, K	.800 (20.32)
-49470P02105-C-	1	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470R02105-C-	1	K, M	BR	5	N, L, M, J, K	.660 (16.76)
-49470R02105-C-	1	K, M	BR	4	A, B, D, C, F	.270 (6.86)
-49470P02125-C-	1.2	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02125-C-	1.2	J, K	BP	2	A, B, D, C, F	.530 (13.46)
-49470R02125-C-	1.2	K, M	BR	5	N, L, M, J, K	.660 (16.76)
-49470R02125-C-	1.2	K, M	BR	4	A, B, D, C, F	.390 (9.91)
-49470P02155-C-	1.5	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02155-C-	1.5	J, K	BP	2	A, B, D, C, F	.530 (13.46)
-49470R02155-C-	1.5	K, M	BR	5	N, L, M, J, K	.800 (20.32)
-49470R02155-C-	1.5	K, M	BR	4	A, B, D, C, F	.390 (9.91)
-49470P02185-C-	1.8	J, K	BP	1	N, L, M, J, K	.800 (20.32)
-49470P02185-C-	1.8	J, K	BP	2	A, B, D, C, F	.660 (16.76)
-49470R02185-C-	1.8	K, M	BR	4	N, L, M, J, K	.530 (13.46)
-49470P02225-C-	2.2	J, K	BP	2	N, L, M, J, K	.660 (16.76)
-49470R02225-C-	2.2	K, M	BR	4	N, L, M, J, K	.530 (13.46)
-49470P02275-C-	2.7	J, K	BP	2	N, L, M, J, K	.800 (20.32)
-49470R02275-C-	2.7	K, M	BR	4	N, L, M, J, K	.660 (16.76)
-49470P02335-C-	3.3	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470R02335-C-	3.3	K, M	BR	4	N, L, M, J, K	.660 (16.76)
-49470P02395-C-	3.9	J, K	BP	6	N, L, M, J, K	.530 (13.46)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
200 V						
-49470R02395-C-	3.9	K, M	BR	4	N, L, M, J, K	.800 (20.32)
-49470R02395-C-	3.9	K, M	BR	3	A, B, D, C, F	.390 (9.91)
-49470P02475-C-	4.7	J, K	BP	6	N, L, M, J, K	.660 (16.76)
-49470R02475-C-	4.7	K, M	BR	3	N, L, M, J, K	.390 (9.91)
-49470P02565-C-	5.6	J, K	BP	6	N, L, M, J, K	.800 (20.32)
-49470R02565-C-	5.6	K, M	BR	3	N, L, M, J, K	.390 (9.91)
-49470R02685-C-	6.8	K, M	BR	3	N, L, M, J, K	.530 (13.46)
-49470R02825-C-	8.2	K, M	BR	3	N, L, M, J, K	.530 (13.46)
-49470R02106-C-	10	K, M	BR	3	N, L, M, J, K	.660 (16.76)
-49470R02126-C-	12	K, M	BR	3	N, L, M, J, K	.800 (20.32)
-49470R02126-C-	12	K, M	BR	2	A, B, D, C, F	.390 (9.91)
-49470R02156-C-	15	K, M	BR	1	N, L, M, J, K	.530 (13.46)
-49470R02156-C-	15	K, M	BR	2	A, B, D, C, F	.390 (9.91)
-49470R02186-C-	18	K, M	BR	1	N, L, M, J, K	.660 (16.76)
-49470R02186-C-	18	K, M	BR	2	A, B, D, C, F	.530 (13.46)
-49470R02226-C-	22	K, M	BR	1	N, L, M, J, K	.800 (20.32)
-49470R02226-C-	22	K, M	BR	2	A, B, D, C, F	.530 (13.46)
-49470R02276-C-	27	K, M	BR	1	N, L, M, J, K	.800 (20.32)
-49470R02276-C-	27	K, M	BR	2	A, B, D, C, F	.660 (16.76)
-49470R02336-C-	33	K, M	BR	2	N, L, M, J, K	.660 (16.76)
-49470R02396-C-	39	K, M	BR	2	N, L, M, J, K	.800 (20.32)
-49470R02476-C-	47	K, M	BR	6	N, L, M, J, K	.390 (9.91)
-49470R02566-C-	56	K, M	BR	6	N, L, M, J, K	.530 (13.46)
-49470R02686-C-	68	K, M	BR	6	N, L, M, J, K	.530 (13.46)
-49470R02826-C-	82	K, M	BR	6	N, L, M, J, K	.660 (16.76)
-49470R02107-C-	100	K, M	BR	6	N, L, M, J, K	.800 (20.32)
-49470R02127-C-	120	K, M	BR	6	N, L, M, J, K	.800 (20.32)
500V						
-49470P02103-E-	0.01	J, K	BP	5	N, L, M, J, K	.270 (6.86)
-49470P02123-E-	0.012	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02153-E-	0.015	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02183-E-	0.018	J, K	BP	5	N, L, M, J, K	.390 (9.91)
-49470P02223-E-	0.022	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02273-E-	0.027	J, K	BP	5	N, L, M, J, K	.530 (13.46)
-49470P02333-E-	0.033	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02333-E-	0.033	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02393-E-	0.039	J, K	BP	5	N, L, M, J, K	.660 (16.76)
-49470P02393-E-	0.039	J, K	BP	4	A, B, D, C, F	.390 (9.91)
-49470P02473-E-	0.047	J, K	BP	5	N, L, M, J, K	.800 (20.32)
-49470P02473-E-	0.047	J, K	BP	4	A, B, D, C, F	.530 (13.46)
-49470P02563-E-	0.056	J, K	BP	4	N, L, M, J, K	.530 (13.46)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
500 V						
-49470P02683-E-	0.068	J, K	BP	4	N, L, M, J, K	.660 (16.76)
-49470P02823-E-	0.082	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02104-E-	0.1	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02124-E-	0.12	J, K	BP	4	N, L, M, J, K	.800 (20.32)
-49470P02124-E-	0.12	J, K	BP	3	A, B, D, C, F	.390 (9.91)
-49470P02154-E-	0.15	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470Q02154-E-	0.15	K, M	BQ	5	N, L, M, J, K	.270 (6.86)
-49470P02184-E-	0.18	J, K	BP	3	N, L, M, J, K	.390 (9.91)
-49470Q02184-E-	0.18	K, M	BQ	5	N, L, M, J, K	.390 (9.91)
-49470P02224-E-	0.22	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470Q02224-E-	0.22	K, M	BQ	5	N, L, M, J, K	.390 (9.91)
-49470P02274-E-	0.27	J, K	BP	3	N, L, M, J, K	.530 (13.46)
-49470Q02274-E-	0.27	K, M	BQ	5	N, L, M, J, K	.390 (9.91)
-49470P02334-E-	0.33	J, K	BP	3	N, L, M, J, K	.660 (16.76)
-49470Q02334-E-	0.33	K, M	BQ	5	N, L, M, J, K	.530 (13.46)
-49470P02394-E-	0.39	J, K	BP	3	N, L, M, J, K	.800 (20.32)
-49470P02394-E-	0.39	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470Q02394-E-	0.39	K, M	BQ	5	N, L, M, J, K	.530 (13.46)
-49470P02474-E-	0.47	J, K	BP	1	N, L, M, J, K	.530 (13.46)
-49470P02474-E-	0.47	J, K	BP	2	A, B, D, C, F	.390 (9.91)
-49470Q02474-E-	0.47	K, M	BQ	5	N, L, M, J, K	.530 (13.46)
-49470P02564-E-	0.56	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02564-E-	0.56	J, K	BP	2	A, B, D, C, F	.530 (13.46)
-49470Q02564-E-	0.56	K, M	BQ	5	N, L, M, J, K	.660 (16.76)
-49470Q02564-E-	0.56	K, M	BQ	4	A, B, D, C, F	.390 (9.91)
-49470P02684-E-	0.68	J, K	BP	1	N, L, M, J, K	.660 (16.76)
-49470P02684-E-	0.68	J, K	BP	2	A, B, D, C, F	.530 (13.46)
-49470Q02684-E-	0.68	K, M	BQ	5	N, L, M, J, K	.800 (20.32)
-49470Q02684-E-	0.68	K, M	BQ	4	A, B, D, C, F	.390 (9.91)
-49470P02824-E-	0.82	J, K	BP	1	N, L, M, J, K	.800 (20.32)
-49470P02824-E-	0.82	J, K	BP	2	A, B, D, C, F	.660 (16.76)
-49470Q02824-E-	0.82	K, M	BQ	4	N, L, M, J, K	.530 (13.46)
-49470P02105-E-	1	J, K	BP	2	N, L, M, J, K	.660 (16.76)
-49470Q02105-E-	1	K, M	BQ	4	N, L, M, J, K	.530 (13.46)
-49470P02125-E-	1.2	J, K	BP	2	N, L, M, J, K	.800 (20.32)
-49470Q02125-E-	1.2	K, M	BQ	4	N, L, M, J, K	.530 (13.46)
-49470P02155-E-	1.5	J, K	BP	6	N, L, M, J, K	.530 (13.46)
-49470Q02155-E-	1.5	K, M	BQ	4	N, L, M, J, K	.660 (16.76)
-49470P02185-E-	1.8	J, K	BP	6	N, L, M, J, K	.660 (16.76)
-49470Q02185-E-	1.8	K, M	BQ	4	N, L, M, J, K	.800 (20.32)
-49470Q02185-E-	1.8	K, M	BQ	3	A, B, D, C, F	.390 (9.91)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Config.	Maximum A dimension inch (mm)
500 V						
-49470P02225-E-	2.2	J, K	BP	6	N, L, M, J, K	.800 (20.32)
-49470Q02225-E-	2.2	K, M	BQ	3	N, L, M, J, K	.390 (9.91)
-49470Q02275-E-	2.7	K, M	BQ	3	N, L, M, J, K	.530 (13.46)
-49470Q02335-E-	3.3	K, M	BQ	3	N, L, M, J, K	.530 (13.46)
-49470Q02395-E-	3.9	K, M	BQ	3	N, L, M, J, K	.530 (13.46)
-49470Q02475-E-	4.7	K, M	BQ	3	N, L, M, J, K	.660 (16.76)
-49470Q02565-E-	5.6	K, M	BQ	3	N, L, M, J, K	.800 (20.32)
-49470Q02565-E-	5.6	K, M	BQ	2	A, B, D, C, F	.390 (9.91)
-49470Q02685-E-	6.8	K, M	BQ	1	N, L, M, J, K	.660 (16.76)
-49470Q02685-E-	6.8	K, M	BQ	2	A, B, D, C, F	.390 (9.91)
-49470Q02825-E-	8.2	K, M	BQ	1	N, L, M, J, K	.660 (16.76)
-49470Q02825-E-	8.2	K, M	BQ	2	A, B, D, C, F	.530 (13.46)
-49470Q02106-E-	10	K, M	BQ	1	N, L, M, J, K	.660 (16.76)
-49470Q02106-E-	10	K, M	BQ	2	A, B, D, C, F	.530 (13.46)
-49470Q02126-E-	12	K, M	BQ	1	N, L, M, J, K	.800 (20.32)
-49470Q02126-E-	12	K, M	BQ	2	A, B, D, C, F	.660 (16.76)
-49470Q02156-E-	15	K, M	BQ	2	N, L, M, J, K	.800 (20.32)
-49470Q02186-E-	18	K, M	BQ	2	N, L, M, J, K	.800 (20.32)
-49470Q02226-E-	22	K, M	BQ	6	N, L, M, J, K	.530 (13.46)
-49470Q02276-E-	27	K, M	BQ	6	N, L, M, J, K	.530 (13.46)
-49470Q02336-E-	33	K, M	BQ	6	N, L, M, J, K	.660 (16.76)
-49470Q02396-E-	39	K, M	BQ	6	N, L, M, J, K	.800 (20.32)

1/ Complete PIN shall include additional symbols to indicate product level (M for B level, or T for T level), capacitance tolerance and configuration.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC
NASA - NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2010-012)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - MC
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.