INCH-POUND

MIL-P-70762 (AR)
AMENDMENT 1
30 September 1991

MILITARY SPECIFICATION

PROPELLANT, COMPOSITE, CAST, FOR USE IN SIMULATOR, MISSILE: SAGGER XM27

This Amendment forms a part of Military Specification MIL-P-70762 (AR) dated 12 April 1990, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.3.4 Delete ",890 ± 50 calories per gram" and substitute "850 ± 50 calories per gram."

PAGE 7

4.3.1 Delete paragraph 4.3.1 in its entirety and substitute the following paragraph:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of five (5) blocks of propellant for lots of multiple mixer loads or three (3) blocks of propellant for lots of a single mixer load. The sample propellant shall have been vacuum cast and cured in accordance with note two (2) of drawing 12576572. Each block shall be large enough for all first article tests of Section 4.3.2, but shall not be larger than 700 cubic inches. One of the five sample blocks shall be cast from the first mixer load and one from the last mixer load of the propellant lot. The three remaining sample blocks shall be randomly taken from the propellant mix if the lot contains more than one mixer load. If the lot is one mixer load, then one sample block shall be taken from the top, one from the bottom, and one from the middle. These samples shall be obtained from the first production lot which has been produced by the contractor using the same production process, procedures and equipment as will be used in fulfilling the contract. All material shall be obtained from the sources of supply as will be used in regular production."

DISTIRBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.4 Delete paragraph 4.4.4 in its entirety, and substitute with:

"4.4.4 Quality conformance sampling and testing. The quality conformance sample shall consist of five (5) blocks of propellant for lots of multiple mixer loads or three (3) blocks of propellant for lots of a single mixer load. These sample blocks shall have been vacuum cast and cured in accordance with note two (2) of drawing 12576572. Each sample block shall be large enough to do the testing required but not larger than 300 cubic inches. One of the five sample blocks shall be cast from the first mixer load and one from the last mixer load of propellant lot. The remaining three (3) sample blocks shall be randomly taken from the propellant lot if a lot contains more than one mixer load. If the lot contains only one mixer load, then one sample block shall be cast from the top, one from the bottom, and one from the middle of the lot. Each of the sample blocks shall be subjected to all the tests of Section 3 and Section 4 of this specification. If any of the samples do not meet the requirements of Section 3, the lot shall be rejected."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project: 1376-A420)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.