INCH-POUND

MIL-DTL-13777/2C
14 June 2011
SUPERSEDING
MIL-C-13777/2B
15 September 1969

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL 6, 7, 8, 9, 10, 12, 13, AND 15 CONDUCTORS

Inactive for new design after 1 July 2002.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-13777.

REQUIREMENTS:

Dimensions and configurations: See applicable figure and design data for the following cable types specified in table I. Design data is shown in table II.

TABLE I. Cable types.

060410S	070618	080766	100660	150885
060480	070730	080840	100870	150915S
060565	070823S	080918	101091	
061530	070930	090540	120620	
061805	071090	090675	120650S	
070590	S080625	100595	130685	

In any conflict between the design data and the applicable figure, the design data shall govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Design data.

	Design data			
Type designation	060410S		060480	060565
Figure number	1		2	2
Total wires	6		6	6
Number of conductors & AWG #	3/#18	3/#18S	6/#18	6/#16
Insulation				
Minimum average thickness	0.012”	0.012”	0.015”	0.015”
Spark test voltage	2000	2000	2000	2000
Inspection test voltage	1000	1000	1500	1500
Cabling				
Layer 1	Filler		Filler	Filler
Layer 2				
(a) Number of wires	3	3	6	6
(b) AWG #	#18	#18S	#18	#16
(c) Maximum lay				5.00”
Sheath				
Number of layers	1		1	1
Total thickness min	0.056”		0.070”	0.078”
Minimum OD cable	0.390”		0.460”	0.540”
Maximum OD cable	0.430”		0.500”	0.590”
	Design data			
Type designation	061530		061805	070590
Figure number	3		4	5
Total wires	6		6	7
Number of conductors & AWG #	4/#18	2/#0	3/#00	3/#5	7/#16
Insulation					
Minimum average thickness	0.015”	0.078”	0.075”	0.060”	0.020”
Spark test voltage	3000	7500	7500	3000	4000
Inspection test voltage	1500	2500	5000	1500	2000
Cabling					
Layer 1			Filler		Filler
(a) Number of wires	4	2			
(b) AWG #	#18	#0			
(c) Maximum lay					
Layer 2					
(a) Number of wires			6		7
(b) AWG #			3/#00	3/#5	#16
(c) Maximum lay			12.00		
Sheath					
Number of layers	2		2		1
Total thickness min	0.125”		0.188”		0.070”
Minimum OD cable	1.480”		1.760”		0.575”
Maximum OD cable	1.579”		1.850”		0.605”

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data				
Type designation	070618		070730		070823S
Figure number	5		6		7
Total wires	7		7		7
Number of conductors & AWG #	7/#18				
Insulation					
Minimum average thickness	0.015”	0.015”	0.020”		0.015”
Spark test voltage	3000	3000	4000		3000
Inspection test voltage	1500	1500	2000		1500
Cabling					
Layer 1	Filler		Filler		Filler
Layer 2					
(a) Number of wires	7	4	3		
(b) AWG #	#18	#16	#12		#18
(c) Maximum lay	4.00”				5.00”
Sheath					
Number of layers	1		2		2
Total thickness minimum	0.093”		0.098”		0.109”
Minimum OD cable	0.596”		0.710”		0.798
Maximum OD cable	0.640”		0.750”		0.848”
	Design data				
Type designation	070930	071090	S080625	080766	
Figure number	5	5	8	9	
Total wires	7	7	8	8	
Number of conductors & AWG #	7/#10	7/#8	8/#18	4/#16	4/#12
Insulation					
Minimum average thickness	0.020”	0.025”	0.015”	0.015”	0.020”
Spark test voltage	4000	4000	3000	3000	4000
Inspection test voltage	2000	2000	1500	1500	2000
Cabling					
Layer 1	Filler	Filler	Filler	Filler	
Layer 2					
(a) Number of wires	7	7	8	4	4
(b) AWG #	#10	#8	#18	#16	#12
(c) Maximum lay	6.00”	8.00”	2.50”		
Sheath					
Number of layers	2	2	1	1	
Total thickness minimum	0.125”	0.120”	0.070”	0.080”	
Minimum OD cable	0.912”	1.070”	0.610”	0.746”	
Maximum OD cable	0.948”	1.110”	0.640”	0.786”	
Maximum weight (lbs. /1000ft.)			245		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data				
Type designation	080840	080918		090540	090675
Figure number	9	10		11	11
Total wires	8	8		9	9
Number of conductors & AWG #	8#12	4/#18	4/#9	9/#20	9/#18
Insulation					
Minimum average thickness	0.020”	0.015”	0.040”	0.012”	0.015”
Spark test voltage	4000	3000	4000	3000	3000
Inspection test voltage	2000	1500	2000	1500	1500
Cabling					
Layer 1	Filler	Filler		Filler	Filler
Layer 2					
(a) Number of wires	8	4	4	9	9
(b) AWG #	#12	#18	#9	#20	#18
(c) Maximum lay				3.5”	3.10”
Sheath					
Number of layers	1	2		1	1
Total thickness minimum	0.070”	0.110”		0.063”	0.094”
Minimum OD cable	0.815”	0.888”		0.525”	0.660”
Maximum OD cable	0.865”	0.948”		0.555”	0.690”
Maximum weight (lbs. /1000ft.)					255
	Design data				
Type designation	100595	100660		100870	
Figure number	18	12		19	
Total wires	10	10		10	
Number of conductors & AWG #	10/#20	10/#18	6/#16		4/#12
Insulation					
Minimum average thickness	0.015”	0.015”	0.015”		0.020”
Spark test voltage	3000	3000	3000		4000
Inspection test voltage	1500	1500	1500		2000
Cabling					
Layer 1					
(a) Number of wires	2	2		2	
(b) AWG #	#20	#18		#16	
(c) Maximum lay					
Layer 2					
(a) Number of wires	8	8	4		4
(b) AWG #	#20	#18	#16		#12
(c) Maximum lay		4.00”			
Sheath					
Number of layers	1	2		2	
Total thickness minimum	0.070”	0.110”		0.098”	
Minimum OD cable	0.580”	0.645”		0.845”	
Maximum OD cable	0.610”	0.675”		0.895”	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.


	Design data					
Type designation	101091		120620	120650S		130685
Figure number	13		14	15		16
Total wires	10		12	12		13
Number of conductors & AWG #	6/#18	4/#9	12/#20	8/#20	4/#20S	13/#18
Insulation						
Minimum average thickness	0.015”	0.040”	0.015”	0.015”		0.015”
Spark test voltage	3000	4000	3000	3000		3000
Inspection test voltage	1500	2000	1500	1500		1500
Cabling						
Layer 1	Filler			Filler		Filler
(a) Number of wires			3			
(b) AWG #			#20			
(c) Maximum lay						
Layer 2						
(a) Number of wires	6	4	9	4		3
(b) AWG #	#18	#9	#20	#20S		#18
(c) Maximum lay						4.25”
Layer No. 3						
(a) Number of wires				8		10
(b) AWG #				#20		#18
(c) Maximum lay						6.00”
Sheath						
Number of layers	2		1	1		1
Total thickness minimum	0.155”		0.070”	0.056”		0.090”
Minimum OD cable	1.061”		0.605”	0.635”		0.670”
Maximum OD cable	1.121”		0.635”	0.665”		0.700”
Maximum weight (lbs. /1000ft.)						320

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data				
Type designation	150885		150915S		
Figure number	17		17		
Total wires	15		15		
Number of conductors & AWG #	12/#18	3/#12	7/#18	5/#18S	3/#12
Insulation					
Min average thickness	0.015”	0.020”	0.015”	0.015”	0.020”
Spark test voltage	3000	4000	3000	3000	4000
Inspection test voltage	1500	2000	1500	1500	2000
Cabling					
Layer 1	Filler		Filler		
Layer 2					
(a) Number of wires	3		3		
(b) AWG #	#12		#12		
(c) Maximum lay	3.00”		3.00”		
Layer 3					
(a) Number of wires	12			7	5
(b) AWG #	#18			#18	#18S
(c) Maximum lay	6.00”			6.00”	
Sheath					
Number of layers	2		2		
Total thickness minimum	0.125”		0.120”		
Minimum OD cable	0.870”		0.900”		
Maximum OD cable	0.900”		0.930”		
Maximum weight (lbs. /1000ft.)	490		557		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.



NOTE: Double circle indicate shielded construction.

FIGURE 1. Cable type (060410S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 2. Cable types (060480, 060565).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 3. Cable type (061530).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 4. Cable type (061805).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 5. Cable types (070590, 070930, 070618, 071090).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 6. Cable type (070730).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 7. Cable type (070823S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 8. Cable type (S080625).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 9. Cable types (080766, 080840).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 10. Cable type (080918).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 11. Cable types (090540, 090675).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 12. Cable type (100660).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 13. Cable type (101091).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.





FIGURE 14. Cable type (120620).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.



Note: Double circle indicates shielded construction.

FIGURE 15. Cable type (120650S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 16. Cable type (130685).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 17. Cable types (150885, 15091S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 18. Cable type (100595).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.




FIGURE 19. Cable type (100870).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Referenced documents. This document references MIL-DTL-13777.

CONCLUDING MATERIAL

Custodians:
Army – AR
Navy – SH
Air Force – 85
DLA - CC

Preparing activity:
DLA – CC

(Project 6145-2011-003)

Review activities:
Army – AT, CR, CR4, MI
Navy – EC, MC

Note: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information using the Assist Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:17Z
Check the source to verify that this is the current version before use.