INCH-POUND

MIL-DTL-13777/3B
w/AMENDMENT 1
4 April 2021
SUPERSEDING
MIL-DTL-13777/3B
11 May 2011

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL 16, 17, 18, 19, AND 20 CONDUCTORS

Inactive for new design after 1 July 2002.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-13777.

REQUIREMENTS:

Dimensions and configurations: See applicable figure and design data for the following cable types. The cable types are specified in table I. Design data information is specified in table II.

TABLE I. Cable types.

160636 S160878S 161065S	S161375S 170752 170874	180675 180848 S190875	S190965S 191110S 191140	200935

AMSC N/A

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.

TABLE II. Design data.

	Design data				
Type designation	160636	S160878S		161065S	
Figure number	1	2		3	
Total wires	16	16		16	
Number of conductors & AWG #	16/#20	8/#18	8/#18S	12/#18	4/#18 1/
Insulation					
Min average thickness	0.012”	0.015”		0.015”	
Spark test voltage	3000	3000		3000	
Inspection test voltage	1500	1500		1500	
Coaxial jacket insulation					
(a) Minimum average thickness				0.025”	
Cabling					
Layer 1	Filler	Filler		Filler	
Layer 2					
(a) Number of wires	5	6		4	
(b) AWG #	#20	#18		#18S	
(c) Maximum lay	2.0”	2.50”		3.75”	
Layer 3					
(a) Number of wires	11	2	8	12	
(b) AWG #	#20	#18	#18S	#18	
(c) Maximum lay	4.5”	5.00”		6.00”	
Sheath					
Number of layers	2	1		2	
Total thickness min.	0.109”	0.080”		0.100”	
Minimum OD cable	0.616”	0.863”		1.050”	
Maximum OD cable	0.656”	0.893”		1.080”	
Maximum weight (lbs./1000ft.)		538			

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data				
Type designation	S161375S			170752	170874
Figure number	4			5	5
Total wires	16			18	18
Number of conductors & AWG #	2/#18S	10/#18S	4/#6	18/#18	18/#16
Insulation					
Minimum average thickness	0.015”		0.060”	0.015”	0.015”
Spark test voltage	3000		7500	3000	3000
Inspection test voltage	1500		2500	1500	1500
Cabling					
Layer 1				Filler	Filler
(a) Number of wires	2				
(b) AWG #	#18[4/]				
(c) Maximum lay	3.00”				
Layer 2					
(a) Number of wires	5	5	4	6	6
(b) AWG #	#18[5/]	#18S	#6	#18	#16
(c) Maximum lay	8.00”				
Layer 3					
(a) Number of wires				[2/]	[3/]
(b) AWG #				#18	#16
(c) Maximum lay				5.00”	6.00”
Sheath					
Number of layers	2			2	2
Total thickness minimum	0.100”			0.110”	0.109”
Minimum OD cable	1.360”			0.737”	0.849”
Maximum OD cable	1.390”			0.767”	0.899”

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data			
Type designation	180675	180848		S190875
Figure number	6	7		8
Total wires	18	18		19
Number of conductors & AWG #	18/#20	14/#18	4/#16	19/#18
Insulation				
Minimum average thickness	0.015”	0.015”		0.015”
Spark test voltage	3000	3000		3000
Inspection test voltage	1500	1500		1500
Cabling				
Layer 1	Filler	Filler		Filler
Layer 2				
(a) Number of wires	6	2	4	7
(b) AWG #	#20	#18	#16	#18
(c) Maximum lay				
Layer 3				
(a) Number of wires	12	12		6/
(b) AWG #	#20	#18		#18
(c) Maximum lay				5.00”
Sheath				
Number of layers	1	2		1
Total thickness minimum	0.080”	0.098”		0.094”
Minimum OD cable	0.650”	0.823”		0.850”
Maximum OD cable	0.700”	0.873”		0.900”

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data			
Type designation	S190965S		191110S	
Figure number	9		8	
Total wires	19		19	
Number of conductors & AWG #	8/#18S	11/#18	7/#20	12/#20S
Insulation				
Minimum average thickness	0.015”		0.012”	
Spark test voltage	3000		3000	
Inspection test voltage	1500		1500	
Cabling				
Layer 1	Filler		Filler	
Layer 2				
(a) Number of wires	8		7	
(b) AWG #	#18		#20	
(c) Maximum lay	2.50”		4.0”	
Layer 3				
(a) Number of wires	8	3	12	
(b) AWG #	#18S	#18	#20S	
(c) Maximum lay	5.00”		8.0”	
Sheath				
Number of layers	1		2	
Total thickness min	0.080”		0.140”	
Minimum OD cable	0.950”		1.080”	
Maximum OD cable	0.980”		1.140”	

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.

TABLE II. Design data – Continued.

	Design data		
Type designation	191140	200935	
Figure number.	8	10	
Total wires	19	20	
Number of conductors & AWG #	19/#12	13/#18	7/#15
Insulation			
Minimum average thickness	0.020”	0.015”	
Spark test voltage	4000	3000	
Inspection test voltage	2000	1500	
Cabling			
Layer 1	Filler	Filler	
Layer 2			
(a) Number of wires	7	7	
(b) AWG #	#12	#15	
(c) Maximum lay		3.25”	
Layer 3			
(a) Number of wires	12	13	
(b) AWG #	#12	#18	
(c) Maximum lay		4.25”	
Sheath			
Number of layers	2	2	
Total thickness minimum	0.098”	0.125”	
Minimum OD cable	1.115”	0.920”	
Maximum OD cable	1.165”	0.950”	
Maximum weight (lbs/1000ft.)		540	

1/ Jacketed coaxial wires
2/ 11 & 1 filler
3/ 11 W/fillers
4/ Shield applied over twisted pair of AWG #18 – Maximum twist lay 3.00”
5/ Assembly with max lay of 3.00”
6/ 12 W/filler

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.





FIGURE 1. Cable type (160636).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.



NOTE: Double circle indicates shielded conductors.

FIGURE 2. Cable type (S160878S).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.



NOTE: Triple circle indicates coaxials with driven shields.

FIGURE 3. Cable type (161065S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.



NOTE: Double circle indicates shielded conductors.

FIGURE 4. Cable type (S161375S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.




FIGURE 5. Cable types (170752, 170874).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.




FIGURE 6. Cable type (180675).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.





FIGURE 7. Cable type (180848).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.



NOTE: *Double circle indicates shielded conductors.

FIGURE 8. Cable types (S190875, 191110S*, 191140).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.



NOTE: Double circle indicates shielded conductors.

FIGURE 9. Cable type (S190965S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.




FIGURE 10. Cable type (200935).

CONCLUDING MATERIAL

Custodians:
Army – AR
Navy – SH
Air Force – 85
DLA CC

Preparing activity:
DLA – CC

(Project 6145-2021-008)

Review activities:
Army – CE, CR, MI
Navy – MC
Air Force – 19

Note: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information using the Assist Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:18Z
Check the source to verify that this is the current version before use.