MILITARY SPECIFICATION

FILTER MATERIAL

This amendment forms a part of MIL-F-0013785B(EA), dated 24 November 1969, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Paragraph 1.2:

Delete: "Type 5 . . ."
"Type 6 . . ."
"Type 7 . . ."
"Type 15-N . . ."
"Type 6 and 7 differ in composition (See table 1)"

Add: "Type 5G - Glass-fiber-bearing (low resistance)"

PAGE 2

Paragraph 2.1:

Delete under Federal specifications:

"O-P-94 - Paper, Test; pH Indicator.
TT-W-572 - Wood Preservative, Water Repellent.
CCC-T-191 - Textile Test Methods."

Add under Federal specifications:

"NNN-T-1529 - Test Paper, Hydrogen Ion."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:19Z
Check the source to verify that this is the current version before use.

Delete the following:

"MILITARY"

"MIL-B-2427 - Boxes, Ammunition Packing; Wood Nailed."

Add under STANDARDS:

"FEDERAL"

"FED-STD-191 - Textile Test Methods"

Delete under DRAWINGS:

"D150-2-1 - Marking Diagram for Shipping Containers."

Paragraph 2.2: Delete in it's entirety.

PAGE 3

Paragraph 3.1, Table I:

	"Type	*Fibers
Add:	"**5G	g, r, f, h"
Delete:	"15-N	b (or g), f, h, r"
	"5	b, r, f, h"
	"6	b, e, f, h"
	"7	b, r, a (or i), h"
Delete:	"b	asbestos"
	"e	esparto"
Change:	"g	glass fibers (0.4 to 0.6 micron diameter)"
To:	"g	glass fibers"

Add: "**Use of 100 percent glass fibers is permitted" to the bottom of Table I.

Paragraph 3.1.1: Delete in it's entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:19Z
Check the source to verify that this is the current version before use.

PAGE 4

Paragraph 3.2: Delete Table II and subsequent note and rewrite as follows:

"TABLE II. Physical requirements

PROPERTY	REQUIREMENT		TEST METHOD
	TYPE 5G	TYPE 8	
Thickness (inch)	0.014 to 0.030	.033 to .043	4.2.4.1
Airflow resistance in MM H_2O (flowrate 32 L/min)	19 to 35	44 Max	4.2.4.2
DOP Smoke Penetration (percent) (flowrate - 32 L/Min)	0.33 Max	0.05 Max	4.2.4.2
Tensile strength (lb/in width)	---	2.0 min	4.2.4.3
Water Repellency, (inches)	15 min	20 min	4.2.4.4
*pH value	7.0 to 8.0	7.0 to 8.0	4.2.4.5
Mildew resistance (%)	No growth discernable to unaided eye	No growth discernable to unaided eye	4.2.4.6
Fold characteristics	No tears, breaks, or cracks	No tears, breaks, or cracks	4.2.4.7

*If type 5G consists of 100 percent glass fibers, the pH requirement shall be 4.0 to 8.0."

PAGE 5

Paragraph 4.2.2.2: Rewrite as follows:

"4.2.2.2 For tests. A test strip, three feet long, shall be taken from the free end of each slit roll across the entire width of the roll at a sufficient distance from the end to prevent inclusion of material damaged due to shipping and wrapping. Each test strip shall be identified with the roll from which it was taken."

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:19Z
Check the source to verify that this is the currentversion before use.

PAGE 6

Paragraph 4.2.4.2: Rewrite the following sentence: "A test pad shall consist of five layers for type 5 and one layer for types 6, 7, 8, and 15-N material" to read: "A test pad shall consist of five layers for type 5G and one layer for type 8 material."

PAGE 7

Paragraph 4.2.4.4: Rewrite the following sentence: "The test pads shall consist of seven layers for type 5 material and one layer of type 6, 7, 8, and 15-N material." to read: "The test pads shall consist of seven layers for type 5G material and one layer of type 8 material."

Paragraph 4.2.4.5: Rewrite as follows:

"4.2.4.5 pH value. The pH of each roll of paper shall be determined immediately after treatment for water repellancy as follows: Moisten a strip of class B, style 1, indicator paper conforming to NNN-T-1529, with distilled water. Place the moist indicator paper flat on the outer layer of the roll of paper. After 10 seconds, check the color of the indicator paper in accordance with NNN-T-1529."

Paragraph 4.2.4.6: Rewrite as follows:

"4.2.4.6 Mildew resistance. The mildew resistance of the filter material shall be determined using method 5750 of FED-STD-191 except the test specimens shall not be leached. Evaluation shall be qualitative."

Paragraph 4.2.4.7: Rewrite the following sentence: "A fold characteristic test shall be performed on specimens of type 6, 7, 8, and 15-N Filter Material." to read: "A fold characterisitc test shall be performed on types 5G and 8 Filter Material."

Section 5: Delete "PREPARATION OF DELIVERY" and substitute "PACKAGING" in lieu thereof.

Paragraph 5.1: Add new paragraph as follows:

"5.1 Unit packing. Unit packing shall be level A or B as follows (see 6.2)."

Paragraph 5.1: Change paragraph number to "5.1.1" and in first line in title, delete "Packaging." Paragraph title will be "5.1.1 Level A."

Paragraph 5.1.1: In first line, change paragraph number to "5.1.2"; in title, delete "Packaging."; and change "packaged" to "unit packed".

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:19Z
Check the source to verify that this is the currentversion before use.

PAGE 8

Paragraph 5.1.2: Delete in its entirety.

Paragraph 5.2: Add new paragraph "5.2" as follows:

"5.2 Packing. Packing shall be level A or B as follows (see 6.2)."

Paragraph 5.2: Change paragraph number to "5.2.1" and in first line of text, change "packaged" to "unit packed"; and in second line, add "Grade A" between "Style A" and "of PPP-B-621"; and lines 4 thru 8, delete text beginning with "The boxes . . ." and ending with ". . . of MIL-B-2427."

Paragraph 5.2.1: In line one, change paragraph number to "5.2.2"; in title, delete "Packing"; and change "packaged" to "unit packed"; and in second line, delete "no wood preservation will be applied" and substitute with "Grade B: boxes shall be used; and change "5.2" to "5.2.1".

Paragraph 5.2.2: Delete in its entirety.

Paragraph 5.3: In line two, change "packages" to "packs" and followed by "(5.1 and shipping containers (5.2)"; and line 3 and 4, delete sentence beginning with "shipping . . ."; and in line 5, change "5.2" to "5.2.1".

PAGE 9

Paragraph 6.1: Rewrite as follows:

"6.1 Intended use. This specification covers two types of filter material intended for use as the filter medium for removing particulates from influent air in gas masks and collective protectors."

Paragraph 6.2(b): Change "packaging" to "unit packing".

Paragraph 6.3: Delete in it's entirety and substitute the following:

"6.3 Interim specification. The revision of NNN-T-1529 to be used to determine pH is NNN-T-001529A, dated 22 June 1970."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A965

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:19Z
Check the source to verify that this is the current version before use.