NOT MEASUREMENT SENSITIVE

MIL-DTL-14639/48
20 December 1996
SUPERSEDING
MIL-I-3949/6D
20 March 1995

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, VICE ADMIRAL, NAVY AND LIEUTENANT GENERAL, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass or Nickel Silver

DASH NO.
-1: Regular Size
-2: Miniature Size

DIMENSIONS:
CIRCUMSCRIBED DIAMETER OF STAR:
-1: 1 inch (2.54 cm) (REF)
-2: 9/16 inch (1.43 cm) (REF)
WIDTH (Overall):
-1: 2-15/16 inches ± 1/64 inch (4.46 cm ± 0.04 cm)
-2: 1-11/16 inches ± 1/64 inch (4.29 cm ± 0.04 cm)
THICKNESS (Star Overall):
-1: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)
-2: 0.105 inch ± 0.005 inch (0.266 cm ± 0.012 cm)

FINISH: Nickel Plated, Rhodium Plated, Mirror-like Polished

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:11Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Stars shall be soldered to the connecting bar 3/4 inch ± 1/64 inch (1.91 cm ± 0.04 cm) on centers for Dash No. -1 and 9/16 inch ± 1/64 inch (1.43 cm ± 0.04 cm) on centers for Dash No. -2. Both Dash No. -1 and -2 may be made in one piece.

3. Connecting bar for Dash No. -1 shall be 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) wide by 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) thick. Connecting bar for Dash No. -2 shall be 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) wide by 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) thick.

4. The attaching device shall be prong and clutch type. Prongs shall be centered on the back of the outside stars.

5. Insignia may be made from sterling silver for commercial sale and if so, the thickness dimensions are for reference only. A minimum weight of 280 grains for Dash No. -1 and 75 grains for Dash No. -2 shall govern. The finish shall be as specified except the nickel plating shall not apply.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0874)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:11Z
Check the source to verify that this is the current version before use.