INCH-POUND
MIL-PRF-8805/92F
4 July 2024
SUPERSEDING
MIL-PRF-8805/92E
19 November 2018

PERFORMANCE SPECIFICATION SHEET

SWITCH ASSEMBLIES, SENSITIVE, LEVER LOCK, 5 AMPERES, UNSEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-PRF-8805.






FIGURE 1. Configurations and dimensions.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.
FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.





NOTES:

1. Dimensions are in inches. Unless otherwise specified, tolerances are ±.015 for three place decimals and ±.02 for two place decimals.
4. Design configuration optional provided specified dimensions are not exceeded.
5. Base switch number shall be permanently marked as shown.
6. Double turret type terminals shall accept two AN-20 or equivalent wires.
7. Alternative base metals and protective finishes, as approved by the qualifying activity, may be utilized for hexagon nut, lock washer and key washer material. Dimensions shall be in accordance with the referenced hardware specifications.
8. Details for MS25081-C4 may be found in MS25081, MS25082-C21 in MS25082, and MS35333-136 in NASM35333.

FIGURE 1. Configurations and dimensions - continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Enclosure design: 1 (Unsealed).

Temperature characteristic: 1 (-55°C to +85°C).

Shock type: M (100 g, test condition I, of MIL-STD-202-213).

Vibration grade: 1 (10 to 500 Hz).

Weight: See table III.

Operating characteristics:

Coincidence of operating and releasing points: All poles shall transfer within 10° of lever travel.

Locking arrangement: Positive locking shall be accomplished and shall prevent motion of the toggle lever until the locking mechanism is manually released.

Locking mechanism release: The force required to release the locking mechanism shall be 3 to 5 pounds.

Material:

Bracket and lever: Corrosion resistant steel.

Switch assembly: Basic switch shall be MS25085-2 (MIL-PRF-8805/2) switch listed on QPL-8805.

Contact resistance: Not applicable.

Dielectric withstanding voltage:

Sea level: 1,000 Vrms.

Altitude: 50,000 feet, 400 Vrms

In qualification inspection table after electrical endurance the dielectric withstanding voltage points of application between all unconnected terminals of the same pole are not applicable.

Mechanical endurance: 100,000 cycles.

Lever lock switches shall be tested for 100,000 cycles (at room ambient conditions) with the lever being pulled to its fully extended position and then permitted to return to its fully retracted position by spring action without operation of the switches. The cycling rate for this test shall be 60 cycles per minute maximum. In addition to this test, the lever lock switches shall receive a normal mechanical endurance test of 100,000 cycles of operation with the lever lock mechanism held in its fully extended position continuously throughout the test.

Electrical endurance: 25,000 cycles.

Electrical ratings: See table I.

Qualification inspection (group submission): See table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): See table III.

Circuit configuration: See table IV.

TABLE I. Electrical ratings.

	Sea level		50,000 feet
Load	28 V dc	115 V ac, 60 Hz	28 V dc
	amperes	amperes	amperes
Resistive	5	5	5
Inductive	3	5	2.5
Lamp	2.4	1.5	2.4

TABLE II. Qualification inspection group submission.

Examination or test	Basic switch assembly	Additional sample units for combined submission	Extent of approval
Group I. Visual and mechanical examination Operating characteristics	M8805/92-002 (12 sample units)	(2 sample units each) M8805/92-005 M8805/92-016 M8805/92-019 (tested to group I only)	All
Group II. Strength of actuating means (2 sample units only) Strength of mounting bushing (2 sample units only) Thermal shock Vibration Shock Operating characteristics Dielectric withstanding voltage Visual and mechanical examination	(4 sample units from group I)	- - - - -	
Group III. Salt spray (corrosion) Visual and mechanical examination	(2 sample units from group I)	- - - -	
Group IV. Low temperature operation (2 sample units) Mechanical endurance at room ambient conditions (2 units) Operating characteristics Dielectric withstanding voltage Visual and mechanical examination	(4 sample units from group I)	- - - -	
Group V. Electrical endurance Inductive load, dc	(2 sample units from group I)	- - - -	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.

TABLE III. PIN's and characteristics.

PIN M8805/92-	Switch configuration number (See figure I)	Locking combination	Table IV circuit configuration	Switch action			Weight lb. max
				Opposite keyway	Center	Keyway	
001	1	D	1	Main	None	Main	.075
002	3	D	4				.100
003		F					.100
004		G					.100
005	1	E	2	Mom	Main	Mom	.075
006		A		Main	Main	Main	.075
007		D					.075
008		E					.075
009		F					.075
010		G					.075
011		J					.075
012		K					.075
013		L					.075
014		M					.075
015		N					.075
016		B		Mom	Main	Main	.075
017		E					.075
018		P					.075
019	2	A	3	Main	Main	Main	.090

TABLE IV. Circuit configuration.

Circuit configuration	Switch pole number	Circuit closed with the toggle lever in		
		Opposite keyway side	Center	Keyway side
1	1	C-NC	None	C-NO
	2	C-NC		C-NO
2	1	C-NO	C-NC	C-NC
	2	C-NC	C-NC	C-NO
3	1	C-NO	C-NC	C-NC
	2	C-NC	C-NC	C-NO
	3	C-NO	C-NC	C-NC
4	1	C-NC	None	C-NO
	2	C-NC		C-NO
	3	C-NC		C-NO
	4	C-NC		C-NO

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-8805, this document references the following:

MIL-PRF-8805/2
MIL-STD-202-213
MS25081
MS25082
NASM35333

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA - CC

Review activities:
Army – AR, MI
Navy – AS, MC, OS
Air Force – 19

Preparing activity:
DLA - CC

(Project 5930-2024-040)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:18Z
Check the source to verify that this is the current version before use.