MILITARY
SPECIFICATION

MIL-C-12813A(SigC)
Amendment No. 5
29 July 1959
Superseding
Amendment No. 4
26 Apr 1956

# CRYSTAL UNITS, QUARTZ
# WIRE-MOUNTED, METAL PLATED

1. Paragraph 1.2 Classification.- Change "CR-2/U" to "CR-2D/U" in both places. Change "CR-3/U" to "CR-3C/U". Change "CR-4/u" to "CR-4C/U".

2. Paragraph 2.1: Under STANDARDS, MILITARY, add:

MIL-STD-202 Test Methods for Electronic and Electric Component Parts.

Under DRAWINGS, SIGNAL CORPS, delete all reference to SC-D-8260 and SC-D-8261.

3. Paragraph 3.1.1(b) Selection.- Last two lines, complete sentence with a period after "document", and add the following sentence after it: "Optional deviations from the detailed document, if described herein, may be exercised by the contractor."

4. Paragraph 3.2.4 Preproduction inspection.- Table I: Delete "Frequency Shift" and associated paragraph references.

5. Paragraph 3.5 Quartz crystal element.- Delete and substitute:

"3.5 Design and construction.-

3.5.1 Quartz crystal element.- The quartz crystal element shall be wire-mounted and shall have its major faces plated with a metallic film.

3.5.2 Crystal holder.- Crystal Holder HC-17/U shall be used for each crystal unit. The physical dimensions and materials shall conform to Signal Corps Drawing List SC-DL-107568 and subsidiary drawings, and all requirements and tests of Specification MIL-H-10056 shall be met. The length and width of the crystal unit after solder sealing shall not exceed the maximum length and width specified for the unassembled crystal holder by more than 0.007 inches in each case."

6. Paragraph 3.7.2 Frequency shift.- Delete in its entirety.

7. Paragraph 3.16 Crystal Unit CR-2/U (200 KC).- Change "CR-2/U" to "CR-2D/U".

8. Paragraph 3.17 Crystal Unit CR-2/U (500 KC).- Change "CR-2/U" to "CR-2D/U".

9. Paragraph 3.18 Crystal Unit CR-3/U.- Change "CR-3/U" to "CR-3C/U".

10. Paragraph 3.18.5 Permissible tolerances for frequency, frequency drift, frequency shift, and activity. In last line of table, change "Maximum" to "Minimum". Delete "Frequency Shift" column.

11. Paragraph 3.19 Crystal Unit CR-4/U.- Change "CR-4/U" to "CR-4C/U".

12. Paragraph 3.19.5 Permissible tolerances for frequency, frequency drift, frequency shift, and activity.- Delete "Frequency Shift" column.



FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

13. Paragraph 3.20.6 Permissible tolerances for frequency drift, frequency shift and activity.- Delete "Frequency Shift" column.

14. Paragraph 4.1 Inspection, general.- Add new sentence at end of paragraph:

"Unless otherwise specified herein, all measurements and tests shall be made at 25° ± 10° C., ambient atmospheric pressure, and ambient humidity. (See also 4.3.3 and 4.4.3)".

15. Paragraph 4.1.1.3 Test routine.- Table II: Delete "Frequency Shift" and associated paragraph references.

16. Paragraphs 4.3.3 and 4.4.3 Determination of change.- Change the latter part of each paragraph to the following: "....has reached thermal equilibrium, and that the ambient temperature in which the second measurement is made is within ±2°C of the temperature in which the first measurement was made. (See also 4.1.)"

17. Paragraph 4.3.5 Frequency shift.- Delete in its entirety.

18. Paragraph 4.7 Immersion.- Change the last sentence to the following: "At the end of this test, the d-c resistance shall be measured between the pins of the unit and also between each pin and any other external metal part of the unit, using a d-c test voltage of 50 to 100 volts, and the frequency and activity shall be measured using the methods specified in 4.3.1 and 4.4.1."

19. Paragraph 4.10 Corrosion test.- Delete and replace with:

"4.10 Corrosion test.- The crystal unit shall be tested in accordance with Method 101, test condition B, of Standard MIL-STD-202. After this test the unit shall be examined for compliance with 3.12."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.