INCH-POUND

MIL-DTL-12779D
8 July 2014
SUPERSEDING
MIL-C-12779C
10 January 1969

DETAIL SPECIFICATION

CARTRIDGE, CALIBER .45, BLANK, LINE, THROWING – M32

This specification is approved for use by all Departments and Agencies of the Department of Defense within the distribution limitations noted at the bottom of the page.

Reinstated after 11 October 2013 and may be used for new and existing designs and acquisitions.

1. SCOPE

1.1 Scope. This specification covers the requirements and verification methods for Cartridge, Caliber .45, Blank, Line, Throwing – M32 for use in the Caliber .45 Line Throwing Device.

Comments, suggestions, or questions on this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: RDAR-EIQ-SE, Picatinny Arsenal, New Jersey 07806-5000 or e-mailed to usarmy.picatinny.ardec.list.ardec-stdzn-branch@mail.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT D. Distribution authorized to the Department of Defense and U.S. DoD contractors only to safeguard critical technology as determined on 02 June 2009. Other requests for this document shall be referred to the Office of the Project Manager for Maneuver Ammunition Systems, ATTN: SFAE-AMO-MAS, Picatinny Arsenal, NJ 07806-5000.

WARNING - This document contains technical data whose export is restricted by the Arms Export Control Act (Title 22, U.S.C., Sec 2751, et. seq.) or the Export Administrative Act of 1979, as amended, Title 50, U.S.C., App. 2401 et. seq. Violations of these export laws are subject to severe criminal penalties. Disseminate in accordance with provisions of DoD Directive 5230.25.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-636	-	Visual Inspection Standards for Small Arms Ammunition through Caliber .50
MIL-STD-1168	-	Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916	-	DoD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at https://quicksearch.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

7553068	-	Cartridge, Caliber .45, Blank, Line Throwing, M32
7643674	-	Classification of Cartridge Case Defects
10524075	-	Case

(Copies of these drawings are available from U.S. Army ARDEC, ATTN: RDAR-EIS-PE, Picatinny Arsenal, NJ 07806-5000, or email usarmy.picatinny.ardec.list.drawing-request-help-desk@mail.mil.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) PUBLICATIONS

SCATP-45	-	Ammunition Ballistic Acceptance Test Methods, Test Procedures for Caliber .45 Cartridges

(Application for copies should be addressed to Quality Engineering and System Assurance, U.S. Army, ARDEC, Picatinny Arsenal, NJ 07806-5000, ATTN: RDAR-EIQ-MD or email usarmy.picatinny.ardec.list.qesa-EIQ-MD@mail.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample of the M32 cartridges shall be subjected to first article inspection in accordance with 4.3.

3.2 Conformance inspection. A sample of the M32 cartridges shall be subjected to conformance inspection in accordance with 4.4.

3.3 Cartridge. The cartridge shall comply with all the requirements specified on dwg. 7553068.

3.4 Waterproof test. The cartridges, after submersion under one inch head of water for 24 hours, shall be conditioned at 70° ± 2° Fahrenheit (F), and fired at an angular elevation of 30 degrees for range with line-carrying rod and the line attached. The minimum acceptable range shall be 75 yards from the muzzle of the weapon.

3.5 Primer sensitivity. The energy imparted by a steel ball 1.94 ± .02 ounces falling not greater than 18 inches (critical height plus five times standard deviation) shall cause initiation of the primer. The energy imparted by a steel ball 1.94 ± .02 ounces falling not less than 3 inches (critical height minus two time standard deviation) shall not cause initiation of the primer.

3.6 Residual stress. The brass cartridge cases shall not split when subjected to one percent (%) mercurous nitrate solution for 15 minutes.

3.7 Velocity. The maximum individual velocity of the rod with line attached, when imparted by the cartridge, and conditioned at 0° ± 2°F, 70° ± 2°F and 120° ± 2°F, shall not exceed 227 feet per second (fps) at 6 feet from the muzzle of the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

3.8 Chamber pressure. The average chamber pressure of the sample cartridge, conditioned at 0° ± 2°F, 70° ± 2°F, and 120° ± 2°F, shall be not greater than 20,000 pounds per square inch (psi). The average chamber pressure plus 2.36 times the standard deviations nor the chamber pressure of an individual sample cartridge shall be not greater than 20,000 psi.

3.9 Range. The cartridges conditioned at 0° ± 2°F, 70° ± 2°F, and 120° ± 2°F, shall project the line-carrying rod with its trailing line a minimum of 75 yards from the muzzle of the weapon when fired at an angular elevation of 30 degrees.

3.10 Function and casualty. The cartridges shall function without casualty when tested for compliance with paragraphs 3.4, 3.7, 3.8, and 3.9.

3.11 Workmanship. The cartridge shall be free of corrosion, stains, discolorations, dirt, oil and smears of lacquer. The cleaning method used shall not be injurious to any part, nor shall be parts be contaminated by any cleaning agent.

3.12 Ammunition lot numbering. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement/verification cross-reference matrix.

Method of Verification 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test		Classes of Verification A – First article B – Conformance						
Section 3 Requirement	Description	Verification Methods				Verification Class		Section 4 Verification Method
		1	2	3	4	A	B	
3.1	First article			X	X	X		4.3, Table II, Table III, Table IV, Table V, Table VI
3.2	Conformance inspection			X	X		X	4.4, Table IV, Table V, Table VI
3.3	Cartridges			X	X	X	X	4.4.2, Table III, Table IV, Table V, Table VI
3.4	Waterproof			X	X	X	X	4.5.1
3.5	Primer sensitivity				X	X	X	4.5.2
3.6	Residual stress			X	X	X	X	4.5.3
3.7	Velocity				X	X	X	4.5.4
3.8	Chamber pressure				X	X	X	4.5.5
3.9	Range				X	X	X	4.5.6
3.10	Function and casualty				X	X	X	4.5.7
3.11	Workmanship			X		X	X	4.5.8
3.12	Ammunition lot numbering			X		X	X	4.5.9

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Conformance inspection (see 4.4)

4.2 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in section 4.5.

4.3 First article. When specified, a sample of the cartridge assembly and subcomponents shall be subjected to first article verification in accordance with Table II, Table III, Table IV, Table V, Table VI and 4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

4.3.1 First article quantity. The first article sample shall consist of the following item in the sample quantity as indicated in Table II.

TABLE II. First article quantity.

Part Description	Drawings	Quantity
Cartridge, Caliber .45, Blank, Line, Throwing – M32	7553068	500
Empty Primed Cartridge cases (no propellant)	7553068	800
Case	10524075	5 1/
Notes: 1/ Per station per machine. Each station of each machine is considered a separate manufacturing process.		

4.3.2 First article rejection. If any assembly, component or test specimen fails to comply with requirements, the first article sample shall be rejected (see 6.7).

4.4 Conformance inspection.

4.4.1 Inspection lot formation. Lot formation shall be in accordance with MIL-STD-1168. Unless otherwise specified, component parts shall be homogenous, inspected and tested. The cartridge lot shall contain:

a. Cartridge cases from one unchanged process and from one manufacturer
b. Primers from one lot interfix number and from one manufacturer
c. Propellant from no more than two lot numbers and from one manufacturer

4.4.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for critical, major and minor characteristics are defined in MIL-STD-1916. Unless specified otherwise, Inspection Level VII in addition to 100% inspection shall be used for all characteristics defined as Critical, Inspection Level IV shall be used for all characteristics defined as Majors and Inspection Level II for all Minor characteristics.

b. Inspection. Conformance inspection shall be performed in accordance with Table IV, Table V, and Table VI. For all conformance inspections the same sample specimen may be used for all non-destructive examinations or tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

TABLE III. First article inspection.

Examination or Test	Conformance Criteria			Requirement Paragraph	Inspection Method Reference
	Qty	Acc	Rej		
Case (dwg. 10524075)	5 2/	0	1	3.3, 3.11	Visual/Gage 3/
Cartridge, Caliber .45, Blank, Line, Throwing – M32					
Examination for defects				3.3, 3.11	Table V
Critical defect	500	0	1		
Major defect	192	0	1		1/
Minor defect	40	0	1		1/

Notes:

1/ For first article only, inspection sampling shall be tightened to VL V for majors and VL III for minors in accordance with MIL-STD-1916. A random sample of 192 cartridges for major defects shall be selected from the 500 cartridges. The first 40 shall be inspected for major and minor defects and the rest shall be inspected for major defects.

2/ Per station per machine. Each station of each machine is considered a separate manufacturing process.

3/ To be inspected for all drawing requirements using standard measuring and test equipment (except for workmanship which is inspected for visually).

TABLE IV. First article and conformance tests.

Test	Conformance Criteria			Requirement Paragraph	Inspection Method Reference
	Qty	Acc	Rej		
Waterproof	20	1/		3.3	4.5.1
Primer sensitivity	800	2/		3.5	4.5.2
Residual stress (mercurous nitrate)	50	1/		3.6	4.5.3
Velocity					4.5.4
70° ± 2°F	20	3/ 5/		3.7	
0° ± 2°F	20	3/ 5/		3.7	
120° ± 2°F	20	3/ 5/		3.7	
Chamber pressure					4.5.5
70° ± 2°F	20	4/ 5/		3.8	
0° ± 2°F	20	4/ 5/		3.8	
120° ± 2°F	20	4/ 5/		3.8	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

TABLE IV. First article and conformance tests – Continued.

Test	Conformance Criteria			Requirement Paragraph	Inspection Method Reference
	Qty	Acc	Rej		
Range					4.5.6
70° ± 2°F	20	3/		3.9	
0° ± 2°F	20	3/		3.9	
120° ± 2°F	20	3/		3.9	
Function and casualty Cal. .45 Line Throwing Gun, Mark 1, Model 1		6/		3.10	4.5.7

Notes:

1/ Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

2/ Prior to assembly into cartridges, a sample of primers from each primer lot shall be tested for sensitivity. The test sample shall consist of the number of primers required for performance of a complete run-down test wherein 50 primers are tested at each height. If the average critical height ($\overline{H}$) plus five standard deviations (5 sigma) exceeds 18 inches, or if the average critical height ($\overline{H}$) minus two standard deviations (2 sigma) is less than 3 inches, the lot of primers shall be rejected subject to performance of a second complete run-down test wherein 100 primers are tested at each height. Failure of the second sample to comply with the above criteria shall be cause for rejection of the lot of primers.

3/ Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample, consisting of double the quantity of cartridges used in the first test for the temperature at which the failure occurred, may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

4/ Failure of the cartridges in any sample to comply shall be cause for rejection of the lot, subject to testing of a second sample consisting of double the quantity of cartridges used in the first test for the temperature or temperatures at which the failure occurred. Failure of the cartridges of the second sample shall be cause for rejection of the lot.

5/ Velocity and pressure are obtained simultaneously.

6/ Observation for function and casualty defects shall be made during the firing of all ballistic tests. The lot shall be rejected if firing defects exceed the acceptance number in Table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

TABLE V. Defect inspections.

Classification.	Examination or Test 1/	Conformance Criteria 2/	Requirement Paragraph	Inspection Method Reference
Critical				
1	No crimp or insufficient crimp 4/	100% & Level VII	3.3	Gage
2	Cartridge type, incorrect 5/ (3)	100% & Level VII	3.3	Visual/Gage
Major				
101	No primer (25)	Level IV	3.3	Visual
102	Cocked primer (26)	Level IV	3.3	Visual
103	Inverted primer (27)	Level IV	3.3	Visual
104	Cartridge type, incorrect 5/ (3)	Level IV	3.3	Visual/Gage
105	Corroded or stained, if etched (cartridge) (2)	Level IV	3.3	Visual
106	Split case – below top of wad (6)	Level IV	3.3	Visual
107	Perforated case – Below top of wad (7)	Level IV	3.3	Visual
108	Draw scratch (case) (8)	Level IV	3.3	Visual
109	Scratch (case) (9)	Level IV	3.3	Visual
110	Beveled underside of head (case) (10)	Level IV	3.3	Visual
111	Scaly metal (case) (11)	Level IV	3.3	Visual
112	No chamfer of head (rim) (case) (12)	Level IV	3.3	Visual
113	Loose primer	Level IV	3.3	Visual
114	Missing wad(s)	Level IV	3.3	Visual
115	Opening between wad and case wall	Level IV	3.3	Visual
116	Dent (case) (28)	Level IV	3.3	Visual
117	Cartridge profile failure	Level IV	3.3	Gage
118	Diameter of head (rim) max	Level IV	3.3	Gage
119	Thickness of head (rim) max	Level IV	3.3	Gage
120	Depth of primer	Level IV	3.3	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

TABLE V. Defect inspections – Continued.

Classification.	Examination or Test 1/	Conformance Criteria 2/	Requirement Paragraph	Inspection Method Reference
Minor				
201	Discolored, dirty, oily, smeared (cartridge) (1)	Level II	3.3	Visual
202	Round head (case) (4)	Level II	3.3	Visual
203	Dent (case) (5)	Level II	3.3	Visual
204	Split case - between mouth and top of wad (6)	Level II	3.3	Visual
205	Perforated case – Between mouth and top of wad (7)	Level II	3.3	Visual
206	Draw scratch (case) (8)	Level II	3.3	Visual
207	Scratch (9)	Level II	3.3	Visual
208	Beveled underside of head (case) (10)	Level II	3.3	Visual
209	Scaly metal (case) (11)	Level II	3.3	Visual
210	No chamfer on head (rim) (12)	Level II	3.3	Visual
211	Wrinkle (case) (13)	Level II	3.3	Visual
212	Bulge (case) (14)	Level II	3.3	Visual
213	Illegible , missing, or incorrect head stamp (15)	Level II	3.3	Visual
214	Defective head (case) (16)	Level II	3.3	Visual
215	Nicked or dented primer (28)	Level II	3.3	Visual
216	No waterproofing material (primer pocket joint) (29)	Level II	3.3	Visual
217	Fold case	Level II	3.3	Visual
218	Wad and joint between case and wad not completely covered by lacquer	Level II	3.3	Visual
219	Workmanship (see 3.11 and 4.5.8) 3/	Level II	3.3	Visual

Notes:

1/ Numbers in parenthesis after defects description refer to visual standards for defects 1 through 29 in MIL-STD-636 (NATO, 9mm and Caliber .45 Section). While no photographs of blank line throwing cartridges are included in this Standard, the cartridge case defects illustrated in Caliber .45 Section can be used. In the event of conflict between Table V of this specification and MIL-STD-636, as to defect classification, the classification specified in Table V shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

TABLE V. Defect inspections – Continued.

2/ Level II, Level IV, or Level VII refer to verification level II, verification level IV, or verification level VII respectively of sampling plans in MIL-STD-1916. 3/ Defects other than those listed in MIL-STD-636 (NATO, 9mm and Caliber .45 Section). 4/ The crimp shall be considered to be missing or insufficient when the open mouth diameter of the cartridge case exceeds 0.385 inch. 5/ Inspection for incorrect cartridge type shall be performed during or immediately prior to the packaging operation, which is before cartridge lot acceptance. Occurrence of any type other than blank, dummy or inert shall be classified as a critical defect. Occurrence of a dummy or inert shall be classified as a major defect. If a defect is found at 100% inspection, which is during or immediately prior to the packaging operation inspection, the incorrect cartridge type shall be replaced with a correct cartridge type. For verification level inspection, a VL VII sample shall be selected at random from the lot. From this VL VII sample, a VL IV sample shall be selected at random. A VL IV sample shall be inspected for major and critical incorrect cartridge type defects. The cartridges that remain of the initial VL VII sample after the VL IV sample is selected shall be inspected for critical incorrect cartridge type defects only. If a critical defect is found during VL VII inspection, the lot shall be withheld from acceptance and approved procedures for product disposition shall be followed. If a major defect is found during VL IV inspection, the incorrect cartridge type shall be replaced with a correct cartridge type and the entire lot shall be subjected to a subsequent 100% inspection. During the subsequent inspection, any incorrect cartridge type found shall be replaced with a correct cartridge type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

Table VI. Function and casualty firing defects criteria.

Defects 5/	First Article		Lot Acceptance		Classification
	Acc	Rej	First Sample	Cumulative Sample	
1. Misfire 4/					
a. No vent hole, or obstruction in vent hole 1/	0	1	0	-	Major
b. Other	0	1	0	1	Major
2. Primer defects					
a. Perforation in firing pin indent in primer cup 1/	0	1	0	-	Major
b. Escape of gas around primer cup 2/	1	2	2	3	Major
c. Primer remains in pocket but is physically loose 1/	0	1	0	-	Major
d. Blown primer 1/	0	1	0	-	Major
e. Primer falls out of pocket on extraction 1/	0	1	0	-	Major
3. Case casualties					
a. Longitudinal split 3/					
1. Mouth or body (I or J)	1	2	2	3	Major
2. Body (K) 1/	0	1	0	-	Major
3. To head (L) 1/	0	1	0	-	Major
4. Through head (M) 1/	0	1	0	-	Major
b. Circumferential rupture 3/					
1. Partial (J)	0	1	0	1	Major
2. Partial, body (K)	0	1	0	1	Major
3. Partial, head (L) 1/	0	1	0	-	Major
4. Complete 1/	0	1	0	-	Major
4. Failure to extract	0	1	0	1	Major
5. Weapon stoppage 6/	0	1	0	1	Major

Notes:

1/ No second sample permitted. Lot shall be rejected if one or more failure occurs.

2/ Gas escapes around more than fifty percent of periphery of cup.

3/ For location of defects indicated by letters in parentheses, see dwg. 7643674.

4/ Each cartridge that misfires shall be disassembled and examined for presence of vent hole in primer pocket or any obstruction, in the vent hole area of primer pocket that can be assignable as the cause for misfire. If vent hole is missing or obstructed, the lot shall be rejected with no second sample permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

Table VI. Function and casualty firing defects criteria – Continued.

5/ For any ballistic test except function and casualty, where the occurrence of a firing defect prevents the obtaining of a valid result for the characteristic being tested the following shall apply. The defect shall be observed under the appropriate function and casualty defect category and included in the defect count for determining acceptance or rejection in accordance with Table III and/or Table IV. The particular test for which the round was fired shall not be penalized. A replacement round shall be fired to obtain the data for the characteristic being tested. 6/ All stoppages attributable to the ammunition, with the exception of misfire, complete rupture and failure to extract, observed in all tests shall be included.

4.5 Test methods and procedures.

4.5.1 Waterproof. The test shall be conducted in accordance with SCATP-45 Chapter 2 Section 6, Waterproof Test Procedure. The test sample shall be conditioned at 70°F ± 2°F, for not less than two hours and fired at that temperature.

4.5.2 Primer sensitivity. The test shall be conducted in accordance with SCATP-45 Chapter 3 Section 1, Primer Sensitivity Test Procedure. (Run-down Test)

4.5.3 Residual stress (Mercurous nitrate). The test shall be conducted in accordance with SCATP-45 Chapter 1 Section 6, Mercurous Nitrate Test Procedure.

4.5.4 Velocity. The tests shall be conducted in accordance with SCATP-45 Chapter 2 Section 5, Velocity and Chamber Pressure Test Procedure, and shall be conducted in conjunction with the chamber pressure tests, except that line shall be attached. The test sample shall be conditioned at 70°F ± 2°F, for not less than two hours and fired at that temperature. The test sample shall be conditioned at 0°F ± 2°F and 120°F ± 2°F for 4 hours and shall be fired at that temperature. The weapon in which these tests are fired shall be at room temperature.

4.5.5 Chamber pressure. The tests shall be conducted in accordance with SCATP-45 Chapter 2 Section 5, Velocity and Chamber Pressure Test Procedure, except that line shall be attached. The test sample shall be conditioned at 70°F ± 2°F, for not less than two hours and fired at that temperature. The test sample shall be conditioned at 0°F ± 2°F and 120°F ± 2°F for 4 hours and shall be fired at that temperature. The weapon in which these tests are fired shall be at room temperature.

4.5.6 Range. The test shall be conducted in accordance with SCATP-45 Chapter 2 Section 3, Range Test Procedure. The test sample shall be conditioned at 70°F ± 2°F, for not less than two hours and fired at that temperature. The test sample shall be conditioned at 0°F ± 2°F and 120°F ± 2°F for 4 hours and shall be fired at that temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

4.5.7 Function and casualty. The test shall be conducted in accordance with SCATP-45 Chapter 2 Section 1, Function and Casualty Test Procedure. The test shall be performed in conjunction with the velocity and chamber pressure, waterproof, and range tests.

4.5.8 Workmanship. Visually verify that all parts and assemblies meet the requirements of 3.11.

4.5.9 Ammunition lot numbering. Visually verify that an ammunition lot number has been applied to each lot as described in MIL-STD-1168.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The cartridge covered by this specification is intended for use in .45 caliber military device making this cartridge military unique.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Type and level of packing for the cartridge.
c. Provisions for the submission of Inspection Equipment Designs (see 6.3)
d. Requirements for submissions of first article sample (see 3.1)
e. Provisions for submission of acceptance inspection results for each lot of ammunition presented to the Government (see 6.4)
f. Applicable national stock number

6.3 Submission of inspection equipment designs for approval. Submit equipment designs as required to Commander, U.S. Army ARDEC, ATTN: RDAR-EIQ-MD, Picatinny Arsenal, NJ 07806-5001. Request letter of submittal should state the contractor, contract number, specification number, item nomenclature and classification of defects or tests. This address will be specified on the Contract Data Requirements List in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

6.4 Submission of test data. In addition to the normal distribution of records, when the cartridge is procured by the US ARDEC, one (1) copy of all ballistic data and the ammunition data card for each lot should be forwarded to: Commander, ARDEC, ATTN: RDAR-EIQ-MD, Picatinny Arsenal, NJ 07806-5000.

6.5 Hazard notice. The cartridge described herein and some of its components are flammable and explosive and consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

6.6 Shipping. When cartridges from more than one lot are shipped at one time, each lot should be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6.7 First article rejection. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

6.8 Rationale for critical defects.

Critical Defect	Rationale
Inspection Defect: Cartridge type, incorrect	Occurrence of any incorrect type (live ammunition) mixed with blank or dummy rounds could cause death or injury to user during training/ceremony/weapon demonstration.
Inspection Defect: No crimp, insufficient crimp	Occurrence of defect can cause the rod to wedge into the cartridge which in turn could cause a high pressure build up causing the gas escapement to the rear of the cartridge. Gas escapement to the rear could cause damage to the weapon or create catastrophic failure of the weapon and/or high velocity hot gas, when vented, would be directed towards the operator's face. Furthermore, due to damage weapon the ARMY vessels will not be able to deploy or support ongoing mission.

6.9 Subject term (key word) listing.

Function and Casualty Tests
Small Arms Ammunition
Munitions

6.10 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army – AR
Navy – OS
Air Force – 99

Review Activity:
Army – AV, MI, MR,
Navy – AS, MC, SH,
Air Force – 70

Preparing activity:
Army – AR
(Project 1305-2014-055)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:20Z
Check the source to verify that this is the current version before use.