MIL-F-12774D (PA)
22 May 1975
Superseding
MIL-F-12774C (MU)
14 February 1969

FUZE, MINE, COMBINATION, M605
LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of fuze designated as Fuze, Mine, Combination, M605.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-223 - Powder, Black
MIL-C-13739 - Composition, Delay
MIL-P-20444 - Primer, Percussion, M42, Loading, Assembling and Packing
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

7548179 - Box, Packing, Ammunition for Mine, APERS, M16A1 or M16A2 (with Fuze, Mine, Combination, M605)
7548190 - Ammunition, Container, Metal for Fuze, Mine, Combination, M605, Assembly, Details, Packing and Marking
7548284 - Fuze, Mine, Combination, M605 Assembly
8863609 - Support, Packing, Ammunition for Mine, APERS, M16A1 or M16A2 (with Fuze, Mine, Combination, M605

INSPECTION EQUIPMENT DRAWINGS

8792739 - Functioning test fixture
8796343 - Propellant charge

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS (see 6.7)

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Fuze assembly. - The mine fuze assembly shall comply with all requirements specified on Drawing (dwg.) 7548284 and with all requirements specified in applicable specifications.

3.3 Moisture content of black powder. - The moisture content of the black powder at the time of loading shall not exceed the amount specified in MIL-P-223.

3.4 Moisture content of delay composition. - The moisture content of the delay composition at the time of loading shall not exceed 0.04 percent.

3.5 Functioning. - The fuze shall function satisfactorily (see 6.5) and shall function with a delay time of not less than 1.0 second nor more than 2.0 seconds (see 6.6).

*3.6 Waterproofness. - The fuze shall function after being subjected to the specified test procedures.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, chips, dirt, corrosion products and other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few slight scratches not exposing base material. All required markings shall be neat and sharply defined.

3.8 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. The following certifications are required:

a. Certificate of conformance denoting primer composition and the drying procedure as per Dwg. 7548287 shall be furnished with each lot submitted for acceptance.

b. Certificate of conformance denoting drying procedure of the flash igniter head assembly in the event of excess exposure as per Dwg. 7548286 shall be furnished with each lot submitted for acceptance.

*4.2 Classification of inspections. - The following types of inspections shall be conducted on this item.

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First Article Inspection

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. The first article sample shall consist of fifty (50) consecutively produced complete assemblies. The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

*4.3.2 Inspections to be performed. - The first article samples shall be submitted in accordance with paragraph 4.3.1 and will be subjected by the Government to any or all of the requirements of the applicable drawings, the examinations of paragraphs 4.4.2.1 thru 4.4.2.5 and Table I specified herein.

*4.3.3 Rejection. - (See MIL-A-48078).

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-12774D (PA)

PARAGRAPH	TITLE: Fuze, Mine, Combination, M605		SHEET 1 OF 1		DRAWING NUMBER: 7548284
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major A	Functioning Test	25		3.5	4.5.3/8792739
Major A	Waterproofness Test	25		3.6	4.5.4

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the currentversion before use.

4.4 Quality conformance inspection

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Lot numbering as required shall be in accordance with MIL-STD-1168. In addition, inspection lots of loaded fuzes shall contain:

a. Parts of not more than one lot interfix number from one manufacturer.
b. Black powder from not more than one lot.
c. Delay composition from one batch or blending of batches which results in homogeneity of all delay composition used in loading the entire fuze lot.
d. Primers from not more than one lot interfix number from one manufacturer.
e. Head assemblies from not more than one lot interfix number from one manufacturer.

*4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major or minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-12774D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Flash Igniter Head Assembly		7548288
			NEXT HIGHER ASSEMBLY 7548284

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Delay Charge missing		0.40%	3.2	Visual
132	Flash hole obstructed		0.40%	3.2	Visual
Minor					
201	Total Length, (max.)		0.65%	3.2	Gage
202	Diameter of Head, (max.)		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DARPA-QA FORM 2967 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-12774D (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Flash Igniter Assembly		7548289
			NEXT HIGHER ASSEMBLY 7548284

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Tube crimp less than 360 degrees		0.40%	3.2	Visual
132	Crack in flash igniter charge tube		0.40%	3.2	Visual
Minor					
201	Total length (max)		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-12774D (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
#4.4.2.3	Primer Housing Assembly	1 OF 1	7548287
			NEXT HIGHER ASSEMBLY: 7548284

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Primer missing		0.40%	3.2	Visual
132	Primer inverted		0.40%	3.2	Visual
133	Primer crimp less than 360 degrees		0.40%	3.2	Visual
134	Sealant missing or inadequate		0.40%	3.2	Visual
135	Primer assembly above flush		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202640-17T23:19Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.4	Loading Assembly		7548286
			NEXT HIGHER ASSEMBLY 7548284

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Total Length (max)		0.40%	3.2	Gage
132	Seal of flash igniter assembly thread in primer housing missing or inadequate		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
*4.4.2.5	Fuze, Mine, Comb, M605, Assembly				7548284
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Interlocking safety pin, striker safety pin or release pin of safety pin assembly missing or not interlocked		100%	3.2	Visual
2	Release pin cotter pin missing or pin leg not bent		100%	3.2	Visual
3	Explosive in loading assembly exposed or evidence of leakage		100%	3.2	Visual
Major A					
101	Distance between prong and striker, (max)		0.25%	3.2	Gage
102	Release pin ring missing or damaged		0.25%	3.2	Visual
Major B					
131	Total length, (max)		0.40%	3.2	Gage
132	Distance between prong and top of release pin ring, (max)		0.40%	3.2	Gage
133	External thread damaged		0.40%	3.2	Visual
134	Cords missing or damaged		0.40%	3.2	Visual
135	Gasket missing from case		0.40%	3.2	Visual
136	Any part dented or distorted		0.40%	3.2	Visual
137	Prong missing		0.40%	3.2	Visual
138	Seal of igniter tube-head joint inadequate		0.40%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-12774D (PA)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
*4.4.2.5	Fuze, Mine, Comb, M605, Assembly				7548284
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major B					
139	Crack in crimp of igniter tube		0.40%	3.2	Visual
140	Seal of loading assembly threads in case inadequate		0.40%	3.2	Visual
Minor					
201	Marking misleading or unidentifiable including incorrect color code		0.65%	3.7	Visual
202	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Container, Metal, Sealed		7548190
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Puncture or hole		0.40%	3.2	Visual
132	Container dented or deformed		0.40%	3.2	Visual
133	Key missing		0.40%	3.2	Visual
Minor					
201	Contents move when container is shaken		0.65%	3.2	Manual
202	Bare spots on exterior other than slight scratches		0.65%	3.2	Visual
203	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Box, Packing, Wooden, Sealed	1 OF 1	7548179
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Hardware missing, broken or loose		0.40%	3.2	Visual/Manual
132	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
133	Contents exposed		0.40%	3.2	Visual
134	Board broken or split		0.40%	3.2	Visual
135	DOD symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Hardware improperly engaged		0.65%	3.2	Visual/Manual
202	Handle missing or insecure		0.65%	3.2	Visual/Manual
203	Contents loose when box is tilted		0.65%	3.2	Manual
204	Strapping improperly assembled		0.65%	3.2	Visual
205	Car seal missing, unsealed or improperly positioned		0.65%	3.2	Visual
206	Marking misleading or unidentifiable, including incorrect color code		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

*4.4.3.1 Moisture content of the black power. - (see 3.3) - Major A Defect.-The contractor shall provide adequate controls to assure that the black powder complies with the applicable requirement. For verification, a minimum of one sample of black powder shall be selected at the loading station at the time of loading from each eight hours of production. A composite sample shall not be used. The test shall be performed as specified in 4.5.1. Failure of the sample to comply with the applicable requirement, shall cause the black powder represented by the sample, including any fuzes loaded with the non-conforming black powder, to be rejected. The contractor shall maintain adequate records to provide identification of the specific amount of black powder and the loaded items which are represented by the sample.

*4.4.3.2 Moisture content of delay composition - (see 3.4) - Major A Defect. - The moisture content of the delay composition shall be determined at the time of loading not less than once for each eight hours of production or portion thereof. The sample shall be selected just prior to loading and the moisture content determination made as specified in 4.5.2. Composite samples shall not be used in this determination. If the moisture content exceeds the requirement specified, the delay composition shall be rejected. If this determination is made after loading has begun, components loaded therewith shall be rejected. Equipment used in this determination shall be in accordance with 4.4.4.

*4.4.3.3 Functioning - (see 3.5).-Major A Defect.

4.4.3.3.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria specified, the sampling plan for this test shall be in accordance with MIL-STD-105 using Code Letter L and an AQL of 0.65 percent. The test shall be performed as specified in 4.5.3 using equipment in accordance with 4.4.4. Any fuze assembly which fails to function, or fails to function within the specified delay time requirements, shall be classed defective. Any fuze which functions in less than 1.0 second shall cause the lot to be rejected with no second sampling permitted. Any fuze which fails to function, or whose delay time is lost, shall be replaced in order to determine if the lot complies with the delay time requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-17T23:19Z
Check the source to verify that this is the currentversion before use.

4.4.3.3.2 After three (3) consecutive lots have met the criteria of 4.4.3.3.1, the sampling plan for this test shall be in accordance with MIL-STD-105 using Code Letter J and an AQL of 0.65 percent.

*4.4.3.4 Waterproofness of head assembly - (see 3.6) - Major A Defect.-The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter J, double sampling plan and an AQL of 4.0 percent. Twenty-five (25) assemblies shall be subjected to the pull test and twenty-five (25) to the pressure test. The test shall be performed as specified in 4.5.4 using equipment in accordance with 4.4.4. Any assembly failing to meet the specified requirement shall be classed defective.

4.4.3.5 Check test for possible deterioration of primers - Major A defect. - If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into the fuze exceeds two years, or if the primers have been subjected to adverse conditions for any period of time since previous test, the primer lot shall be subjected to and must satisfactorily pass the check test for possible deterioration specified in MIL-P-20444 immediately before the assembly of primer lot into the fuzes. This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primer lot into the fuzes and shall be conducted at Government expense without cost to the contractor assembling the primers into the fuzes. Furthermore, this test shall not constitute a basis of rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.3 herein.

4.5 Test methods and procedures - (see 6.7)

4.5.1 Moisture content of black powder. - The moisture content of the black powder shall be determined as specified in MIL-P-223.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:19Z
Check the source to verify that this is the current version before use.

4.5.2 Moisture content of delay composition. - The moisture content of the delay composition shall be determined as specified in MIL-C-13739.

4.5.3 Functioning. - The assembly shall be kept with the prongs pointed upward, and shall be maintained at 70 plus or minus 20 degrees Fahrenheit (F.) at all times during the test procedure. The fuze assembly shall be assembled to the propelling charge (dwg. no. 8796343) and the test fixture specified on dwg. no. 8792739 and functioned to determine compliance with 3.5.

*4.5.4 Waterproofness. - The fuze head assembly with loaded primer housing and igniter assembly shall be submerged in an upright position in water with prongs no less than 6 inches below the surface for a minimum of 24 hours. On removal from the water, the fuze assembly shall be shaken lightly to remove external water, then placed in a cold cabinet in an upright position and conditioned at minus 40 degrees Fahrenheit minimum for 6 hours minimum. Immediately after removal from the cold cabinet, the release pin, interlocking safety pin, and the striker safety pin shall be removed in that order. One fraction of the sample shall be subjected to a pull, not to exceed 15 pounds, applied at a rate of one foot maximum per minute, to the release spring parallel to the axis of the release pin. The remaining fraction of the sample head assemblies shall be subjected to a pressure, not to exceed 45 pounds, applied at a rate of one foot maximum, per minute, to the prongs parallel to the axis of the head assembly. Observation shall be made for compliance with 3.6.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A. - The fuzes shall be packaged in metal containers in accordance with dwg. 7548190.

5.2 Packing

5.2.1 Level A. - The fuzes, packaged in accordance with 5.1.1, shall be packed in wooden boxes with M16A1 or M16A2 Mines in accordance with dwg. 7548179.

5.3 Marking. - Marking shall be in accordance with dwgs. 7548179 and 7548190.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

6. NOTES

*6.1 Intended use. - The fuze covered by this specification is intended for use in the M16A1 or M16A2 Anti-Personnel Mine.

*6.2 Ordering data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

*6.3 Submission of inspection equipment designs for approval - (See MIL-A-48078). Submit equipment designs as required, to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T, Dover, New Jersey 07801.

*6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

6.5 Functioning. - The fuze shall have functioned satisfactorily when the propelling charge has been ignited.

6.6 Delay time. - Delay time is defined as the time between functioning of the head assembly and functioning of propelling charge.

*6.7 International Standardization Agreement. - Certain provisions, section 3 and 4.4, of this specification are the subject of international standardization agreement QSTAG-255. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Officers so that appropriate action may be taken respecting the International agreement concerned.

6.8 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-122

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-767/101

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-17T23:19Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:19Z
Check the source to verify that this is the current version before use.