MILITARY SPECIFICATION

GASKET MATERIAL, NON-METALLIC

This amendment forms a part of Military Specification MIL-G-12803B(MR), dated 20 October 1976, and is approved for use by the Army Materials and Mechanics Research Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Line 9: Delete "15% minimum" and substitute "15% maximum".

Line 10: Delete "10% weight" and substitute "20% weight".

Paragraph 2.1, line 20: Delete "Fed. Std. No. 356" and substitute Military Standard "MIL-STD-1188".

PAGE 3

Paragraph 2.2, line 9: Delete "F39 - Testing Compressed Asbestos Sheet Packing"

Paragraph 2.2, line 10 and 11: Delete "F64 - Corrosive and Adhesive Effects of Gasket Materials on Metal Surfaces" and substitute "F607 - Adhesion of Gasket Materials to Metal Surfaces"

Paragraph 2.2, below F152 - Tension Testing of Non-Metallic Gasket Materials (line 15) add: "F495 - Ignition Loss of Gasket Material Containing Inorganic Substances"

PAGE 4

After paragraph 3.4.1, add the following paragraphs:

"3.4.2 Fabricated gaskets. Fabricated gaskets die cut, shall be of the shape and dimensions specified (see 6.2).

"3.4.3 Thickness types 1, 2 and 3 gaskets. The thick;ness of types 1, 2 and 3 gaskets shall be specified (see 6.2).

"3.4.3.1 Thickness tolerances. Unless otherwise specified (see 6.2), thickness tolerances shall be in accordance with table 3 of ASTM F104 for F-identification numbers."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:22Z
Check the source to verify that this is the current version before use.

PAGE 8

Table II, below "Thickness change" (line 23) in "Physical and mechanical characteristics" column add: "Weight loss on ignition - 1 hr at 1459 - 1539°F (793 - 837°C)" and add "F495" to "ASTM test method" column.

Table II, line 26: Delete "Adhesion and Corrosion" from "Physical and mechanical characteristic" column and substitute "Adhesion to metal surfaces."

Table II, line 26: Delete F64" from "ASTM test method" column and substitute "F607."

PAGE 9

Paragraph 4.5.1: Delete in its entirety and add:

"4.5.1 Loss on ignition . Loss on ignition of type 1 gasket materials shall be determined in accordance with ASTM F495."

Paragraph 5.1.2, line 2: Delete "Fed. Std. No. 356" and substitute "MIL-STD-1188".

PAGE 10

Paragraph 5.2.3, lines 1 and 2: Delete "Fed. Std. No. 356" and substitute "MIL-STD-1188".

PAGE 12

Footnote 1/: Delete "See table VII for definition and interpretation of E suffix numbers." and sbustitute "Refer to ASTM F104 for definition and interpretation of E suffix numbers."

PAGE 16

Delete Table VII in its entirety.

Custodian:

Army - MR

Preparing activity:

Army - MR
Project No. 5330-A086

★ U.S. GOVERNMENT PRINTING OFFICE: 1982—505-022/1373 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:22Z
Check the source to verify that this is the current version before use.