INCH-POUND

MIL-P-12764G (AR)
AMENDMENT 7
23 March 1993

SUPERSEDING
AMENDMENT 6
08 May 1990

MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH, ILLUMINATING, M335A2
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-P-12764G (AR), dated 11 March 1981, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1, Under "PRODUCT AND PACKING DRAWINGS," change "pellet" to "pallet."

PAGE 3

3.4.2, Luminosity, Delete "703,000" and substitute "800,000"; also delete "670,000" and substitute "750,000."

PAGE 4

* 4.3.1, Change under "Quantity", First nine (9) "15" to "10". Add the following:

"Canister Base Assembly	8886447	10
Plate, Base	8833779	10
Base, Canister	8833781	10
Pin, Swivel	8886448	10
Illuminating Canister Loading Assembly Prior to Load of Illuminant	8886446	10"

AMSC N7A FSC 1919

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

tic particle inspection, exhibits two (2) or examined by magne

PAGE 5

TABLE I: Correct typing error "illuminent" to "illuminant"

Add "Canister body assembly
(Dwg. 8885176)
Examination for defects...15...3.2...4.4.2.4.1
Salt spray test.....2...3.2...4.5.5"

TABLE I, Under "Illuminating canister loading assembly..."
Delete line "Salt spray test...2...3.2...4.5.5"

* Table I, (sheet 1 of 3) Change under "NO. OF SAMPLE UNITS," "15" to "10". Add the following:

"Canister Base Assembly
(Dwg. 8886447)
Examination for defects...10...3.2...4.4.2.15

Plate, Base
(Dwg. 8833779)
Examination for defects...10...3.2...4.4.2.16

Base, Canister
(Dwg. 8886453)
Examination for defects...10...3.2...4.4.2.17

Pin, Swivel
(Dwg. 8886453)
Examination for defects...10...3.2...4.4.2.18"

PAGE 6

* Table I (sheet 2 of 3) Change under "NO. OF SAMPLE UNITS," last three (3) "15" to "10".

Table I, Change under "TITLE," "Asembly" to "Assembly."

PAGE 7

TABLE I: Correct typing error "Asembly" to "Assembly"

PAGE 8

4.4.1.c, Delete "lot" and substitute "lot interfix."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

be cause for rejection of the sample and all progressive

PAGE 10

* 4.4.2.2, Major 102, Add "max" after "Radius". Add "Note 1" after "Gage."

Major 103, Add "max" after "Arc length". Add "Note 1" after "Gage."

Under "Notes," Add "(1) three parts must enter a 3.788-.001 I.D. Ring Gage. With two (2) edges contacting, the remaining edge must accept a .099 feeler gage."

PAGE 12

4.4.2.4, Under Major category, delete defect 102 and substitute the following:

"102 Inside diameter, min...40%...3.2...Gage"

Delete under "NOTES" in its entirety and substitute:

"Samples shall be selected from each production lot in accordance with MIL-STD-105D, Table IIA, code letter D and an AQL of 1.5%."

4.4.2.4.1, Add new paragraph page 12A, included.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:18Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4.1	Canister Body Assembly	1 OF 1	8885176
			NEXT HIGHER ASSEMBLY 8886453

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Brake missing	0.40%	3.2	Visual
102	Spot or projection weld missing	0.40%	3.2	Visual
103	Brake flush	0.40%	3.2	Visual
Minor				
201	Evidence of poor workmanship	0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-17T23:18Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.5, Delete Major 101, 102, 103 and 104 in their entirety and substitute the following:

"101 Liner composition present on open end of can between brakes 0.40%...3.2...Visual"

* Minor 201, Change "3.8" to "3.7."

PAGE 14

4.4.2.6, Under Major category add the following:

"108 Lot number missing 0.40%...3.2...Visual"

* Delete Minor 201 in its entirety and substitute the following:

"201 Outside diameter shall be press die inside diameter, max ...Note B ...3.2 ...Tool Control"

* Minor 203, Change "3.8" to "3.7."

* Add under "NOTES" as follows:

"B. Should the illuminating canister loading assembly experience an interference fit during assembly into projectile body, the consolidation press dies shall be dimensionally inspected and defects corrected prior to further production. The defective parts shall not be included in the lot. There shall be approved recall calibration system in effect for the consolidation press die."

PAGE 15

4.4.2.7, Under Major category add the following:

"106 Single row gathering stitch through felted seam missing when 2-segment canopy was used 0.40%...3.2...Visual

107 Reinforcing tapes on felted seam missing when 2-segment canopy was used 0.40%...3.2...Visual

108 Improper number of double row gathering stitches 0.40%...3.2...Visual:

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:18Z
Check the source to verify that this is the current version before use.

PAGE 15 (Cont'd)

* Major 104, Change "Holes" to "Unpatched holes."

* Minor 202, Change "3.8" to "3.7."

PAGE 16

* 4.4.2.8, Minor 201, Change "3.8" to "3.7."

PAGE 17

4.4.2.9, Delete Major 106 in its entirety and substitute:

"Outer edge of vent tape not within ±1/4 inch when folding 0.40%...3.2...Gage."

Under Major category, add the following:

"108 Rubber band located at shroud sleeving missing 0.40%...3.2...Visual"

* Major 101, Change "Step IX" to "Step X."

PAGE 22A

4.4.2.15, Add new CD sheet, included.

PAGE 22B

4.4.2.16, Add new CD sheet, included.

PAGE 22C

4.4.2.17, Add new CD sheet, included.

PAGE 22D

4.4.2.18, Add new CD sheet, included.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:18Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 8886447
4.5.2.15	Canister Base Assembly		NEXT HIGHER ASSEMBLY 8886446

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Swivel fails to rotate freely	0.40%	3.2	Visual/Manual
102	Missing parts	0.40%	3.2	Visual
Minor				
201	Crimp not 360 degrees	0.65%	3.2	Visual
202	Evidence of poor workmanship	0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Plate, Base		8833779
			NEXT HIGHER ASSEMBLY 8886447

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Diameter of plate	0.65%	3.2	Gage
202	Thickness of plate	0.65%	3.2	Gage
203	Evidence of poor workmanship	0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Base, Canister	1 OF 1	8833781
			NEXT HIGHER ASSEMBLY 8886447

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outside dia. of bearing bore boss, max.	0.65%	3.2	Gage
202	Inside dia. of base plate bore	0.65%	3.2	Gage
203	Inside dia. of bearing bore	0.65%	3.2	Gage
204	Depth of bearing bore from base plate bore	0.65%	3.2	Gage
205	Surface finish improper	0.65%	3.2	Visual
206	Evidence of poor workmanship	0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

SHEET 1 OF 1

DRAWING NUMBER
8886448

NEXT HIGHER ASSEMBLY
8886447

PARAGRAPH 4.4.2.18 TITLE: Pin, Swivel

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Dia. of ball bearing race (2)	0.65%	3.2	Gage
202	Dia. of hole, max.	0.65%	3.2	Gage
203	Width of flange	0.65%	3.2	Gage
204	Surface finish improper	0.65%	3.2	Visual
205	Evidence of poor workmanship	0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:18Z
Check the source to verify that this is the current version before use.

PAGE 27

4.5.2, Delete "703,000" and substitute "800,000" also delete "670,000" and substitute "750,000."

* Seventh line, Change "The first five" to "The first fire."

* 4.5.3, First line, Change "A gooseneck adapter" to "An adapter." Fifth line, Change "180 degrees" to "approximately 120 degrees."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AE55)

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:18Z
Check the source to verify that this is the current version before use.