MIL-P-12808E
8 October 1981
SUPERSEDING
MIL-P-12808D
2 May 1974

MILITARY SPECIFICATION

PLUMBING FIXTURES AND ACCESSORIES, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for preservation, packing, and marking of plumbing fixtures, fittings, trims, and accessories and may be used as a guide in the selection of materials to preserve, pack, and mark similar items not specifically listed herein.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-585	- Boxes, Wood, Wirebound.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

NO DELIVERABLE DATA REQUIRED BY THIS DOCUMENT

AREA PACK

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-676	- Boxes, Setup.

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Water-proofed, Flexible.
MIL-B-22191	- Barrier Material, Transparent, Flexible, Heat Sealable.
MIL-B-26195	- Box, Wood-Cleated, Skidded, Load- Bearing Base.
MIL-C-52950	- Crate, Wood, Open and Covered.

STANDARDS

FEDERAL

FED-STD-101	- Preservation, Packaging and Packing Materials: Test Procedures.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-147	- Palletized Unit Loads.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by manufacturer's in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

3.2 Preproduction pack. Unless otherwise specified (see 6.2), the contractor shall furnish a preproduction pack for examination and test within the time frame specified (see 6.2), to prove prior to starting production packaging, that the applied preservation, packing, and marking comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The preproduction pack may be accomplished utilizing either the preproduction model or the production model. If the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model.

3.3 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Preservatives and methods of preservation. Preservatives shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116. Methods of preservation indicated by symbols herein shall conform to the corresponding symbols in MIL-P-116.

3.3.1.2 Unprotected surfaces. Unprotected metal surfaces of fixtures, fittings, trim and accessories requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with a preservative compound as applicable. Components coated with a soft, nondrying type preservative shall be enclosed in a bag or wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 1 or 2, or MIL-B-22191. The wrap or bag shall be secured by heat sealing, taping or tying. Tape shall not be applied to finished surfaces.

3.3.1.3 Threads. Threads of fixtures, fittings, trim and accessories shall be protected with metal, plastic or other type thread protectors or the threaded surfaces shall be wrapped with not less than two layers of barrier material conforming to MIL-B-121, type I, grade A, class 1 or 2. The wrap shall be secured by taping or tying. Tape shall not be applied to finished surfaces.

3.3.1.4 Accessories.

3.3.1.4.1 Fixture accessories. Accessories not attached to basic fixtures such as but not limited to floor drains, sink drains, drain traps, shower heads faucets, rubber stoppers, water-closet flush bulbs, flush connections, mixing valves and lavatory drains shall be preserved either method I or III as applicable. Preservatives shall be applied as specified in 3.3.1.2. Accessories preserved method I (coated with a preservative) shall be individually bagged or wrapped as specified in 3.3.1.2. Accessories preserved method III (mechanical and physical protection) shall be preserved individually in boxes conforming to PPP-B-566, variety 1, style, type and class optional; PPP-B-676, variety 1, type, class and style optional or in the contractor standard commercial box, when the weight or contents is ten pounds or less. Accessories exceeding ten pounds weight shall be placed in boxes conforming to PPP-B-636, class domestic. The contents shall be secured within the box to prevent movement or damage in accordance with MIL-STD-1186.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

3.3.1.4.2 Other accessories. Other accessories such as soap holders, soap dispensers, toilet-paper-roll holders, water tumblers, toothbrush holders, paper-cup dispensers and paper towel dispensers shall be preserved individually method III. Boxes and securing shall be as specified in 3.3.1.4.1.

3.3.1.5 Consolidation. Accessories of like description preserved as specified in 3.3.1.4.1 and 3.3.1.4.2 shall be consolidated together, in quantities specified (see 6.2), in boxes conforming to PPP-B-636, class weather resistant, style optional. When specified (see 6.2), accessories of various descriptions required for a complete installation (see 3.4.1.1) shall be consolidated together in boxes specified herein. The boxes shall be waterproof sealed in accordance with the appendix to the box specification, method V closure.

3.3.2 Commercial. Fixtures, fittings, trim and accessories shall be preserved in accordance with MIL-STD-1188.

3.4 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

3.4.1 Level A.

3.4.1.1 Basic fixtures. Basic fixtures such as but not limited to bathtubs, drinking fountains, lavatories, laundry tubs, sinks, urinals and water closets shall be packed as a single fixture without accesories; as a single fixture with all accessories required for installation; or as consolidated packs of fixtures, with or without accessories, of like description or of various description as specified (see 6.2).

3.4.1.1.1 Fixtures and fixtures with accessories. Each fixture, fixture with accessories, two or more fixtures or two or more fixtures with accessories shall be packed, not to exceed the weight limitation, in close-fitting boxes conforming to PPP-B-621, class 2, style optional, PPP-B-601, overseas type, style optional, or PPP-B-585, class 3, style optional. Fixtures, fixtures with accessories or consolidated packs of fixtures exceeding the weight limitation of the boxes specified above, shall be packed in a box conforming to MIL-B-26195, type II, style optional, class 2, with rubbing strips and plywood superstructure or in crates conforming to MIL-C-52950, type V, style A, or MIL-C-104, type or class optional, style A. Unless otherwise specified (see 6.2), crates conforming to MIL-C-52950 shall be nondemountable. Blocking, bracing, anchoring, closure and strapping shall be in accordance with the appendix to the box or crate specification as applicable and in accordance with MIL-STD-1186. Strapping for boxes or crates shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified, (see 6.2) strapping shall be finish A.

3.4.1.1.2 Accessories. Accessories of like description shall be packed as specified in 3.4.1.1.1.

3.4.2 Level B.

3.4.2.1 Basic fixtures. Basic fixtures shall be packed as specified in 3.4.1.1 (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

3.4.2.1.1 Fixtures and fixtures with accessories. Each fixture, fixture with accessories, two or more fixtures or two or more fixtures with accessories shall be packed, not to exceed the weight limitation, in close-fitting boxes conforming to PPP-B-636, class weather-resistent, style optional, PPP-B-640, class 2, style optional, PPP-B-585, class 3, style optional, PPP-B-621, class 1, style optional or PPP-B-601, domestic type, style optional. Fixtures, fixtures with accessories or consolidated packs of fixtures exceeding the weight limitation of the boxes specified above, shall be packed in a box or crate as specified in 3.4.1.1.1, except crates conforming to MIL-C-52930 shall be style A or B as applicable. Blocking, bracing, anchoring, closure and strapping shall be in accordance with the appendix to the box or crate specification as applicable and in accordance with MIL-STD-1186.

3.4.2.1.2 Accessories. Accessories of like description shall be packed in boxes as specified in 3.4.2.1.1.

3.4.3 Commercial. Fixtures, fittings, trim, and accessories shall be preserved in accordance with MIL-STD-1188.

3.5 Palletization. When a quantity of fixtures or accessories are being shipped to the same destination; packed level A, level B, or commerical they shall be palletized, unless the size of the boxes makes palletization impractical. Fixtures or accessories packed for level A or level B shall be palletized in accordance with MIL-STD-147, load type as applicable. Fixtures or accessories packed for commercial may utilize a commercial type pallet suitable for the weight and size involved.

3.6 Marking.

3.6.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

3.6.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the items by application of the requirements specified herein, to prevent corrosion, deterioration and mechanical or physical damage during handling, shipment, and damage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined as specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction pack of boxed or crated equipment for level A or B shall be tested in accordance with 4.3.2.1 or 4.3.2.2, as applicable. Failure of the applicable test shall be cause for refection.

4.3.2.1 Boxed fixtures and accessories. Boxed fixtures and accessories not exceeding 200 pounds shall be subjected to the free-fall drop test in accordance with FED-STD-101, test method 5007, procedure E. Boxed equipment exceeding 200 pounds shall be subjected to the pendulum impact test in accordance with FED-STD-101, test method 5012, except the vertical height of drop shall be 18 inches.

4.3.2.2 Crated fixtures and accessories. Crated fixtures and accessories shall be subjected to the guided-impact test (railroad car) as specified in MIL-STD-1186, Appendix A. Crates not exceeding 9.5 feet in length shall be subjected to the tests on each end and each side, a total of 8 impacts.

4.3.2.3 Basic for rejection. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking or bracing or any visual damage to the contents shall constitute failure of the preproduction pack test and shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspecton shall be in two stages as follows:

(a) The first stage shall include inspection of materials, methods, containers, and markings prior to placing the fixtures and accessories in the shipping containers.
(b) The second stage shall include inspection of materials and markings of the completed pack as prepared for shipment.

4.4.2 Unit of product. For the purpose of inspection, a pack of any one level, containing all components prepared for an applicable stage of inspection, shall be considered a unit of product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I. Acceptable quality level shall be 2.5 percent defective.

TABLE I. Classification of Defects.

Number	Defect	Level		
		A	B	Commercial
101.	Materials, methods or containers not as specified. Each incorrect material, method or container shall constitute one defect.	X	X	
102.	Nondrying preservatives, when required, not bagged or wrapped as specified.	X		
103.	Threads not protected as specified.	X		
104.	Consolidation not as specified.	X		
105.	Consolidated boxes not sealed as specified.	X		
106.	Preservation not in accordance with referenced document.			X
107.	Packing not as specified.	X	X	
108.	Strapping not as specified.	X		
109.	Packing not in accordance with reference document.			X
110.	Palletization not as specified	X	X	X
111.	Marking missing, illegible, incorrect or incomplete.	X	X	X

5. PACKAGING

(Not applicable to this specification).

6. NOTES

6.1 Intended use. It is intended that this specification be referenced in Section 5 of commodity specifications or be used for direct reference in contracts or in the preparation of packaging data sheets.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) When a preproduction pack is not required (see 3.2).
(d) Degree of preservation and degree of packing required (see 3.3 and 3.4).
(e) Quantity to be consolidated (see 3.3.1.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

(f) When consolidation of accessories of various description for a complete installation is required (see 3.3.1.5).
(g) Whether complete fixtures, fixtures with accessories for installation or consolidated packs of fixtures with or without accessories are to be packed (see 3.4.1.1 and 3.4.2.1).
(h) When other than finish B strapping is required (see 3.4.1.1.1 and 3.4.1.1.2).
(i) When crates shall be demountable (see 3.4.1.1.1 and 3.4.1.1.2).

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack and mark the fixtures and accessories in accordance with this specification.

6.5 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of the specification (see 3.1).

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - SM
DLA - CS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project PACK-0642

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-12808E Plumbing Fixtures and Accessories, Packaging of

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:23Z
Check the source to verify that this is the current version before use.