MIL-S-12840G
12 February 1985
SUPERSEDING
MIL-S-12840F
14 March 1975

MILITARY SPECIFICATION

SADDLE ASSEMBLY: STEEL AND PLYWOOD; FOR 24-TON, 2-PART PNEUMATIC FLOAT, PONTON BRIDGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a saddle assembly and its components for the pneumatic ponton supporting the roadway and superstructure of class 60 floating bridges.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel and Seals.
TT-P-320	- Pigment, Aluminum; Powder and Paste for Paint.
TT-V-119	- Varnish, Spar, Phenolic-Resin.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-G-413	- Glue, Marine, and Aviation Marine (Waterproof).
MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-3774	- Crates, Wood; Open, 12,000- and 16,000-Pound Capacity.
MIL-S-4383	- Sealing Compound, Topcoat, Fuel Tank, Buna-N Type.
MIL-S-8802	- Sealing Compound, Temperature-Resistant, Integral Fuel Tanks and Fuel Cell Cavities, High-Adhesion.
MIL-C-16173	- Corrosion Preventive Compound, Solvent Cutback, Cold-Application.
MIL-W-18142	- Wood Preservative Solutions, Oil-Soluble, Ship and Boat Use.
MIL-G-20241	- Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-C-52950	- Crates, Wood, Open and Covered.
MIL-S-81733	- Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.
MIL-STD-1472	- Human, Engineering Design Criteria for Military Systems, Equipment and Facilities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

2.1.2 Government drawings. The following Government drawings form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13211E7560 Saddle Assembly.

(Copies of specifications, standards and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/ASME - Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
ANSI/AWS - D1.1 - Structural Welding Code, Section 5, Qualification.

(Applications for copies should be addressed to the American National Standards Institute, Inc., 1420 Broadway, New York NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951-Standard Practice for Commercial Packaging
D 2016-Wood, Moisture Content of

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The saddle assembly and its components shall be in accordance with Top Assembly TA13211E7560 and as specified herein (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the saddle assembly. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subject to first article inspection (see 4.3 and 6.3).

3.3 Material. Material shall be as specified herein and as shown on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The saddle assembly shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the saddle assembly may be newly fabricated from recovered materials to the maximum extent practicable, provided the saddle assembly produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the saddle assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

3.3.3 Wood. Wood shall be oak. The moisture content at the time of preservative treatment shall be not less than 10 or more than 18 percent when determined in accordance with ASTM D 2016. Slope of grain shall be not more than 1 inch in 10 inches. The wood shall be all heartwood and shall be free from defects except that the following will be acceptable; Sound knots not more than 5/8-inch average diameter, streaks, sound stain, sound bird pecks, scattered pin-wormholes not more than 1/16-inch diameter, and surface checks not more than 1/32 inch wide and 6 inches long.

3.4 Identification marking. The saddle assembly or component, as applicable, shall be metal-die stamped as shown on the applicable drawing. Die stamping shall be legible after painting.

3.5 Treatment and painting. All parts of the saddle assembly or components, except as specified herein, shall be treated and painted in accordance with MIL-T-704, type B. Pins, springs, inside and outside handle pins, and threaded portions of components shall not be painted but shall be coated with a preservative conforming to MIL-C-16173, grade 1. The edges of plywood panels shall be treated as specified in 3.5.2 and shall not have less than a prime coat of paint prior to assembly of the metal edge bands.

3.5.1 Preservative treatment. All lumber other than plywood shall be treated by soaking for 24 hours in colored preservative conforming to MIL-W-18142, type B. End grain and surfaces which have been cut, bored, or worked after preservative treatment shall be thoroughly swabbed with the specified preservative.

3.5.2 Bedding and sealing. Faying surfaces and contact edges of all members riveted or bolted to plywood (except the 3-inch channels) shall be coated after sealing and painting with marine glue conforming to MIL-G-413, class 2. Holes for bolts in plywood shall be coated with a mastic conforming to MIL-S-8802, class A-2, or MIL-S-4383. All edges of plywood shall be given two dips or brush coats of a sealer composed of aluminum paste conforming to TT-P-320, type II, class B, and phenolic resin varnish conforming to TT-V-119. The sealer shall be in the proportion of 2 pounds of aluminum paste to 1 gallon of varnish.

3.6 Stenciling. The nomenclature, National Stock Number, weight, and cube shall be stenciled on each saddle assembly. The letters "NET WT" shall precede the numerals in the weight and the letters "CU" shall precede the cubic displacement. The minimum number of people required to lift the saddle assembly, as defined in paragraph 5.9.11.3 of MIL-STD-1472, shall be stenciled on each side of the assembly as "(specify) Person Lift." Markings shall be Gothic-type capitals and Arabic numerals 3/4 inch high. Stenciling shall conform to MIL-T-704.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:25Z
Check the source to verify that this is the current version before use.

3.7 Government-loaned property. Unless otherwise specified (see 6.2), the following property in the quantities indicated will be loaned by the Government (see 6.7):

Item No.	Description	Identification	Quantity
1	Inspection equipment (gage) for saddle assembly, steel and plywood for 24-Ton, 2-Part, pneumatic float, ponton bridge	Quality assurance pamphlet, P715-117 included in top assembly microfilm	1 set

3.8 Workmanship. The fabricated saddle assemblies or components shall be free from sharp edges, slivers, or burrs.

3.8.1 Steel fabrication. Steel used in the fabrication of the saddle assemblies or components shall be free from laminations, kinks, and sharp bends. Steel shall be cut by shearing, sawing, or flame cutting. Burned surfaces of flame-cut material shall be ground or machined to remove ash and cooling checks. The straightening of material shall be done by methods that will not cause injury to the metal. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly.

3.8.2 Bolted connections. Boltholes and pinholes shall be located by the use of single or multiple steel jig assemblies. Holes shall be drilled or bored and shall have the burrs removed.

3.8.3 Riveted connections. Rivet holes shall be punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall fill the holes. Formed rivet ends shall be concentric with the rivet shank axis and shall have full bearing on the surface of the member.

3.8.4 Welders and welding.

3.8.4.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

AWS D1.1, Structural Welding Code, Section 5, Qualification.
ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

Certification shall be made available for inspection by the contracting officer or designated representitive, upon request.

3.8.4.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded, electric-arc method and shall conform to the provisions of ANSI/AWS D1.1 and as specified herein. Work shall be positioned for flat welding whenever practicable. Before welding over previously deposited

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:25Z
Check the source to verify that this is the currentversion before use.

weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean. The finished item shall be straight and within toleranced dimensions. Straightening and stress relieving shall be permitted to relieve distortion, provided the straightening process does not damage the end item.

3.8.4.2.1 Welding jigs. Components shall be assembled in steel jigs or frames and welded while held in position. The jigs or frames shall be of a design that will limit the distortion to an amount that can be removed without changing the physical characteristics of the metal of the parts being welded.

3.8.5 Interchangeability. Like parts and components shall be fabricated to be duplicates within the tolerances specified, and shall be interchangable.

3.8.6 Machine work. Tolerances and gages for metal fits shall conform to the limitations specified herein and on the applicable drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards and drawings, as applicable.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the quality assurance provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.5 and 6.6).

4.2 Classification of inspections. The inspections requirements specified herein are as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Examination. The first article saddle assembly or component(s), as applicable, shall be examined in accordance with 4.4.2.1 and for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The first article saddle assembly shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination.

4.4.2.1 Individual. Each saddle assembly or component(s) as applicable, shall be examined for conformance to the dimensions covered by the QAP shown on the drawings under "Major - 100 percent inspection". Unless otherwise specified (see 6.2), Government-loaned inspection equipment (see 3.7) shall be used in accordance with the Government QA Pamphlet included in the TA package (see 3.1) to inspect dimmensions as applicable. Nonconformance to any of these dimensions shall constitute failure of this examination and shall be cause for rejection.

4.4.2.2 Samples. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 1.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The saddle assembly or components, as applicable, shall be examined as specified herein for the following defects:

Major

101. Materials not as specified.
102. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operating environments.
103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
104. Contractor does not have documentation available for identification of material, material finishes or treatment.
105. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the saddle assembly.
106. All dimensions designated major, but not 100 percent inspection on the QAP, not as specified.
107. Workmanship not as specified.
108. Welding certification not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the currentversion before use.

Minor

201. All dimensions not designated major on the QAP not as specified.
202. Identification marking incorrect, missing, or illegible.
203. Treatment and painting not as specified.
204. Stenciling not as specified.
205. Preservation treatment and sealing not as specified.

4.5.2 Assembly test. Assemble the components into one complete saddle assembly. Interference of mating members or improper fits at joints shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Preproduction pack inspection.

4.6.1.1 Examination. Examine the preproduction pack for the defects specified in 4.6.2.3. Presence of one or more defects shall be cause for rejection.

4.6.1.2 Test. Subject the preproduction pack of crated items for level A or B to the railroad-impact test in accordance with appendix A to MIL-STD-1186. At the conclusion of the preproduction pack test, the pack shall be examined. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking, or bracing, or any visible damage to the components shall constitute failure of the preproduction pack test and shall be cause for rejection.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following defects. AQL shall be 2.5 percent defective for major defects.

109. Complete saddle assemblies or components packed together in quantities other than specified for level A or B.
110. Boxes and crates not as specified for level A or B.
111. Small loose components for each complete saddle assembly not packed in boxes as specified for level A or B.
112. Components not packed on crate base to provide maximum compactness and low center of gravity for level A or B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

113. Strapping not as specified for level A or B.
114. Blocking, bracing, and anchoring not adequate to prevent shifting of contents for level A or B.
115. Packing not in accordance with the referenced document for commercial.
116. Marking illegible, incorrect, incomplete, or missing for level A, B, or commercial.

5. PACKAGING

5.1 First article pack. The contractor shall furnish a first article pack for examination and test within the time frame specified (see 6.2), to prove prior to starting production packing, that the applied packing and marking comply with the packaging requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The first article pack may be prepared utilizing either the first article or a production unit. When the first article is utilized, any packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the first article and production units.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 When complete saddle assemblies are procured.

5.2.1.1.1 Small loose components. Small loose components for each complete saddle assembly, such as pins and bridge pin retainers, shall be packed together in a close-fitting box conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. Strapping shall not be required.

5.2.1.1.2 Saddle assemblies. The unassembled saddle assemblies, with the packed small components comprising of three complete saddle assemblies, shall be packed in a crate conforming to MIL-C-3774, type II. The saddle assemblies with the boxed components shall be arranged on the crate base to provide maximum compactness and low center of gravity. Blocking, bracing, and anchoring of contents shall be provided and shall be in accordance with the appendix to the crate specification and MIL-STD-1186.

5.2.1.2 When saddle assembly components are procured. When the saddle beam pin assembly, interior panel assembly, or end panel assembly is procured separately from the saddle assembly, it shall be packed as follows.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

5.2.1.2.1 Saddle beam pin assembly. Pin assemblies shall be packed in close-fitting boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.2.1.2.2 Interior panel assembly and end panel assembly. Two end panel assemblies or four interior panel assemblies shall be packed together in a crate conforming to MIL-C-52950, type V, style A, class 1, or in a close-fitting box conforming to PPP-B-621, class 2, style 7, with hood. Blocking, bracing, and anchoring of the contents to prevent movement shall be provided and shall be in accordance with MIL-STD-1186. Strapping shall be as specified in 5.2.1.2.1.

5.2.2 Level B. Packing shall be as specified for level A except boxes shall be domestic type or class as applicable, and strapping shall be finish A.

5.2.3 Commercial. Complete saddle assemblies or separately procured saddle assembly shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with ASTM D 3951.

6. NOTES

6.1 Intended use. The saddle assembly is intended to be used to support the roadway and superstructure of a floating bridge on pneumatic pontons.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Whether complete saddle assemblies or components are required (see 3.1).

c. When a first article is required for inspection and approval, and the number of units required (see 3.2, 4.3 and 6.3).

d. When Government-loaned property is not to be furnished and used for inspection (see 3.7 and 4.4.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

e. Time frame required for submission of first article pack (see 5.1).

f. Degree of packing required (see 5.2).

g. When other than finish B strapping is required (see 5.2.1.2.1 and 5.2.1.2.2).

6.3 First article. When a first article inspection is required, the item shall be examined and tested, and should be a first produced saddle assembly. The contracting officer should include specific instructions in the acquisition documents regarding arrangements for examinations and approval of the documents first article.

6.4 First article pack. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to pack, and mark the saddle assemblies in accordance with this specification.

6.5 Quality assurance provisions (QAP). The contracting officer should require the contractor to maintain records of all QAP inspections. A suggested paragraph is as follows:

"The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include, as a minimum lot size, sample size, drawing requirements, actual measurements, number and type of deficiencies found, quantity approved, quantity rejected and corrective action taken when applicable."

6.6 Definitions.

6.6.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements Section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.7 Government-loaned property. The contracting officer should arrange to loan the property specified in 3.7, when applicable.

Custodian:
Army - ME

Review activity:
Navy - MC

Preparing activity:
Army - ME

Project 5420-0153

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-12840G	Saddle Assembly: Steel and Plywood; For 24-Ton, 2-Part Pneumatic Float, Ponton Bridge

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY
Commander
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.