INCH-POUND

MIL-S-12840H
06 November 1992
SUPERSEDING
MIL-S-12840G
12 FEBRUARY 1985

MILITARY SPECIFICATION

SADDLE ASSEMBLY: STEEL AND PLYWOOD, FOR 24-TON, 2-PART PNEUMATIC FLOAT, PONTON BRIDGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a saddle assembly and its components for the pneumatic ponton supporting the roadway and superstructure of class 60 floating bridges.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: SATBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-V-119	- Varnish, Spar, Phenolic-Resin.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-G-413	- Glue, Marine, and Aviation Marine (Waterproof).
MIL-T-704	- Treatment and Painting of Material.
MIL-C-3774	- Crates, Wood; Open, 12,000- and 16,000-Pound Capacity.
MIL-S-4383	- Sealing Compound, Topcoat, Fuel Tank, Buna-N Type.
MIL-S-8802	- Sealing Compound, Temperature-Resistant, Integral Fuel Tanks and Fuel Cell Cavities, High-Adhesion.
MIL-C-16173	- Corrosion Preventive Compound, Solvent Cutback, Cold-Application.
MIL-W-18142	- Wood Preservative Solutions, Oil-Soluble, Ship and Boat Use.
MIL-C-52950	- Crates, Wood, Open and Covered.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-209	- Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.
MIL-STD-1472	- Human, Engineering Design Criteria for Military Systems, Equipment and Facilities.

(Unless otherwise indicated, copies of federal and military specifications and standards are available from the Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings. The following other Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

TA13211E7560 - Saddle Assembly.

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development and Engineering Center. ATTN: SATBE-JBS, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers, and Welding and Brazing Operators.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 962	- Aluminum Powder and Paste Pigments for Paints.
D 3953	- Strapping, Flat Steel and Seals.
D 4675	- Selection and Use of Flat Strapping Materials.
D 4442	- Direct Moisture Content Measurement of Wood and Wood-Base Materials.
D 4444	- Use and Calibration of Hand-Held Moisture Meters.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

D 1.1 - Structural Welding Code - Steel.

(Application for copies should be addressed to the American Welding Society, 555 NW 42nd Street, Miami, FL 33126.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE AGENT

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Association, Inc., ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The saddle assembly and its components shall be in accordance with TA13211E7560 and as specified (see 6.2).

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviations from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly and operation of the saddle assembly. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. When specified (see 6.2) a sample shall be subject to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. The saddle assembly shall be fabricated from compatible materials, inherently corrosion resistant or

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the saddle assembly may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish, or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces, and parts incorporated in the saddle assembly may be newly fabricated from recovered materials to the maximum extent practicable, provided the saddle assembly produced meets all other requirements of this specification. Used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the saddle assembly.

3.3.3 Wood. Wood shall be oak. The moisture content at the time of preservative treatment shall be not less than 10 or more than 18 percent when determined in accordance with ASTM D 4442 or D 4444. Slope of grain shall be not more than 1 inch in 10 inches. The wood shall be all heartwood and shall be free from defects except that the following will be acceptable; sound knots not more than 0.625 inch average diameter, streaks, sound stain, sound bird pecks, scattered pin-wormholes not more than 0.063 inch in diameter, and surface checks not more than 0.031 inch wide and 6 inches long.

3.4 Identification marking. The saddle assembly shall be identified in accordance with MIL-STD-130 and shall be metal-die stamped as shown on the applicable drawing. Die stamping shall be legible after painting.

3.5 Treatment and painting. All parts of the saddle assembly or components, except as specified herein, shall be treated and painted in accordance with MIL-T-704, type B. Pins, springs, inside and outside handle pins, and threaded portions of components shall not be painted but shall be coated with a preservative conforming to MIL-C-16173, grade 1. The edges of plywood panels shall be treated as specified in 3.5.2 and shall not have less than a prime coat of paint prior to assembly of the metal edge bands.

3.5.1 Preservative treatment. All lumber other than plywood shall be treated by soaking for 24 hours in colored preservative conforming to MIL-W-18142, type A or C. End grain and surfaces which have been cut, bored, or worked after preservative treatment shall be thoroughly swabbed with the specified preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

3.5.2 Bedding and sealing. Faying surfaces and contact edges of all members riveted or bolted to plywood (except the 3-inch channels) shall be coated after sealing and painting with marine glue conforming to MIL-G-413, class 2. Holes for bolts in plywood shall be coated with a mastic conforming to MIL-S-8802, class A-2, or MIL-S-4383. All edges of plywood shall be given two dips or brush coats of a sealer composed of aluminum paste conforming to D 962, type II, class B, and phenolic resin varnish conforming to TT-V-119. The sealer shall be in the proportion of 2 pounds of aluminum paste to 1 gallon of varnish.

3.6 Stenciling. The nomenclature, National Stock Number, weight, and cube shall be stenciled on each saddle assembly.. The letters "NET WT" shall precede the numerals in the weight and the letters "CU" shall precede the cubic displacement. The minimum number of people required to lift the saddle assembly, as defined in MIL-STD-1472, shall be stenciled on each side of the assembly as "(specify) Person Lift." Markings shall be Gothic capitals and Arabic numerals 0.750 inch high. Stenciling shall conform to MIL-T-704.

3.7 Government-loaned property. Unless otherwise specified (see 6.2), the following property in the quantities indicated in table I will be loaned by the Government (see 6.7).

TABLE I. Government-loaned property.

Item	Description	Identification	Quantity
1	Inspection equipment (gage) for saddle assembly, steel and plywood for 24-Ton, 2-Part pneumatic float, ponton bridge.	Quality assurance pamphlet, P715-117 included in top assembly microfilm.	1 set

3.8 Workmanship. The fabricated saddle assemblies or components shall be free from sharp edges, slivers, or burrs.

3.8.1 Steel fabrication. Steel used in the fabrication of the saddle assemblies or components shall be free from delaminations, kinks, and sharp bends. Steel shall be cut by shearing, sawing, or flame cutting. Burned surfaces of flame-cut material shall be ground or machined to remove ash and cooling checks. The straightening of material shall be done by methods that will not cause injury to the metal. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly.

3.8.2 Bolted connections. Bolt holes and pin holes shall be located by the use of single or multiple steel jig assemblies. Holes shall be drilled or bored and shall have the burrs removed.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the currentversion before use.

3.8.3 Riveted connections. Rivet holes shall be punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall fill the holes. Formed rivet ends shall be concentric with the rivet shank axis and shall have full bearing on the surface of the member.

3.8.4 Welders and welding.

3.8.4.1 Welders or welding operator. Before assigning any welder or welding operator to manual welding work covered by this specification, the contractor shall obtain certification that the welder or welding operator has passed qualification tests as prescribed by either AWS D 1.1 or the ASME code for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined. Contractors who only make horizontal welds need not qualify welders for "all position welding". The contractor is responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes. In the event of evidence of poor welds, the Government reserves the right to require retesting of any welder or welding operator (see 6.6).

3.8.4.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded, electric-arc method and shall conform to the provisions of either ASME or AWS. Work shall be positioned for flat welding whenever practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean. The finished item shall be straight and within toleranced dimensions. Straightening and stress relieving shall be permitted to relieve distortion, provided the straightening process does not damage the end item.

3.8.4.2.1 Welding jigs. Components shall be assembled in steel jigs or frames and welded while held in position. The jigs or frames shall be of a design that will limit the distortion to an amount that can be removed without changing the physical characteristics of the metal of the parts being welded.

3.8.5 Interchangeability. Like parts and components shall be fabricated to be duplicates within the tolerances specified and shall be interchangeable.

3.8.6 Machine work. Tolerances and gages for metal fits shall conform to the limitations specified herein and on the applicable drawings.

3.9 Tiedown provisions. The tiedown provisions shall conform to MIL-STD-209, class 2 or 3, type IV equipment. The tiedown provisions shall satisfactorily complete the pull testing as specified without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components.

3.9.1 Slinging provisions. The slinging provisions shall conform to MIL-STD-209, class 1 or 3, type IV. The provisions shall enable the complete saddle assembly to be lifted in the normal operating position. The provisions shall be located so that not less than one inch clearance is maintained between

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

slings and all exterior parts and shall be fastened to members which will withstand stresses in the amount and direction of pull specified for the provisions without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components. Slinging provisions may also be used as tiedown provisions when such provisions meet the requirements specified in 3.9. All slinging/tiedown provisions shall be labeled "LIFT", "TIEDOWN", or "LIFT TIEDOWN", as appropriate, in 1-inch (2.54 cm) high letters.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.1.3 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the quality assurance provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.5 and 6.6.1).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Examination. The first article saddle assembly or component(s) as applicable, shall be examined for the defects as specified in 4.5.1, as applicable. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article saddle assembly shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.2 Examination.

4.4.2.1 Individual. Each saddle assembly or component(s) as applicable, shall be examined for conformance to the dimensions covered by the QAP shown on the drawings under "Major - 100 percent inspection". Unless otherwise specified (see 6.2), Government-loaned inspection equipment (see 3.7), shall be used in accordance with Government QA Pamphlet included in the TA package (see 3.1) to inspect dimensions as applicable. Nonconformance to any of these dimensions shall constitute failure of this examination and shall be cause for rejection.

4.4.2.2 Samples. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1.

4.5 Inspection procedure.

4.5.1 Examination. The saddle assembly or components shall be examined as specified herein for the following defects:

Major

101. Materials not as specified (see 3.3).
102. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operation environments (see 3.3.1).
103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other (see 3.3.1.1).
104. Contractor does not have documentation available for identification of material, material finishes or treatment (see 3.3.1.2).
105. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the saddle assembly (see 3.3.2).
106. All dimensions designated major, but not 100 percent inspection on the QAP, not as specified (see 3.1.1).
107. Workmanship not as specified (see 3.8).
108. Welding certification not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

109. Welders and welding operators not certified as specified (see 3.8.4.1).
110. Welding and welds not as specified (see 3.8.4.2).
111. Slinging, tiedown provisions not as specified (see 3.9 and 3.9.1).

Minor

201. All dimensions not designated major on the QAP not as specified (see 3.1.1).
202. Identification marking incorrect, missing, or illegible (see 3.4).
203. Treatment and painting not as specified (see 3.5).
204. Stenciling not as specified (see 3.6).
205. Preservation treatment and sealing not as specified (see 3.5.1).

4.5.2 Assembly test. Assemble the components into one complete saddle assembly. Interference of mating members or improper fits at joints shall constitute failure of this test.

4.5.3 Tiedown provisions test. The tiedown provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.9. Inability to meet the requirements of 3.9 shall constitute failure of this demonstration.

4.5.3.1 Slinging provisions test. The slinging provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.9.1. Inability to meet the requirements of 3.9 shall constitute failure of this demonstration.

4.6 Inspection of packaging.

4.6.1 First article pack inspection.

4.6.1.1 Examination. Examine the quality conformance pack for the defects specified in 4.6.2.3. Presence of one or more defects shall be cause for rejection.

4.6.1.2 Test. Subject the first article of crated items for level A or B to the railroad-impact test in accordance with appendix A to MIL-STD-1186. At the conclusion of the first article test, the pack shall be examined. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking or bracing, or any visible damage to the components shall constitute failure of the first article test and shall be cause for rejection.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following defects.

112.	Small loose components for each complete saddle assembly not packed in boxes as specified for level A or B (see 5.2.1.1.1).
113.	Saddle assemblies and components not packed together in quantities and crates not as specified for level A or B (see 5.2.1.1.2).
114.	Saddle assemblies with the boxed components not arranged on the crate base and not blocking, bracing, and anchoring as specified for level A or B (see 5.2.1.1.2).
115.	Saddle beam pin assembly not packed as specified for level A or B (see 5.2.1.2.1).
116.	Interior panel assemblies or end panel assemblies not packed together in quantities and crates not as specified for level A or B (see 5.2.1.2.2).
117.	Marking illegible, incorrect, incomplete, or missing (see 5.3).

5. PACKAGING

5.1 First article pack. The contractor shall furnish a first article pack for examination and test within the time frame specified (see 6.2), to prove prior to starting production packing, that the applied packing and marking comply with the packaging requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The first article pack may be prepared utilizing either the first article or a production unit. When the first article is utilized, any packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the first article and production units.

5.2 Packing. Packing shall be level A, B, or level C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 When complete saddle assemblies are procured.

5.2.1.1.1 Small loose components. Small loose components for each complete saddle assembly, such as pins and bridge pin retainers, shall be packed together in a close-fitting box conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. Strapping shall not be required.

5.2.1.1.2 Saddle assemblies. The unassembled saddle assemblies, with the packed small components comprised of three complete saddle assemblies, shall be packed in a crate conforming to MIL-C-3774, type II. The saddle assemblies with the boxed components shall be arranged on the crate base to provide maximum compactness and low center of gravity. Blocking, bracing, and anchoring of contents shall be provided and shall be in accordance with the appendix to the crate specification and MIL-STD-1186.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

5.2.1.2 When saddle assembly components are procured. When the saddle beam pin assembly, interior panel assembly, or end panel assembly is procured separately from the saddle assembly, it shall be packed as follows.

5.2.1.2.1 Saddle beam pin assembly. Pin assemblies shall be packed in close-fitting boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. Box closure shall be in accordance with the appendix to the box specification. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675.

5.2.1.2.2 Interior panel assembly and end panel assembly. Two end panel assemblies or four interior panel assemblies shall be packed together in a crate conforming to MIL-C-52950, type V, style A, class 1, or in a close-fitting box conforming to PPP-B-621, class 2, style 7, with hood. Blocking, bracing, and anchoring of the contents to prevent movement shall be provided and shall be in accordance with MIL-STD-1186. Strapping shall be as specified in 5.2.1.2.1.

5.2.2 Level B. Packing shall be as specified for level A except boxes shall be domestic type or class as applicable, and strapping may be zinc-coated.

5.2.3 Level C. Complete saddle assemblies or separately procured saddle assembly shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking specified in the contract or purchase order, marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The saddle assembly is intended to be used to support the roadway and superstructure of a floating bridge on pneumatic pontons.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Whether complete saddle assemblies or components are required (see 3.1).
d. When a first article is required for inspection and approval, and the number of units required (see 3.2, 4.3 and 6.3).
e. When Government-loaned property is not to be furnished and used for inspection (see 3.7 and 4.4.2.1).
f. Time frame required for submission of first article pack (see 5.1).
g. Level of packing required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:25Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article inspection is required, the item(s) should be a production model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results, and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test,

must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 First article pack. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the Government. Approval of the first article pack will not relieve the contractor of his obligation to pack, and mark the saddle assemblies in accordance with this specification.

6.5 Quality assurance provisions (QAP). The contracting officer should require the supplier to maintain record of all QAP inspections. A suggested paragraph is as follows:

"The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirements, actual measurements, number and type of deficiencies found, quantity approved, quantity rejected, and corrected action taken when applicable."

6.6 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Description (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/ provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DoD Far Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference paragraph	DID Number	DID Title
3.8.4.1	DI-MISC-80876	Welding Procedure Qualification Test Report.
3.8.4.1	DI-MISC-80875	Welding Procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.

6.7 Definitions.

6.7.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.8 Government-loaned property. The contracting officer should arrange to loan the property specified in 3.7, when applicable.

6.9 Subject term (key word) listings.

Bridge, floating
Bridge, ponton
Float, pneumatic
Floating bridge
Ponton bridge
Ponton, pneumatic
Saddle assembly, bridge
Saddle assembly, steel and plywood

6.10 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 5420-0171

Source: https://assist.dla.mil -- Downloaded: 202640-17T23:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-S-12840H	2. DOCUMENT DATE (YYMMDD) 921106

3. DOCUMENT TITLE
Saddle Assembly: Steel and Plywood, for 24-Ton, 2 Part Pneumatic Float, Ponton Bridge

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Geraldine F. Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3469 (2) AUTOVON 654-3468
c. ADDRESS (Include Zip Code US Army Belvoir RDE Center ATTN: SATBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:25Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:25Z
Check the source to verify that this is the current version before use.