INCH-POUND

MIL-A-70753 (AR)
AMENDMENT 1

28 January 1991

MILITARY SPECIFICATION

ADAPTERS, PALLET, WOODEN CONTAINER FOR 105MM AND 120MM TANK AMMUNITION

This amendment forms a part of Military Specification MIL-A-70753 (AR), dated 28 June 1988, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1: Delete:

"FEDERAL
TT-C-490 - Cleaning and .... Protective Coating".

PAGE 2

Delete: "MIL-STD-171 - Finishing of Metal and Wood Surfaces".

2.1.2 DRAWINGS Add:

"AC00000423 - Chemical Agent Resistant Coating (CARC) Finishing Requirements for Metal Pallets and/or Pallet Adapters".

PAGE 3

3.3.1 Delete in its entirety and substitute:

"3.3.1 Tensile strength of weld on ring and ring support assembly. The tensile strength of the weld shall sustain a vertical force of 2500 pounds minimum for a duration of 30 seconds minimum."

3.4 Delete in its entirety and substitute:

"3.4 Painted surface. The painted surfaces of the adapters shall comply with the requirements of drawing AC200000423."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:57Z
Check the source to verify that this is the current version before use.

3.6.1 Adapters. Add new sentence to the end of the paragraph:

"Weld splatter is permissible on non-load bearing surfaces provided it is firmly attached."

PAGE 4

3.6.2 Delete in its entirety and substitute:

"3.6.2 Paint coating. The finished coat shall cover all required surfaces and be continuous. Paint runs are permissible provided they are no more than three inches in length, solid and free from cracks and blisters. Excess thickness is acceptable in areas where multiple passes of the paint gun are required to obtain total coverage. Paint chips which expose primer or bare metal are acceptable provided they are not more than 0.25 inch in diameter and no more than two such paint chips on a pallet adapter. Scratches which expose primer or bare metal are permissible provided they are no more than 1.5 inches in length and no more than 10 inches total on a pallet adapter. Bare metal is permissible on contact surfaces and in areas inaccessible to paint."

PAGE 7

4.4.2.1:

Major 103: Delete and substitute: "103 Tensile strength of weld on ring and ring support assembly 100% 3.3.1 Test".

Add Major 105:

"105 Weld missing, incomplete or incorrect 1.0% 3.3 Visual".

Minor 202: Delete and substitute: "202 Protective coating thickness (total thickness minus primer thickness) see drawing AC200000423 and Note (b) below 1.0% 3.2 Gage".

Under Notes, add: "(b) The primer thickness shall be determined from a test panel."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 8140 - A816)

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:57Z
Check the source to verify that this is the currentversion before use.